

Recommendation for Space Data System Standards

ORBIT DATA MESSAGES

PROPOSED STANDARD

CCSDS 502.0.P-2.38

PINK BOOK
24 November 2018 DRAFT

AUTHORITY

Issue:	Proposed Standard, Issue 3
Date:	24 November 2018 DRAFT
Location:	Washington, DC, USA

This document has been approved for publication by the Management Council of the Consultative Committee for Space Data Systems (CCSDS) and represents the consensus technical agreement of the participating CCSDS Member Agencies. The procedure for review and authorization of CCSDS documents is detailed in the *Procedures Manual for the Consultative Committee for Space Data Systems*, and the record of Agency participation in the authorization of this document can be obtained from the CCSDS Secretariat at the address below.

This document is published and maintained by:

CCSDS Secretariat
Space Communications and Navigation Office, 7L70
Space Operations Mission Directorate
NASA Headquarters
Washington, DC 20546-0001, USA

STATEMENT OF INTENT

The Consultative Committee for Space Data Systems (CCSDS) is an organization officially established by the management of its members. The Committee meets periodically to address data systems problems that are common to all participants, and to formulate sound technical solutions to these problems. Inasmuch as participation in the CCSDS is completely voluntary, the results of Committee actions are termed **Recommended Standards** and are not considered binding on any Agency.

This **Recommended Standard** is issued by, and represents the consensus of, the CCSDS members. Endorsement of this **Recommendation** is entirely voluntary. Endorsement, however, indicates the following understandings:

- o Whenever a member establishes a CCSDS-related **standard**, this **standard** will be in accord with the relevant **Recommended Standard**. Establishing such a **standard** does not preclude other provisions which a member may develop.
- o Whenever a member establishes a CCSDS-related **standard**, that member will provide other CCSDS members with the following information:
 - The **standard** itself.
 - The anticipated date of initial operational capability.
 - The anticipated duration of operational service.
- o Specific service arrangements shall be made via memoranda of agreement. Neither this **Recommended Standard** nor any ensuing **standard** is a substitute for a memorandum of agreement.

No later than five years from its date of issuance, this **Recommended Standard** will be reviewed by the CCSDS to determine whether it should: (1) remain in effect without change; (2) be changed to reflect the impact of new technologies, new requirements, or new directions; or (3) be retired or canceled.

In those instances when a new version of a **Recommended Standard** is issued, existing CCSDS-related member standards and implementations are not negated or deemed to be non-CCSDS compatible. It is the responsibility of each member to determine when such standards or implementations are to be modified. Each member is, however, strongly encouraged to direct planning for its new standards and implementations towards the later version of the Recommended Standard.

FOREWORD

This document is a Recommended Standard for Orbit Data Messages (ODMs) and has been prepared by the Consultative Committee for Space Data Systems (CCSDS). The set of orbit data messages described in this Recommended Standard is the baseline concept for trajectory representation in data interchange applications that are cross-supported between Agencies of the CCSDS.

This Recommended Standard establishes a common framework and provides a common basis for the interchange of orbit and orbit-relevant data. It allows implementing organizations within each Agency to proceed coherently with the development of compatible derived standards for the flight and ground systems that are within their cognizance. Derived Agency standards may implement only a subset of the optional features allowed by the Recommended Standard and may incorporate features not addressed by this Recommended Standard.

Through the process of normal evolution, it is expected that expansion, deletion, or modification of this document may occur. This Recommended Standard is therefore subject to CCSDS document management and change control procedures, which are defined in the *Procedures Manual for the Consultative Committee for Space Data Systems*. Current versions of CCSDS documents are maintained at the CCSDS Web site:

<http://www.ccsds.org/>

Questions relating to the contents or status of this document should be addressed to the CCSDS Secretariat at the address indicated on page i.

At time of publication, the active Member and Observer Agencies of the CCSDS were:

Member Agencies

- Agenzia Spaziale Italiana (ASI)/Italy.
- British National Space Centre (BNSC)/United Kingdom.
- Canadian Space Agency (CSA)/Canada.
- Centre National d'Etudes Spatiales (CNES)/France.
- China National Space Administration (CNSA)/People's Republic of China.
- Deutsches Zentrum für Luft- und Raumfahrt e.V. (DLR)/Germany.
- European Space Agency (ESA)/Europe.
- Russian Federal Space Agency (RFSA)/Russian Federation.
- Instituto Nacional de Pesquisas Espaciais (INPE)/Brazil.
- Japan Aerospace Exploration Agency (JAXA)/Japan.
- National Aeronautics and Space Administration (NASA)/USA.

Observer Agencies

- Austrian Space Agency (ASA)/Austria.
- Belgian Federal Science Policy Office (BFSPPO)/Belgium.
- Central Research Institute of Machine Building (TsNIIMash)/Russian Federation.
- Centro Tecnico Aeroespacial (CTA)/Brazil.
- Chinese Academy of Sciences (CAS)/China.
- Chinese Academy of Space Technology (CAST)/China.
- Commonwealth Scientific and Industrial Research Organization (CSIRO)/Australia.
- CSIR Satellite Applications Centre (CSIR)/Republic of South Africa.
- Danish National Space Center (DNSC)/Denmark.
- European Organization for the Exploitation of Meteorological Satellites (EUMETSAT)/Europe.
- European Telecommunications Satellite Organization (EUTELSAT)/Europe.
- Geo-Informatics and Space Technology Development Agency (GISTDA)/Thailand.
- Hellenic National Space Committee (HNSC)/Greece.
- Indian Space Research Organization (ISRO)/India.
- Institute of Space Research (IKI)/Russian Federation.
- KFKI Research Institute for Particle & Nuclear Physics (KFKI)/Hungary.
- Korea Aerospace Research Institute (KARI)/Korea.
- Ministry of Communications (MOC)/Israel.
- National Institute of Information and Communications Technology (NICT)/Japan.
- National Oceanic and Atmospheric Administration (NOAA)/USA.
- National Space Organization (NSPO)/Chinese Taipei.
- Naval Center for Space Technology (NCST)/USA.
- Scientific and Technological Research Council of Turkey (TUBITAK)/Turkey.
- Space and Upper Atmosphere Research Commission (SUPARCO)/Pakistan.
- Swedish Space Corporation (SSC)/Sweden.
- United States Geological Survey (USGS)/USA.

DOCUMENT CONTROL

Document	Title	Date	Status
CCSDS 502.0-B-1	Orbit Data Messages, Issue 1	September 2004	Original issue, superseded
CCSDS 502.0.P-2.38	ORBIT DATA MESSAGES, Proposed Standard, Issue 3	24 November 2018 DRAFT	Current issue: – changes from the original issue are documented in ANNEX K
EC 1	Editorial Change 1		Corrects erroneous cross references and table of contents entries; corrects typographical anomaly in annex D; updates informative references to current issues in ANNEX K, Section K2
CCSDS 502.0.R-2, Cor. 1	Technical Corrigendum 1		Corrects/clarifies text; updates references [1] and [4] to current issues in 0.
CCSDS 502.0.P-2.38	Orbit Comprehensive Message SANA Registry for ODM Keyword values		Added Orbit Comprehensive Message (OCM) and transitioned ODM keyword values to SANA registry

CONTENTS

<u>Section</u>	<u>Page</u>
1 INTRODUCTION.....	1-1
1.1 PURPOSE AND SCOPE	1-1
1.2 APPLICABILITY	1-2
1.3 RATIONALE.....	1-2
1.4 DOCUMENT STRUCTURE	1-2
1.5 DEFINITIONS.....	1-3
1.6 NOMENCLATURE.....	1-3
1.7 REFERENCES.....	1-3
2 OVERVIEW.....	2-1
2.1 ORBIT DATA MESSAGE TYPES	2-1
2.2 ORBIT PARAMETER MESSAGE (OPM)	2-1
2.3 ORBIT MEAN-ELEMENTS MESSAGE (OMM).....	2-1
2.4 ORBIT EPHEMERIS MESSAGE (OEM)	2-2
2.5 ORBIT COMPREHENSIVE MESSAGE (OCM).....	2-2
2.6 EXCHANGE OF MULTIPLE MESSAGES.....	2-3
2.7 DEFINITIONS.....	2-3
3 ORBIT PARAMETER MESSAGE (OPM)	3-1
3.1 GENERAL	3-1
3.2 OPM CONTENT/STRUCTURE.....	3-1
3.3 OPM EXAMPLES AND SUPPLEMENTARY INFORMATION.....	3-7
4 ORBIT MEAN-ELEMENTS MESSAGE (OMM)	4-1
4.1 GENERAL.....	4-1
4.2 OMM CONTENT/STRUCTURE	4-1
4.3 OMM EXAMPLES AND SUPPLEMENTARY INFORMATION	4-9
5 ORBIT EPHEMERIS MESSAGE (OEM).....	5-1
5.1 GENERAL.....	5-1
5.2 OEM CONTENT/STRUCTURE	5-1
5.3 OEM EXAMPLES AND SUPPLEMENTARY INFORMATION	5-8
6 ORBIT COMPREHENSIVE MESSAGE (OCM)	6-1
6.1 GENERAL.....	6-1
6.2 OCM CONTENT/STRUCTURE	6-1
6.3 OCM EXAMPLES AND SUPPLEMENTARY INFORMATION	6-53
7 ORBIT DATA MESSAGE SYNTAX	7-0
7.1 OVERVIEW	7-0
7.2 GENERAL.....	7-0
7.3 ODM LINES	7-0
7.4 KEYWORD = VALUE NOTATION (I.E., NON-XML) AND ORDER OF ASSIGNMENT STATEMENTS.....	7-1
7.5 VALUES.....	7-2
7.6 UNITS IN THE ORBIT DATA MESSAGES.....	7-4
7.7 COMMENTS IN THE ORBIT DATA MESSAGES	7-5
7.8 ORBIT DATA MESSAGE KEYWORDS	7-7

8	CONSTRUCTING AN ODM/XML INSTANCE	8-9
8.1	OVERVIEW	8-9
8.2	XML VERSION.....	8-9
8.3	BEGINNING THE INSTANTIATION: ROOT ELEMENT TAG.....	8-9
8.4	THE STANDARD ODM/XML HEADER SECTION	8-10
8.5	THE ODM BODY SECTION.....	8-11
8.6	THE ODM METADATA SECTION	8-11
8.7	THE ODM DATA SECTION	8-11
8.8	CREATING AN OPM INSTANTIATION	8-11
8.9	CREATING AN OMM INSTANTIATION.....	8-14
8.10	CREATING AN OEM INSTANTIATION.....	8-16
8.11	CREATING AN OCM INSTANTIATION.....	8-19
ANNEX A IMPLEMENTATION CONFORMANCE STATEMENT PRO FORMA		
	(NORMATIVE).....	A-1
ANNEX B NORMATIVE VALUES AND REFERENCES FOR TIMING SYSTEM,		
REFERENCE FRAME, ORBITAL ELEMENT, AND COVARIANCE-		
	RELATED KEYWORDS (NORMATIVE).....	B-1
ANNEX C TECHNICAL MATERIAL (INFORMATIVE)		
		C-1
ANNEX D OPM EXAMPLES (INFORMATIVE)		
		D-8
ANNEX E OMM EXAMPLES (INFORMATIVE)		
		E-1
ANNEX F OEM EXAMPLES (INFORMATIVE).....		
		F-1
ANNEX G OCM EXAMPLES AND ASSOCIATED SUPPLEMENTARY		
	INFORMATION (INFORMATIVE).....	G-1
ANNEX H ABBREVIATIONS AND ACRONYMS (INFORMATIVE).....		
		H-1
ANNEX I RATIONALE FOR ORBIT DATA MESSAGES (INFORMATIVE).....		
		I-1
ANNEX J ITEMS FOR AN INTERFACE CONTROL DOCUMENT		
	(INFORMATIVE).....	J-1
ANNEX K CHANGES IN ODM VERSION 3 (INFORMATIVE)		
		K-1
ANNEX L L-1		
ANNEX M INFORMATIVE REFERENCES (INFORMATIVE)		
		M-1

Figure

No table of contents entries found.

Table

3-1	OPM HEADER	3-2
3-2	OPM METADATA	3-3
3-3	OPM DATA	3-5
4-1	OMM HEADER.....	4-2
4-2	OMM METADATA.....	4-4
4-3	OMM DATA.....	4-7
5-1	OEM FILE LAYOUT SPECIFICATIONS.....	5-2
5-2	OEM HEADER	5-3

CCSDS PROPOSED STANDARD FOR ORBIT DATA MESSAGES

5-3 OEM METADATA	5-4
6-1 OEM METADATA	6-3
6-2 OEM METADATA	6-4
6-3 OEM METADATA	6-7
6-4 OEM METADATA	6-15
6-5 OEM METADATA	6-18
6-6 OEM METADATA	6-24
6-7 OEM METADATA	6-28
6-8 OEM METADATA	6-32
6-9 OEM METADATA	6-33
6-10 OEM METADATA	6-37
6-11 OEM METADATA	6-44
6-12 OEM METADATA	6-49
6-13 OEM METADATA	6-53
8-1 NDM/XML ROOT ELEMENT TAGS.....	8-9

1 INTRODUCTION

1.1 PURPOSE AND SCOPE

This Orbit Data Message (ODM) Recommended Standard specifies four standard message formats for use in transferring spacecraft orbit information between space agencies and commercial or governmental spacecraft operators: the Orbit Parameter Message (OPM), the Orbit Mean-Elements Message (OMM), the Orbit Ephemeris Message (OEM) and the Orbit Comprehensive Message (OCM). Such exchanges are used for:

- a) pre-flight planning for tracking or navigation support;
- b) scheduling tracking support;
- c) carrying out tracking operations (sometimes called metric predicts);
- d) performing orbit comparisons;
- e) carrying out navigation operations such as orbit propagation and orbit reconstruction;
- f) assessing mutual physical and electromagnetic interference among satellites orbiting the same celestial body (currently primarily Earth, Moon, and Mars);
- g) performing orbit conjunction (collision avoidance) studies; and
- h) developing and executing collaborative maneuvers to mitigate interference or enhance mutual operations.

This Recommended Standard includes sets of requirements and criteria that the message formats have been designed to meet. For exchanges where these requirements do not capture the needs of the participating agencies and satellite operators, another mechanism may be selected.

The Orbit Data Message (ODM) is an international standard published under the auspices of CCSDS and International Standards Organization (ISO) Technical Committee 20, Subcommittee 13, developed jointly and in concert with the ISO TC20/SC14. As such, this CCSDS standard is also properly labeled as ISO 26900.

The recommended Orbit Data Message format is ASCII (reference [3]).

This ODM document describes both 'Keyword = Value Notation' (or KVN) as well as Extensible Markup Language (XML, reference [4]) formatted messages. Selection of KVN or XML format should be specified in an ICD.

NOTE – As currently specified, an OPM, OMM, or OEM file is to represent orbit data for a single spacecraft and the OCM is to represent orbit data for either a single spacecraft or single parent spacecraft of a parent/child spacecraft deployment scenario. It is possible that the architecture may support multiple spacecraft per file; this could be considered in the future.

1.2 APPLICABILITY

The rationale behind the design of each orbit data message is described in ANNEX I and may help the application engineer to select a suitable message. Definition of the orbit accuracy underlying a particular orbit message is outside of the scope of this Recommended Standard and should be specified via Interface Control Document (ICD) between data exchange participants (or specified via COMMENT sections in the message itself). Applicability information specific to each orbit data message format appears in sections 3, 4, and 5, as well as in I2.4.

This Recommended Standard is applicable only to the message format and content, but not to its transmission. The transmission of the message between agencies and operators is outside the scope of this document and should be specified in the ICD.

Description of the message formats based on the use of Extensible Markup Language (XML) is detailed in an integrated XML schema document for all Navigation Data Message Recommended Standards. (See reference [4].)

1.3 RATIONALE

This update to version 2 of the Orbit Data Messages adds a fourth message type (OCM) based on collaboration of the CCSDS Navigation Working Group and the ISO Technical Committee 20, Subcommittee 14, Working Group 3 (ISO TC20/SC14/WG3). A full list of the changes in this document is located in ANNEX K.

1.4 DOCUMENT STRUCTURE

Section 0 provides a brief overview of the CCSDS-recommended Orbit Data Message types, the Orbit Parameter Message (OPM), Orbit Mean-Elements Message (OMM), Orbit Ephemeris Message (OEM) and the Orbit Comprehensive Message (OCM).

Section 3 provides details about the structure and content of the OPM.

Section 4 provides details about the structure and content of the OMM.

Section 5 provides details about the structure and content of the OEM.

Section 6 provides details about the structure and content of the OCM.

Section 7 discusses the syntax considerations of the set of Orbit Data Messages (OPM, OMM, OEM and OCM).

Following the principal content of the document, there are a number of annexes, both normative and informative, to guide the ODM user.

1.5 DEFINITIONS

For the purposes of this document, the following definitions apply:

- a) the word ‘agencies’ may also be construed as meaning ‘satellite operators’ or ‘satellite service providers’;
- b) the word ‘participant’ denotes an entity that has the ability to acquire or broadcast navigation messages and/or radio frequencies, for example, a spacecraft, a tracking station, a tracking instrument, or an agency/operator;
- c) the notation ‘n/a’ signifies ‘not applicable’;
- d) depending on context, the term ‘ODM’ may be used to refer to this document, or may be used to refer collectively to the OPM, OMM, OEM and OCM messages.
- e) An ‘observation’ is a unique measurement set of a satellite’s state from a single sensor configuration at a single time (e.g. azimuth from a single sensor at a single time).
- f) A ‘sensor track’ is a set of observations **within NMINTRK minutes** for the same object, observed by the same sensor configuration, where each observation is within a specified number of minutes (which is dependent on the orbit regime of the object) of the other observations in the track (e.g. a set of 10 two-way transponder range measurements from the same sensor using the same transponder on the satellite), where the number of minutes could alternately be defined as the time between start and stop of the measurement “session” or signal modulation that enables metric tracking.

1.6 NOMENCLATURE

The following conventions apply for the normative specifications in this Manual:

- a) the words ‘shall’ and ‘must’ imply a binding and verifiable specification;
- b) the word ‘should’ implies an optional, but desirable, specification;
- c) the word ‘may’ implies an optional specification;
- d) the words ‘is’, ‘are’, and ‘will’ imply statements of fact.

NOTE – These conventions do not imply constraints on diction in text that is clearly informative in nature.

1.7 REFERENCES

The following documents contain provisions which, through reference in this text, constitute provisions of this Recommended Standard. At the time of publication, the editions indicated were valid. All documents are subject to revision, and users of this Recommended Standard are encouraged to investigate the possibility of applying the most recent editions of the

CCSDS PROPOSED STANDARD FOR ORBIT DATA MESSAGES

documents indicated below. The CCSDS Secretariat maintains a register of currently valid CCSDS Recommended Standards.

- [1] *Time Code Formats*. Recommendation for Space Data System Standards, CCSDS 301.0-B-4. Blue Book. Issue 4. Washington, D.C.: CCSDS, November 2010.
- [2] *United Nations Office of Outer Space Affairs satellite designator/index, searchable at* <<http://www.unoosa.org/oosa/osoindex> >
- [3] *Information Technology—8-Bit Single-Byte Coded Graphic Character Sets—Part 1: Latin Alphabet No. 1*. International Standard, ISO/IEC 8859-1:1998. Geneva: ISO, 1998.
- [4] *XML Specification for Navigation Data Messages*. Recommendation for Space Data System Standards, CCSDS 505.0-B-1. Blue Book. Issue 1. Washington, D.C.: CCSDS, December 2010.
- [5] Paul V. Biron and Ashok Malhotra, eds. *XML Schema Part 2: Datatypes*. 2nd Edition. W3C Recommendation. N.p.: W3C, October 2004. <<http://www.w3.org/TR/2001/REC-xmlschema-2-20010502/>>
- [6] *IEEE Standard for Binary Floating-Point Arithmetic*. IEEE Std 754-1985. New York: IEEE, 1985.
- [8] Henry S. Thompson, et al. eds. *XML Schema Part 1: Structures*. 2nd ed. W3C Recommendation. N.p.: W3C, October 2004.
- [9] CCSDS 503.0-P-1.0.4, Tracking Data Message, **January 2017**.
- [10] CCSDS 504.0-P-1.5, Attitude Data Message, **October 2017**.

2 OVERVIEW

2.1 ORBIT DATA MESSAGE TYPES

2.2 ORBIT PARAMETER MESSAGE (OPM)

An OPM specifies the position and velocity of a single object at a specified epoch. Optionally, osculating Keplerian elements may be provided. This message is suited to exchanges that (1) involve automated interaction and/or human interaction, and (2) do not require high-fidelity dynamic modeling.

The OPM requires the use of a propagation technique to determine the position and velocity at times different from the specified epoch, leading to a higher level of effort for software implementation than for the OEM. A 6x6 position/velocity covariance matrix that may be used in the propagation process is optional.

The OPM allows for modeling of any number of maneuvers (as both finite and instantaneous events) and simple modeling of solar radiation pressure and atmospheric drag.

The OPM also contains an optional covariance matrix which reflects the uncertainty of the orbit state.

Though primarily intended for use by computers, the attributes of the OPM also make it suitable for applications such as exchanges by email, FAX or voice, or applications where the message is to be frequently interpreted by humans.

2.3 ORBIT MEAN-ELEMENTS MESSAGE (OMM)

An OMM specifies the orbital characteristics of a single object at a specified epoch, expressed in mean Keplerian elements. This message is suited to exchanges that (1) involve automated interaction and/or human interaction, and (2) do not require high-fidelity dynamic modeling. Such exchanges may be inter-agency exchanges, or ad hoc exchanges among satellite operators when interface control documents have not been negotiated. Ad hoc interactions usually involve more than one satellite, each satellite controlled and operated by a different operating authority.

The OMM includes keywords and values that can be used to generate canonical NORAD Two Line Element Sets (TLEs) to accommodate the needs of heritage users (see reference [M-4]).

The OMM also contains an optional covariance matrix which reflects the uncertainty of the mean Keplerian elements. This information may be used to determine contact parameters that encompass uncertainties in predicted future states of orbiting objects of interest.

This message is suited for directing antennas and planning contacts with satellites. It is not recommended for assessing mutual physical or electromagnetic interference among Earth-orbiting spacecraft, developing collaborative maneuvers, or propagating precisely the orbits of

active satellites, inactive man-made objects, and near-Earth debris fragments. It is not suitable for numerical integration of the governing equations.

Though primarily intended for use by computers, the attributes of the OMM also make it suitable for applications such as exchanges by email, FAX or voice, or applications where the message is to be frequently interpreted by humans.

2.4 ORBIT EPHEMERIS MESSAGE (OEM)

An OEM specifies the position and velocity of a single object at multiple epochs contained within a specified time range. The OEM is suited to exchanges that (1) involve automated interaction (e.g., computer-to-computer communication where frequent, fast automated time interpretation and processing is required), and (2) require higher fidelity or higher precision dynamic modeling than is possible with the OPM.

The OEM allows for dynamic modeling of any number of gravitational and non-gravitational accelerations. The OEM requires the use of an interpolation technique to interpret the position and velocity at times different from the tabular epochs.

The OEM also contains an optional covariance matrix which reflects the uncertainty of the orbit solution used to generate states in the ephemeris.

2.5 ORBIT COMPREHENSIVE MESSAGE (OCM)

An OCM specifies position and velocity of either a single object or an en masse parent/child deployment scenario stemming from a single object. The OCM aggregates and extends OPM, OEM and OMM content in a single comprehensive hybrid message (file) and offers the following additional capabilities:

- Optional Earth Orientation (UT1 and UTC) at a nearby (relevant) reference epoch;
- Optional Leap second specification
- Optional area cross-sections for drag, SRP perturbations modeling.
- Optional spacecraft dimensions and orientation information for collision probability estimation
- Optional perturbations model specification;
- Optional maneuver specification (impulsive or finite burn);
- Optional orbit states (specified using one or more of Cartesian and orbit elements and reference frames) for a single or parent object at either a single epoch or as a time history (ephemeris);
- Optional orbit determination data and metrics;
- Optional covariance matrix of selectable/arbitrary order for a single or parent object at either a single epoch or as a time history (ephemeris) which reflects the uncertainty of the orbit solution or Monte Carlo simulation used to obtain the nominal states in the orbit state(s);
- Optional covariance content options (e.g. Cartesian 3x3, 6x6, 7x7, or any combination of order, reference frame and orbit elements)

- Optional State Transition Matrix specification;
- Optional Ephemeris Compression (EC) specification via polynomials;

The OCM simultaneously emphasizes flexibility and message conciseness by offering extensive optional content while minimizing mandatory content. The OCM is well-suited for exchanges that (1) involve automated interaction (e.g., computer-to-computer communication where frequent, fast automated time interpretation and processing is required), and (2) involve regular orbit data transfer for numerous objects (e.g. 200,000) using minimal network bandwidth, disk storage and quantity of files. The OCM allows the user, in a single message/file, to either embed high-fidelity orbit propagation into an ephemeris time history (akin to the OEM ephemeris), or specify orbital states which can be propagated with supplied perturbations model parameters (akin to OPM content), or both.

2.6 EXCHANGE OF MULTIPLE MESSAGES

For a given object, multiple OPM, OMM, or OEM messages may be provided in a message exchange session to achieve ephemeris fidelity requirements, whereas a single, self-contained OCM is typically sufficient. If ephemeris information for multiple objects is to be exchanged, then multiple OPM, OMM, OEM or OCM files must be used, with the exception that the OCM supports parent/child deployment scenario specifications in a single message.

2.7 DEFINITIONS

Definitions of time systems, reference frames, planetary models, maneuvers and other fundamental topics related to the interpretation and processing of state vectors and spacecraft ephemerides are provided in reference [M-1].

3 ORBIT PARAMETER MESSAGE (OPM)

3.1 GENERAL

3.1.1 Orbit information may be exchanged between two participants by sending a state vector (see reference [M-1]) for a specified epoch using an Orbit Parameter Message (OPM). The message recipient must have an orbit propagator available that is able to propagate the OPM state vector to compute the orbit at other desired epochs. For this propagation, additional ancillary information (spacecraft properties such as mass, area, and maneuver planning data, if applicable) may be included with the message.

3.1.2 Osculating Keplerian elements and Gravitational Coefficient may be included in the OPM in addition to the Cartesian state to aid the message recipient in performing consistency checks. If any Keplerian element is included, the entire set of elements must be provided.

3.1.3 If participants wish to exchange mean element information, then the Orbit Mean-Elements Message (OMM) or Orbit Comprehensive Message (OCM) should be the selected message type. (See sections 4 and 6.)

3.1.4 The use of the OPM is best applicable under the following conditions:

- a) an orbit propagator consistent with the models used to develop the orbit data should be available at the receiver's site;
- b) the receiver's modeling of gravitational forces, solar radiation pressure, atmospheric drag, and thrust phases (see reference [M-1]) should fulfill accuracy requirements established between the exchange partners.

3.1.5 The OPM shall be a plain text file consisting of orbit data for a single object.

3.1.6 The OPM file-naming scheme should be agreed to on a case-by-case basis between the exchange partners, and should be documented in an ICD. The method of exchanging OPMs should be decided on a case-by-case basis by the exchange partners and documented in an ICD.

NOTE – Detailed syntax rules for the OPM are specified in section 7.

3.2 OPM CONTENT/STRUCTURE

3.2.1 GENERAL

The OPM shall be represented as a combination of the following:

- a) a header;
- b) metadata (data about data);
- c) data; and
- d) optional comments (explanatory information).

3.2.2 OPM HEADER

3.2.2.1 Table 3-1 specifies for each header item:

- a) the keyword to be used;
- b) a short description of the item;
- c) examples of allowed values; and
- d) whether the item is mandatory or optional.

3.2.2.2 Only those keywords shown in table 3-1 shall be used in an OPM header.

Table 3-1: OPM Header

Keyword	Description	Examples of Values	Mandatory
CCSDS_OPM_VERS	Format version in the form of 'x.y', where 'y' is incremented for corrections and minor changes, and 'x' is incremented for major changes.	2.0	Yes
COMMENT	Comments (allowed in the OPM Header only immediately after the OPM version number). (See 7.7 for formatting rules.)	COMMENT This is a comment	No
CREATION_DATE	File creation date/time in UTC. (For format specification, see 7.5.10)	2001-11-06T11:17:33 2002-204T15:56:23Z	Yes
ORIGINATOR	Creating agency or operator. Select from the accepted set of values indicated in ANNEX B, Section B1 (and note the procedure to propose a new value, if this set of existing ANNEX B values does not accommodate your particular use case).	CNES, ESOC, GSFC, GSOC, JPL, JAXA, INTELSAT, USAF, INMARSAT	Yes

3.2.3 OPM METADATA

Table 3-2 specifies for each metadata item:

- a) the keyword to be used;
- b) a short description of the item;
- c) examples of allowed values; and
- d) whether the item is mandatory or optional.

3.2.3.1 Only those keywords shown in table 3-2 shall be used in OPM metadata.

NOTE – For some keywords (OBJECT_NAME, OBJECT_ID) there are no definitive lists of authorized values maintained by a control authority; the references listed in 1.7 are the best known sources for authorized values to date. For the TIME_SYSTEM and REF_FRAME keywords, see ANNEX B, Section B3 and Section B4 respectively, for guidance and a link to the approved set of values.

CCSDS PROPOSED STANDARD FOR ORBIT DATA MESSAGES

Table 3-2: OPM Metadata

Keyword	Description	Examples of Values	Mandatory
COMMENT	Comments (allowed at the beginning of the OPM Metadata). (See 7.7 for formatting rules.)	COMMENT This is a comment	No
MESSAGE_ID	ID that uniquely identifies a message from a given originator. The format and content of the message identifier value are at the discretion of the originator.	OPM 201113719185 ABC-12_34	No
MESSAGE_CLASSIF	User-defined free-text classification of this OCM	FOUO	No
OBJECT_NAME	Spacecraft name for which the orbit state is provided. While there is no CCSDS-based restriction on the value for this keyword, it is recommended to use names from the UN Office of Outer Space Affairs designator index (reference Error! Reference source not found.), which include Object name and international designator of the participant.	EUTELSAT W1 MARS PATHFINDER STS 106 NEAR	Yes
OBJECT_ID	Object identifier of the object for which the orbit state is provided. There is no CCSDS-based restriction on the value for this keyword, but it is recommended that values be the international spacecraft designator as published in the UN Office of Outer Space Affairs designator index (reference Error! Reference source not found.). Recommended values have the format YYYY-NNNP{PP}, where: YYYY = Year of launch. NNN = Three digit serial number of launch in year YYYY (with leading zeros). P{PP} = At least one letter for the identification of the part brought into space by the launch. In cases where the asset is not listed in the UN Office of Outer Space Affairs designator index or that index format is not used, OBJECT_ID terminology should be mutually agreed in an ICD.	2000-052A 1996-068A 2000-053A 1996-008A	Yes
CENTER_NAME	Origin of reference frame, which may be a natural solar system body (planets, asteroids, comets, and natural satellites), including any planet barycenter or the solar system barycenter, or another spacecraft. Select from the accepted set of values indicated in ANNEX B, Section B2 (and note the procedure to propose a new value, if this set of existing ANNEX B values does not accommodate your particular use case).	EARTH EARTH BARYCENTER MOON SOLAR SYSTEM BARYCENTER SUN JUPITER BARYCENTER EROS	Yes

CCSDS PROPOSED STANDARD FOR ORBIT DATA MESSAGES

Keyword	Description	Examples of Values	Mandatory
REF_FRAME	Reference frame in which the state vector and optional Keplerian element data are given. Select from the accepted set of values indicated in ANNEX B, Section B4 (and note the procedure to propose a new value, if this set of existing ANNEX B values does not accommodate your particular use case).	ICRF1 ITRF2000 J2000	Yes
REF_FRAME_EPOCH	Epoch of reference frame, if not intrinsic to the definition of the reference frame. (See 7.5.10 for formatting rules.)	2001-11-06T11:17:33 2002-204T15:56:23Z	No
TIME_SYSTEM	Time system used for state vector, maneuver, and covariance data (also see table 3-3). Select from the accepted set of values indicated in ANNEX B, Section B3 (and note the procedure to propose a new value, if this set of existing ANNEX B values does not accommodate your particular use case).	UTC, TAI, TT, GPS, TDB, TCB	Yes

3.2.4 OPM DATA

3.2.4.1 Table 3-3 provides an overview of the six logical blocks in the OPM Data section (State Vector, Osculating Keplerian Elements, Spacecraft Parameters, Position/Velocity Covariance Matrix, Maneuver Parameters, and User Defined Parameters), and specifies for each data item:

- a) the keyword to be used;
- b) a short description of the item;
- c) the units to be used;
- d) whether the item is mandatory or optional.

3.2.4.2 Only those keywords shown in table 3-3 shall be used in OPM data.

NOTE – Requirements relating to the keywords in table 3-3 appear after the table.

Table 3-3: OPM Data

Keyword	Description	Units	Mandatory
State Vector Components in the Specified Coordinate System			
COMMENT	(See 7.7 for formatting rules.)	n/a	No
EPOCH	Epoch of state vector & optional Keplerian elements. (See 7.5.10 for formatting rules.)	n/a	Yes
X	Position vector X-component	km	Yes
Y	Position vector Y-component	km	Yes
Z	Position vector Z-component	km	Yes
X_DOT	Velocity vector X-component	km/s	Yes
Y_DOT	Velocity vector Y-component	km/s	Yes
Z_DOT	Velocity vector Z-component	km/s	Yes
Osculating Keplerian Elements in the Specified Reference Frame (none or all parameters of this block must be given.)			
COMMENT	(See 7.7 for formatting rules.)	n/a	No
SEMI_MAJOR_AXIS	Semi-major axis	km	No
ECCENTRICITY	Eccentricity	n/a	No
INCLINATION	Inclination	deg	No
RA_OF_ASC_NODE	Right ascension of ascending node	deg	No
ARG_OF_PERICENTER	Argument of pericenter	deg	No
TRUE_ANOMALY or MEAN_ANOMALY	True anomaly or mean anomaly	deg	No
GM	Gravitational Coefficient (Gravitational Constant x Central Mass)	km**3/s**2	No
Spacecraft Parameters			
COMMENT	(See 7.7 for formatting rules.)	n/a	No
MASS	S/C Mass	kg	No
SOLAR_RAD_AREA	Solar Radiation Pressure Area (A _R)	m**2	No
SOLAR_RAD_COEFF	Solar Radiation Pressure Coefficient (C _R)	n/a	No
DRAG_AREA	Drag Area (A _D)	m**2	No
DRAG_COEFF	Drag Coefficient (C _D)	n/a	No
Position/Velocity Covariance Matrix (6x6 Lower Triangular Form. None or all parameters of the matrix must be given. COV_REF_FRAME may be omitted if it is the same as REF_FRAME.)			
COMMENT	(See 7.7 for formatting rules.)	n/a	No
COV_REF_FRAME	Reference frame in which the covariance data are given. Select from the accepted set of values indicated in ANNEX B, Sections B4 and B5 (and note the procedure to propose a new value, if this set of existing ANNEX B values does not accommodate your particular use case).	ICRF3 ITRF2000 TOD_EARTH	No
CX_X	Covariance matrix [1,1]	km**2	No
CY_X	Covariance matrix [2,1]	km**2	No
CY_Y	Covariance matrix [2,2]	km**2	No
CZ_X	Covariance matrix [3,1]	km**2	No
CZ_Y	Covariance matrix [3,2]	km**2	No
CZ_Z	Covariance matrix [3,3]	km**2	No
CX_DOT_X	Covariance matrix [4,1]	km**2/s	No
CX_DOT_Y	Covariance matrix [4,2]	km**2/s	No
CX_DOT_Z	Covariance matrix [4,3]	km**2/s	No
CX_DOT_X_DOT	Covariance matrix [4,4]	km**2/s**2	No

CCSDS PROPOSED STANDARD FOR ORBIT DATA MESSAGES

Keyword	Description	Units	Mandatory
CY_DOT_X	Covariance matrix [5,1]	km**2/s	No
CY_DOT_Y	Covariance matrix [5,2]	km**2/s	No
CY_DOT_Z	Covariance matrix [5,3]	km**2/s	No
CY_DOT_X_DOT	Covariance matrix [5,4]	km**2/s**2	No
CY_DOT_Y_DOT	Covariance matrix [5,5]	km**2/s**2	No
CZ_DOT_X	Covariance matrix [6,1]	km**2/s	No
CZ_DOT_Y	Covariance matrix [6,2]	km**2/s	No
CZ_DOT_Z	Covariance matrix [6,3]	km**2/s	No
CZ_DOT_X_DOT	Covariance matrix [6,4]	km**2/s**2	No
CZ_DOT_Y_DOT	Covariance matrix [6,5]	km**2/s**2	No
CZ_DOT_Z_DOT	Covariance matrix [6,6]	km**2/s**2	No
Maneuver Parameters (Repeat for each maneuver. None or all parameters of this block must be given.)			
COMMENT	(See 7.7 for formatting rules.)	n/a	No
MAN_EPOCH_IGNITION	Epoch of ignition. (See 7.5.10 for formatting rules.)	n/a	No
MAN_DURATION	Maneuver duration (If = 0, impulsive maneuver)	s	No
MAN_DELTA_MASS	Mass change during maneuver (value is < 0)	kg	No
MAN_REF_FRAME	Reference frame in which the velocity increment vector data are given. Select from the accepted set of values indicated in ANNEX B, Sections B4 and B5 (and note the procedure to propose a new value, if this set of existing ANNEX B values does not accommodate your particular use case).	n/a	No
MAN_DV_1	1 st component of the velocity increment	m/s	No
MAN_DV_2	2 nd component of the velocity increment	m/s	No
MAN_DV_3	3 rd component of the velocity increment	m/s	No
User Defined Parameters (all parameters in this section must be described in an ICD).			
USER_DEFINED_x	User defined parameter, where 'x' is replaced by a variable length user specified character string. Any number of user defined parameters may be included, if necessary to provide essential information that cannot be conveyed in COMMENT statements. Example: USER_DEFINED_EARTH_MODEL = WGS-84	n/a	No

3.2.4.3 All values except Maneuver Parameters in the OPM data are 'at epoch', i.e., the value of the parameter at the time specified in the EPOCH keyword.

3.2.4.4 Table 3-3 is broken into six logical blocks, each of which has a descriptive heading. These descriptive headings shall not be included in an OPM, unless they appear in a properly formatted COMMENT statement.

3.2.4.5 If the solar radiation coefficient, C_R , is set to zero, no solar radiation pressure shall be taken into account.

3.2.4.6 If the atmospheric drag coefficient, C_D , is set to zero, no atmospheric drag shall be taken into account.

3.2.4.7 Parameters for thrust phases may be optionally given for the computation of the trajectory during or after maneuver execution (see reference [M-1] for the simplified modeling of such maneuvers). For impulsive maneuvers, MAN_DURATION must be set to zero.

MAN_DELTA_MASS may be used for both finite and impulsive maneuvers; the value must be a negative number.

3.2.4.8 Multiple sets of maneuver parameters may appear. For each maneuver, all the maneuver parameters shall be repeated in the order shown in table 3-3.

3.2.4.9 If the OPM contains a maneuver definition, the Spacecraft Parameters section must be included.

3.2.4.10 Values in the covariance matrix shall be expressed in the applicable reference frame (COV_REF_FRAME keyword), and shall be presented sequentially from upper left [1,1] to lower right [6,6], lower triangular form, row by row left to right. Variance and covariance values shall be expressed in standard double precision as related in 7.5. This logical block of the OPM may be useful for risk assessment and establishing maneuver and mission margins. The intent is to provide causal connections between output orbit data and both physical hypotheses and measurement uncertainties. These causal relationships guide operators' corrective actions and mitigations.

3.2.4.11 A section of User Defined Parameters may be provided if necessary. In principle, this provides flexibility, but also introduces complexity, non-standardization, potential ambiguity, and potential processing errors. Accordingly, if used, the keywords and their meanings must be described in an ICD. User Defined Parameters, if included in an OPM, should be used as sparingly as possible; their use is not encouraged.

3.3 OPM EXAMPLES AND SUPPLEMENTARY INFORMATION

Example OPMs and associated supplementary (non-normative) information are provided in Annex E.

4 ORBIT MEAN-ELEMENTS MESSAGE (OMM)

4.1 GENERAL

4.1.1 Orbit information may be exchanged between two participants by sending an orbital state based on mean Keplerian elements (see reference [M-1]) for a specified epoch using an Orbit Mean-Elements Message (OMM). The message recipient must use appropriate orbit propagator algorithms in order to correctly propagate the OMM state to compute the orbit at other desired epochs.

4.1.2 The OMM is intended to allow replication of the data content of an existing TLE in a CCSDS standard format, but the message can also accommodate other implementations of mean elements. All essential fields of the 'de facto standard' TLE are included in the OMM in a style that is consistent with that of the other ODMs (i.e., the OPM and OEM). From the fields in the OMM, it is possible to generate a TLE (see reference [M-3]). Programs that convert OMMs to TLEs must be aware of the structural requirements of the TLE, including the checksum algorithm and the formatting requirements for the values in the TLE. The checksum and formatting requirements of the TLE do not apply to the values in an OMM.

4.1.3 If participants wish to exchange osculating element information, then the Orbit Parameter Message (OPM) or the Orbit Comprehensive Message (OCM) should be the selected message type. (See sections 3 and 6.)

4.1.4 The use of the OMM is best applicable under the following conditions:

- a) an orbit propagator consistent with the models used to develop the orbit data should be run at the receiver's site;
- b) the receiver's modeling of gravitational forces, solar radiation pressure, atmospheric drag, etc. (see reference [M-1]), should fulfill accuracy requirements established between the exchange partners.

4.1.5 The OMM shall be a plain text file consisting of orbit data for a single object.

4.1.6 The OMM file-naming scheme should be agreed to on a case-by-case basis between the exchange partners, and should be documented in an ICD. The method of exchanging OMMs should be decided on a case-by-case basis by the exchange partners and documented in an ICD.

NOTE – Detailed syntax rules for the OMM are specified in section 7.

4.2 OMM CONTENT/STRUCTURE

4.2.1 GENERAL

The OMM shall be represented as a combination of the following:

- a) a header;

- b) metadata (data about data);
- c) data; and
- d) optional comments (explanatory information).

4.2.2 OMM HEADER

4.2.2.1 Table 4-1 specifies for each header item:

- a) the keyword to be used;
- b) a short description of the item;
- c) examples of allowed values; and
- d) whether the item is mandatory or optional.

4.2.2.2 Only those keywords shown in table 4-1 shall be used in an OMM header.

Table 4-1: OMM Header

Keyword	Description	Examples of Values	Mandatory
CCSDS_OMM_VERS	Format version in the form of 'x.y', where 'y' is incremented for corrections and minor changes, and 'x' is incremented for major changes.	3.0	Yes
COMMENT	Comments (allowed in the OMM Header only immediately after the OMM version number). (See 7.7 for formatting rules.)	COMMENT This is a comment	No
CREATION_DATE	File creation date/time in UTC. (For format specification, see 7.5.10.)	2001-11-06T11:17:33 2002-204T15:56:23Z	Yes
ORIGINATOR	Creating agency or operator. Select from the accepted set of values indicated in ANNEX B, Section B1 (and note the procedure to propose a new value, if this set of existing ANNEX B values does not accommodate your particular use case).	CNES, ESOC, GSFC, GSOC, JPL, JAXA, INTELSAT, USAF, INMARSAT	Yes

4.2.3 OMM METADATA


4.2.3.1 Table 4-2 specifies for each metadata item:

- a) the keyword to be used;
- b) a short description of the item;
- c) examples of allowed values; and
- d) whether the item is mandatory or optional.

4.2.3.2 Only those keywords shown in table 4-2 shall be used in OMM metadata.

NOTE – For some keywords (OBJECT_NAME and OBJECT_ID there are no definitive lists of authorized values maintained by a control authority; the references listed in 1.7 are the best known sources for authorized values to date.

Table 4-2: OMM Metadata



CCSDS PROPOSED STANDARD FOR ORBIT DATA MESSAGES

Keyword	Description	Examples of Values	Mandatory
COMMENT	Comments (allowed at the beginning of the OMM Metadata). (See 7.7 for formatting rules.)	COMMENT This is a comment	No
MESSAGE_ID	ID that uniquely identifies a message from a given originator. The format and content of the message identifier value are at the discretion of the originator.	OMM 201113719185 ABC-12_34	No
MESSAGE_CLASSIF	User-defined free-text classification of this OCM	FOUO	No
OBJECT_NAME	Spacecraft name for which the orbit state is provided. There is no CCSDS-based restriction on the value for this keyword, but it is recommended to use names from the UN Office of Outer Space Affairs designator index (reference [2]), which include Object name and international designator of the participant.	TelKom 2 Spaceway 2 INMARSAT 4-F2	Yes
OBJECT_ID	Object identifier of the object for which the orbit state is provided. There is no CCSDS-based restriction on the value for this keyword, but it is recommended that values be the international spacecraft designator as published in the UN Office of Outer Space Affairs designator index (reference [2]). Recommended values have the format YYYY-NNNP{PP}, where: YYYY = Year of launch. NNN = Three digit serial number of launch in year YYYY (with leading zeros). P{PP} = At least one capital letter for the identification of the part brought into space by the launch. In cases where the asset is not listed in the bulletin, or the UN Office of Outer Space Affairs designator index format is not used, the value should be provided in an ICD.	2005-046A 2005-046B 2003-022A	Yes
CENTER_NAME	Origin of reference frame, which may be a natural solar system body (planets, asteroids, comets, and natural satellites), including any planet barycenter or the solar system barycenter, or another spacecraft. Select from the accepted set of values indicated in ANNEX B, Section B2 (and note the procedure to propose a new value, if this set of existing ANNEX B values does not accommodate your particular use case).	EARTH MARS MOON	Yes

CCSDS PROPOSED STANDARD FOR ORBIT DATA MESSAGES

REF_FRAME	Name of the reference frame in which the Keplerian element data are given. Select from the accepted set of values indicated in ANNEX B, Section B4 (and note the procedure to propose a new value, if this set of existing ANNEX B values does not accommodate your particular use case). Note: NORAD Two Line Element Sets and corresponding SGP orbit propagator ephemeris output are explicitly defined to be in the True Equator Mean Equinox of Date (TEME of Date) reference frame. Therefore, TEME of date shall be used for OMMs based on NORAD Two Line Element sets, rather than the almost imperceptibly different TEME of Epoch (see reference [M-3] or [M-4] for further details).	TEME J2000	Yes
REF_FRAME_EPOCH	Epoch of reference frame, if not intrinsic to the definition of the reference frame. (See 7.5.10 for formatting rules.)	2001-11-06T11:17:33 2002-204T15:56:23Z	No
TIME_SYSTEM	Time system used for the orbit state and covariance matrix. Select from the accepted set of values indicated in ANNEX B, Section B3 (and note the procedure to propose a new value, if this set of existing ANNEX B values does not accommodate your particular use case).	UTC	Yes
MEAN_ELEMENT_THEORY	Description of the Mean Element Theory. Indicates the proper method to employ to propagate the state.	SGP4 DSST USM	Yes

4.2.4 OMM DATA

4.2.4.1 Table 4-3 provides an overview of the five logical blocks in the OMM Data section (Mean Keplerian Elements, Spacecraft Parameters, TLE Related Parameters, Position/Velocity Covariance Matrix, and User Defined Parameters), and specifies for each data item:

- a) the keyword to be used;
- b) a short description of the item;
- c) the units to be used;
- d) whether the item is mandatory or optional.

4.2.4.2 Only those keywords shown in table 4-3 shall be used in OMM data.

NOTE – Requirements relating to the keywords in table 4-3 appear after the table.

Table 4-3: OMM Data

Keyword	Description	Units	Mandatory
Mean Keplerian Elements in the Specified Reference Frame			
COMMENT	(See 7.7 for formatting rules.)	n/a	No
EPOCH	Epoch of Mean Keplerian elements. (See 7.5.10 for formatting rules.)	n/a	Yes
SEMI_MAJOR_AXIS or MEAN_MOTION	Semi-major axis in kilometers (preferred), or, if MEAN_ELEMENT_THEORY = SGP/SGP4, the Keplerian Mean motion in revolutions per day	km rev/day	Yes
ECCENTRICITY	Eccentricity	n/a	Yes
INCLINATION	Inclination	deg	Yes
RA_OF_ASC_NODE	Right ascension of ascending node	deg	Yes
ARG_OF_PERICENTER	Argument of pericenter	deg	Yes
MEAN_ANOMALY	Mean anomaly	deg	Yes
GM	Gravitational Coefficient (Gravitational Constant x Central Mass)	km**3/s**2	No
Spacecraft Parameters			
COMMENT	(See 7.7 for formatting rules.)	n/a	No
MASS	S/C Mass	kg	No
SOLAR_RAD_AREA	Solar Radiation Pressure Area (A_R)	m**2	No
SOLAR_RAD_COEFF	Solar Radiation Pressure Coefficient (C_R)	n/a	No
DRAG_AREA	Drag Area (A_D)	m**2	No
DRAG_COEFF	Drag Coefficient (C_D)	n/a	No
TLE Related Parameters (This section is only required if MEAN_ELEMENT_THEORY=SGP/SGP4)			
COMMENT	(See 7.7 for formatting rules.)	n/a	No
EPHEMERIS_TYPE	Default value = 0. (See 4.2.4.7.)	n/a	No
CLASSIFICATION_TYPE	Default value = U. (See 4.2.4.7.)	n/a	No
NORAD_CAT_ID	NORAD Catalog Number ('Satellite Number') an integer of up to nine digits. This keyword is only required if MEAN_ELEMENT_THEORY=SGP/SGP4.	n/a	No
ELEMENT_SET_NO	Element set number for this satellite. Normally incremented sequentially, but may be out of sync if it is generated from a backup source. Used to distinguish different TLEs, and therefore only meaningful if TLE-based data is being exchanged (i.e., MEAN_ELEMENT_THEORY = SGP/SGP4).	n/a	No
REV_AT_EPOCH	Revolution Number	n/a	No
BSTAR	SGP/SGP4 drag-like coefficient (in units 1/[Earth radii]). Only required if MEAN_ELEMENT_THEORY=SGP/SGP4	1/ER	No
MEAN_MOTION_DOT	First Time Derivative of the Mean Motion (only required if MEAN_ELEMENT_THEORY = SGP)	rev/day**2	No
MEAN_MOTION_DDOT	Second Time Derivative of Mean Motion (only required if MEAN_ELEMENT_THEORY = SGP)	rev/day**3	No

CCSDS PROPOSED STANDARD FOR ORBIT DATA MESSAGES

Keyword	Description	Units	Mandatory
Position/Velocity Covariance Matrix (6x6 Lower Triangular Form. None or all parameters of the matrix must be given. COV_REF_FRAME may be omitted if it is the same as the REF_FRAME.)			
COMMENT	(See 7.7 for formatting rules.)	n/a	No
COV_REF_FRAME	Reference frame in which the covariance data are given. Select from the accepted set of values indicated in ANNEX B, Sections B4 and B5 (and note the procedure to propose a new value, if this set of existing ANNEX B values does not accommodate your particular use case).	n/a	No
CX_X	Covariance matrix [1,1]	km**2	No
CY_X	Covariance matrix [2,1]	km**2	No
CY_Y	Covariance matrix [2,2]	km**2	No
CZ_X	Covariance matrix [3,1]	km**2	No
CZ_Y	Covariance matrix [3,2]	km**2	No
CZ_Z	Covariance matrix [3,3]	km**2	No
CX_DOT_X	Covariance matrix [4,1]	km**2/s	No
CX_DOT_Y	Covariance matrix [4,2]	km**2/s	No
CX_DOT_Z	Covariance matrix [4,3]	km**2/s	No
CX_DOT_X_DOT	Covariance matrix [4,4]	km**2/s**2	No
CY_DOT_X	Covariance matrix [5,1]	km**2/s	No
CY_DOT_Y	Covariance matrix [5,2]	km**2/s	No
CY_DOT_Z	Covariance matrix [5,3]	km**2/s	No
CY_DOT_X_DOT	Covariance matrix [5,4]	km**2/s**2	No
CY_DOT_Y_DOT	Covariance matrix [5,5]	km**2/s**2	No
CZ_DOT_X	Covariance matrix [6,1]	km**2/s	No
CZ_DOT_Y	Covariance matrix [6,2]	km**2/s	No
CZ_DOT_Z	Covariance matrix [6,3]	km**2/s	No
CZ_DOT_X_DOT	Covariance matrix [6,4]	km**2/s**2	No
CZ_DOT_Y_DOT	Covariance matrix [6,5]	km**2/s**2	No
CZ_DOT_Z_DOT	Covariance matrix [6,6]	km**2/s**2	No
User Defined Parameters (all parameters in this section must be described in an ICD).			
USER_DEFINED_x	User defined parameter, where 'x' is replaced by a variable length user specified character string. Any number of user defined parameters may be included, if necessary to provide essential information that cannot be conveyed in COMMENT statements. Example: USER_DEFINED_EARTH_MODEL = WGS-84	n/a	No

4.2.4.3 All values in the OMM are 'at epoch', i.e., the value of the parameter at the time specified in the EPOCH keyword.

4.2.4.4 Table 4-3 is broken into five logical blocks, each of which has a descriptive heading. These descriptive headings shall not be included in an OMM, unless they appear in a properly formatted COMMENT statement.

4.2.4.5 Values in the covariance matrix shall be expressed in the applicable reference frame (COV_REF_FRAME keyword if used, or REF_FRAME keyword if not), and shall be presented sequentially from upper left [1,1] to lower right [6,6], lower triangular form, row by row left to right. Variance and covariance values shall be expressed in standard double

precision as related in 7.5. This logical block of the OMM may be useful for risk assessment and establishing maneuver and mission margins.

4.2.4.6 For operations in Earth orbit with a TLE-based OMM, some special conventions must be observed, as follows:

- The value associated with the CENTER_NAME keyword shall be 'EARTH'.
- The value associated with the REF_FRAME keyword shall be 'TEMEOFDATE' (see ANNEX B, Section B4).
- The value associated with the TIME_SYSTEM keyword shall be 'UTC'.
- The format of the OBJECT_NAME and OBJECT_ID keywords shall be that of the UN Office of Outer Space Affairs designator index (reference [2]).
- The MEAN_MOTION keyword must be used instead of SEMI_MAJOR_AXIS.

4.2.4.7 For those who wish to use the OMM to represent a TLE, there are a number of considerations that apply with respect to precision of angle representation, use of certain fields by the propagator, reference frame, etc. Some sources suggest the coding for the EPHEMERIS_TYPE keyword: 1=SGP, 2=SGP4, 3=SDP4, 4=SGP8, 5=SDP8. Some sources suggest the following coding for the CLASSIFICATION_TYPE keyword: U=unclassified, S=secret. (For further information see references [M-3] and [M-4])

4.2.4.8 Maneuvers are not accommodated in the OMM. Users of the OMM who wish to model maneuvers may use several OMM files to describe the orbit at applicable epochs.

4.2.4.9 A section of User Defined Parameters is allowed. In principle, this provides flexibility, but also introduces complexity, non-standardization, potential ambiguity, and potential processing errors. Accordingly, if used, the keywords and their meanings must be described in an ICD. User Defined Parameters, if included in an OMM, should be used as sparingly as possible; their use is not encouraged.

4.3 OMM EXAMPLES AND SUPPLEMENTARY INFORMATION

Example OMMs and associated supplementary (non-normative) information are provided in Annex F.

5 ORBIT EPHEMERIS MESSAGE (OEM)

5.1 GENERAL

5.1.1 Orbit information may be exchanged between two participants by sending an ephemeris in the form of a series of state vectors (Cartesian vectors providing position and velocity, and optionally accelerations) using an Orbit Ephemeris Message (OEM). The message recipient must have a means of interpolating across these state vectors to obtain the state at an arbitrary time contained within the span of the ephemeris.

5.1.2 The OEM may be used for assessing mutual physical or electromagnetic interference among Earth-orbiting spacecraft, developing collaborative maneuvers, and representing the orbits of active satellites, inactive man-made objects, near-Earth debris fragments, etc. The OEM reflects the dynamic modeling of any users' approach to conservative and non-conservative phenomena.

5.1.3 The OEM shall be a plain text file consisting of orbit data for a single object.

5.1.4 The OEM file-naming scheme should be agreed to on a case-by-case basis between the participants, typically using an ICD. The method of exchanging OEMs should be decided on a case-by-case basis by the participants and documented in an ICD.

NOTE – Detailed syntax rules for the OEM are specified in section 7.

5.2 OEM CONTENT/STRUCTURE

5.2.1 GENERAL

5.2.1.1 The OEM shall be represented as a combination of the following:

- a) a header;
- b) metadata (data about data);
- c) ephemeris data;
- d) optional covariance matrix data; and
- e) optional comments (explanatory information).

5.2.1.2 OEM files must have a set of minimum required sections; some may be repeated. Table 5-1 outlines the contents of an OEM.

Table 5-1: OEM File Layout Specifications

Required Sections	Header Metadata Ephemeris Data (Appropriate comments should also be included, although they are not required.)
Allowable Repetitions of Sections	Covariance Matrix (optional) Metadata Ephemeris Data Covariance Matrix (optional) Metadata Ephemeris Data Covariance Matrix (optional) Metadata Ephemeris Data Covariance Matrix (optional) ...etc. (Appropriate comments should also be included.)

5.2.2 OEM HEADER

5.2.2.1 The OEM header assignments are shown in table 5-2, which specifies for each item:

- a) the keyword to be used;
- b) a short description of the item;
- c) examples of allowed values; and
- d) whether the item is mandatory or optional.

5.2.2.2 Only those keywords shown in table 5-2 shall be used in an OEM header.

Table 5-2: OEM Header

Keyword	Description	Examples of Values	Mandatory
CCSDS_OEM_VERS	Format version in the form of 'x.y', where 'y' is incremented for corrections and minor changes, and 'x' is incremented for major changes.	3.0	Yes
COMMENT	Comments (allowed in the OEM Header only immediately after the OEM version number). (See 7.7 for formatting rules.)	COMMENT This is a comment	No
CREATION_DATE	File creation date and time in UTC. (For format specification, see 7.5.10.)	2001-11-06T11:17:33 2002-204T15:56:23	Yes
ORIGINATOR	Creating agency or operator. Select from the accepted set of values indicated in ANNEX B, Section B1 (and note the procedure to propose a new value, if this set of existing ANNEX B values does not accommodate your particular use case).	CNES, ESOC, GSFC, GSOC, JPL, JAXA, INTELSAT, USAF, INMARSAT	Yes

5.2.3 OEM METADATA

5.2.3.1 The OEM metadata assignments are shown in table 5-3, which specifies for each item:


- a) the keyword to be used;
- b) a short description of the item;
- c) examples of allowed values; and
- d) whether the item is mandatory or optional.

5.2.3.2 Only those keywords shown in table 5-3 shall be used in OEM metadata.

NOTE – For some keywords (OBJECT_NAME and OBJECT_ID) there are no definitive lists of authorized values maintained by a control authority; the references listed in 1.7 are the best known sources for authorized values to date. For the TIME_SYSTEM and REF_FRAME keywords, see ANNEX B, Section B3 and Section B4 respectively, for guidance and a link to the approved set of values.

5.2.3.3 A single metadata group shall precede each ephemeris data block. Multiple occurrences of a metadata group followed by an ephemeris data block may be used. Before each metadata group the string 'META_START' shall appear on a separate line and after each metadata group (and before the associated ephemeris data block) the string 'META_STOP' shall appear on a separate line.

Table 5-3: OEM Metadata



CCSDS PROPOSED STANDARD FOR ORBIT DATA MESSAGES

Keyword	Description	Examples of Values	Mandatory
META_START	The OEM message contains metadata, ephemeris data, and covariance data; this keyword is used to delineate the start of a metadata block within the message (metadata are provided in a block, surrounded by 'META_START' and 'META_STOP' markers to facilitate file parsing). This keyword must appear on a line by itself.	n/a	Yes
COMMENT	Comments allowed only immediately after the META_START keyword. (See 7.7 for formatting rules.)	COMMENT This is a comment.	No
MESSAGE_ID	ID that uniquely identifies a message from a given originator. The format and content of the message identifier value are at the discretion of the originator.	OEM 201113719185 ABC-12_34	No
MESSAGE_CLASSIF	User-defined free-text classification of this OCM	FOUO	No
OBJECT_NAME	The name of the object for which the ephemeris is provided. There is no CCSDS-based restriction on the value for this keyword, but it is recommended to use names from the UN Office of Outer Space Affairs designator index (reference [2]), which include Object name and international designator of the participant.	EUTELSAT W1 MARS PATHFINDER STS 106 NEAR	Yes
OBJECT_ID	Object identifier of the object for which the ephemeris is provided. There is no CCSDS-based restriction on the value for this keyword, but it is recommended that values be the international spacecraft designator as published in the UN Office of Outer Space Affairs designator index (reference [2]). Recommended values have the format YYYY-NNNP{PP}, where: YYYY = Year of launch. NNN = Three-digit serial number of launch in year YYYY (with leading zeros). P{PP} = At least one capital letter for the identification of the part brought into space by the launch. In cases where the asset is not listed in reference [2], or the UN Office of Outer Space Affairs designator index format is not used, the value should be provided in an ICD.	2000-052A 1996-068A 2000-053A 1996-008A	Yes
CENTER_NAME	Origin of reference frame, which may be a natural solar system body (planets, asteroids, comets, and natural satellites), including any planet barycenter or the solar system barycenter, or another spacecraft. Select from the accepted set of values indicated in ANNEX B, Section B2 (and note the procedure to propose a new value, if this set of existing ANNEX B values does not accommodate your particular use case).	EARTH EARTH BARYCENTER MOON SOLAR SYSTEM BARYCENTER SUN JUPITER BARYCENTER STS 106 EROS	Yes

CCSDS PROPOSED STANDARD FOR ORBIT DATA MESSAGES

Keyword	Description	Examples of Values	Mandatory
REF_FRAME	Reference frame in which the ephemeris data are given. Select from the accepted set of values indicated in ANNEX B, Section B4 (and note the procedure to propose a new value, if this set of existing ANNEX B values does not accommodate your particular use case).	ICRF3 ITRF1993 ITRF1997 ITRF2000 ITRFyyyy (template for future versions) TOD (True Equator and Equinox of Date) J2000 (Earth Mean Equator and Equinox of J2000) TDR (true of date rotating) GRC (Greenwich rotating coordinate frame, another name for TDR)	Yes
REF_FRAME_EPOCH	Epoch of reference frame, if not intrinsic to the definition of the reference frame. (See 7.5.10 for formatting rules.)	2001-11-06T11:17:33 2002-204T15:56:23Z	No
TIME_SYSTEM	Time system used for metadata, ephemeris and covariance data (also see table 3-3). Select from the accepted set of values indicated in ANNEX B, Section B3 (and note the procedure to propose a new value, if this set of existing ANNEX B values does not accommodate your particular use case).	UTC, TAI, TT, GPS, TDB, TCB	Yes
START_TIME	Start of TOTAL time span covered by ephemeris data and covariance data immediately following this metadata block. (For format specification, see 7.5.10.)	1996-12-18T14:28:15.1172 1996-277T07:22:54	Yes
USEABLE_START_TIME USEABLE_STOP_TIME	Optional start and end of USEABLE time span covered by ephemeris data immediately following this metadata block. To allow for proper interpolation near the ends of the ephemeris data block it may be necessary, depending upon the interpolation method to be used, to utilize these keywords with values within the time span covered by the ephemeris data records as delimited by the START/STOP_TIME time tags. (For format specification, see 7.5.10.) These keywords are optional items, and thus may not be necessary, depending on the recommended interpolation method. However, it is recommended to use the USEABLE_START_TIME and USEABLE_STOP_TIME capability in all cases. The USEABLE_START_TIME time tag at a new block of ephemeris data must be greater than or equal to the USEABLE_STOP_TIME time tag of the previous block.	1996-12-18T14:28:15.1172 1996-277T07:22:54	No
STOP_TIME	End of TOTAL time span covered by ephemeris data and covariance data immediately following this metadata block. (For format specification, see 7.5.10.)	1996-12-18T14:28:15.1172 1996-277T07:22:54	Yes

CCSDS PROPOSED STANDARD FOR ORBIT DATA MESSAGES

Keyword	Description	Examples of Values	Mandatory
INTERPOLATION	This keyword may be used to specify the recommended interpolation method for ephemeris data in the immediately following set of ephemeris lines.	HERMITE LINEAR LAGRANGE PROPAGATE	No
INTERPOLATION_DEGREE	Recommended interpolation degree for ephemeris data in the immediately following set of ephemeris lines. Must be an integer value. This keyword must be used if the 'INTERPOLATION' keyword is used and set to anything other than PROPAGATE.	5 1	No
META_STOP	The OEM message contains metadata, ephemeris data, and covariance data; this keyword is used to delineate the end of a metadata block within the message (metadata are provided in a block, surrounded by 'META_START' and 'META_STOP' markers to facilitate file parsing). This keyword must appear on a line by itself.	n/a	Yes

5.2.4 OEM DATA: EPHEMERIS DATA LINES

5.2.4.1 Each set of ephemeris data, including the time tag, must be provided on a single line. The order in which data items are given shall be fixed: **Epoch, X, Y, Z, X_DOT, Y_DOT, Z_DOT, X_DDOT, Y_DDOT, Z_DDOT**.

5.2.4.2 The position and velocity terms shall be mandatory; acceleration terms may be provided.

5.2.4.3 At least one space character must be used to separate the items in each ephemeris data line.

5.2.4.4 Repeated time tags may occur in consecutive ephemeris data blocks if the STOP_TIME of the first ephemeris data block is greater than the START_TIME of the second ephemeris data block. Although the USEABLE_STOP_TIME and USEABLE_START_TIME of the consecutive ephemeris data blocks must not overlap (except for a possibly shared endpoint), the STOP_TIME of the first ephemeris data block may be greater than the START_TIME of the second ephemeris data block if the extra data is required for interpolation purposes.

5.2.4.5 The TIME_SYSTEM value must remain fixed within an OEM.

5.2.4.6 The occurrence of a second (or greater) metadata block after some ephemeris data indicates that interpolation using succeeding ephemeris data with ephemeris data occurring prior to that metadata block shall not be done. This method may be used for proper modeling of propulsive maneuvers or any other source of a discontinuity such as eclipse entry or exit.

5.2.4.7 Details about interpolation method should be specified using the INTERPOLATION and INTERPOLATION_DEGREE keywords within the OEM. All data blocks must contain

a sufficient number of ephemeris data records to allow the recommended interpolation method to be carried out consistently throughout the OEM.

5.2.5 OEM DATA: COVARIANCE MATRIX LINES

5.2.5.1 A single covariance matrix data section may optionally follow each ephemeris data block.

5.2.5.2 If present, the covariance matrix data lines in the OEM are separated from the ephemeris data by means of two new keywords: `COV_START` and `COVARIANCE_STOP`. The '`COV_START`' keyword must appear before the first line of the covariance matrix data. The '`COVARIANCE_STOP`' keyword must appear after the last line of covariance data. Each of these keywords shall appear on a line by itself with no time tags or values.

5.2.5.3 The epoch of the navigation solution related to the covariance matrix must be provided via the '`EPOCH`' keyword. The reference frame of the covariance matrix, if different from that of the states in the ephemeris, must be provided via the '`COV_REF_FRAME`' keyword.

5.2.5.4 Each row of the 6x6 lower triangular covariance matrix must be provided on a single line. The order in which data items are given shall be fixed. The elements in each row of covariates shall be defined by the order in the ephemeris data line (i.e., **X, Y, Z, X_DOT, Y_DOT, Z_DOT**). The six rows of the covariance matrix contain from one to six numbers depending on what row of the matrix is being represented (first row has one element, second row has two, continuing in this fashion until the sixth row has six elements).

5.2.5.5 At least one space character must be used to separate the items in each covariance matrix data line.

5.2.5.6 Multiple covariance matrices may appear in the covariance matrix section; they may appear with any desired frequency (one for each navigation solution that makes up the overall ephemeris is recommended). The OEM may also contain propagated covariances, not just individual covariances associated with navigation solutions.

5.2.5.7 If there are multiple covariance matrices in the data section, they must be ordered by increasing time tag.

5.3 OEM EXAMPLES AND SUPPLEMENTARY INFORMATION

Example OEMs and associated supplementary (non-normative) information are provided in Annex G.

6 ORBIT COMPREHENSIVE MESSAGE (OCM)

6.1 GENERAL

6.1.1 Comprehensive orbit information may be exchanged between two participants by sending orbit data/content for one or more epochs using an Orbit Comprehensive Message (OCM). The OCM aggregates and extends OMM, OPM and OEM content in a single hybrid message. The OCM simultaneously emphasizes flexibility and message conciseness by offering extensive optional standardized content while minimizing mandatory content.

6.1.2 The OCM shall be a plain text file consisting of orbit data for a single space object, or in the case of a parent/child satellite deployment scenario, a single parent object.

6.1.3 The units universally used throughout the OCM are kilometers (for orbit state and covariance time histories) and m/s and m/s^2 (for maneuvers), mass in kilograms and time in seconds.

6.1.4 The OCM file-naming scheme should be agreed to on a case-by-case basis between the exchange partners, and should be documented in an ICD. The method of exchanging OCMs should be decided on a case-by-case basis by the exchange partners and documented in an ICD.

6.1.5 Orbit information may be exchanged between two or more participants by sending an ephemeris in the form of one or more time series of orbital states (selectable as orbital elements and/or Cartesian vectors providing position and optionally velocity and accelerations) using an Orbit Comprehensive Message (OCM). If orbital states are desired at arbitrary time(s) contained within the span of the ephemeris, the message recipient is encouraged to use a suitable interpolation method. For times outside of supplied orbit state time spans or if the step size between orbit states is too large to support interpolation [M-8], optional perturbations parameters can and should be included in this message and the recipient must have a suitably-compatible orbit propagator.

6.1.6 The OCM may be used for assessing mutual physical or electromagnetic interference among Earth-orbiting spacecraft, developing collaborative maneuvers, and representing the orbits of active satellites, inactive man-made objects, near-Earth debris fragments, etc. The OCM reflects the dynamic modeling of any users' approach to conservative and non-conservative phenomena.

NOTE – Detailed syntax rules for the OCM are specified in section 7.

6.2 OCM CONTENT/STRUCTURE

6.2.1 GENERAL

The OCM shall be represented as a combination of the following as shown in Table 6-1. The ordering of these sections is mandatory. The order of occurrence of the OCM sections shall be fixed as shown in table 6-1.

CCSDS PROPOSED STANDARD FOR ORBIT DATA MESSAGES

- 1) one mandatory header;
- 2) one mandatory metadata section (data about data);
- 3) optional data section(s), comprised of one or more data constituent types:
 - a. one or more optional orbit state time histories
 - b. one optional space object physical characteristics section
 - c. one or more optional covariance time histories
 - d. one or more optional State Transition Matrix (STM) time histories
 - e. one or more optional maneuver data section(s)
 - f. one optional perturbations section
 - g. one optional orbit determination data section
 - h. one optional user-defined section containing data and supplemental comments (explanatory information).

Table 6-1: OCM File Layout and Ordering Specification

Section	Content
Mandatory Header	Header of message
Mandatory Metadata	Metadata (Informational comments recommended but not required.)
Optional Orbit Data Section(s)	Optional: One or more orbit state time histories (each consisting of one or more orbit states)
Optional Space Object Physical Description	Optional space object physical characteristics.
Optional Covariance Data Section(s)	Optional: One or more covariance time histories (each consisting of one or more covariance matrices)
Optional State Transition Matrix Data Section(s)	Optional: One or more state transition matrix time histories (each consisting of one or more state transition matrices)
Optional Maneuver Section(s)	Optional maneuver specifications for either impulsive or finite burns or acceleration profiles
Optional Perturbations Section	Optional perturbations parameters
Optional Orbit Determination Section	Optional orbit determination data section
Optional user-defined parameters	Optional: One or more user-defined parameters

6.2.2 OCM HEADER

6.2.2.1 Table 6-2 specifies the keywords for each header item.

6.2.2.2 Only those keywords shown in table 6-2 shall be used in an OCM header.

6.2.2.3 The order of occurrence of these OCM header keywords shall be fixed as shown in table 6-2.

Table 6-2: OCM Header

Keyword	Description	Examples of Values	Mandatory
CCSDS_OCM_VERS	Format version in the form of 'x.y', where 'y' is incremented for corrections and minor changes, and 'x' is incremented for major changes.	3.0	Yes
COMMENT	Comments (a contiguous set of one or more comment lines are allowed in the OCM Header only immediately after the OCM version number). (See 7.7 for formatting rules.)	COMMENT This is a comment	No
CREATION_DATE	File creation date/time in UTC. (For format specification, see 7.5.10.)	2001-11-06T11:17:33 2002-204T15:56:23Z	Yes

6.2.3 OCM METADATA

6.2.3.1 Table 6-3 specifies the metadata keywords. Only those keywords shown in table 6-3 shall be used in OCM metadata.

6.2.3.2 The "OCM Metadata" section is mandatory; "mandatory" in the context of Table 6-3 denotes those keywords which must be included in this section.

6.2.3.3 Each metadata section must begin with keyword META_START and end with keyword META_STOP.

6.2.3.4 Each of these keywords shall appear on a line by itself.

6.2.3.5 At most, only one metadata section shall appear in the entire scope of an OCM.

NOTE – For some keywords (OBJECT_NAME, OBJECT_ID) there are no definitive lists of authorized values maintained by a control authority; the references listed in Section 1.7 are the best known sources for authorized values to date.

NOTE 2 – While specification of OBJECT_NAME, OBJECT_ID and INTERNATIONAL_DESIGNATOR are individually optional, it is recommended that one of these three keywords be supplied.

NOTE 3 – Metadata fields which are relied upon by the subsequent optional OCM message subtypes (orbit state time histories, maneuver data, etc.) are designated as such in the right-hand column of Table 6-3.

6.2.3.6 The order of occurrence of these OCM metadata keywords shall be fixed as shown in table 6-3.

6.2.3.7 When selecting a value for the OBJECT_TYPE keyword, note that per [M-17], objects in the space environment can be categorized in two broad categories: The ones which can be traced back to a launch event and for which the nature can be identified, and the ones for which this is not (yet) possible. With these two major categories in mind, when OBJECT_TYPE is specified, it shall categorize objects into one of the following nine categories:

- **PL:** A payload, which is a space object that is designed to perform specific function in space excluding launch functionality. This includes operational satellites as well as calibration objects.
- **PM:** A payload mission-related object, which is a space object that is released as space debris, which served a purpose for the function of a payload. Common examples include covers for optical instruments or astronaut tools.
- **PF:** A payload fragmentation debris, which is a space object that is fragmented or unintentionally released from a payload as space debris for which their genesis can be traced back to a unique event. This class includes objects created when a payload explodes or when it collides with another object.
- **PD:** Payload debris, which is a space object that is fragmented or unintentionally released from a payload as space debris for which the genesis is unclear but orbital or physical properties enable a correlation with a source.
- **RB:** Rocket body, which is a space object that is designed to perform launch related functionality. This includes the various orbital stages of launch vehicles, but not payloads that release smaller payloads themselves.
- **RM:** Rocket mission related object, which is a space object that is intentionally released as space debris that served a purpose for the function of a rocket body. Common examples include shrouds and engines.
- **RF:** Rocket fragmentation debris, which is a space object that is fragmented or unintentionally released from a rocket body as space debris for which their genesis can be traced back to a unique event. This class includes objects created when a launch vehicle explodes.
- **RD:** Rocket debris, which is a space object that is fragmented or unintentionally released from a rocket body as space debris for which the genesis is unclear but orbital or physical properties enable a correlation with a source.
- **UI:** Unidentified, where a space object cannot be traced back to a launch, its nature cannot be determined, or it is intentionally unspecified by the message creator.

6.2.3.8 When selecting a value for the ORBIT_TYPE keyword, [M-17], orbits shall be characterized as follows:

- **EGO:** Extended Geostationary Orbit, $37948 < a < 46380$ km, $e < 0.25$, $i < 25^\circ$
- **ESO:** Escape Orbits
- **GHO:** GEO-superGEO, Crossing Orbits $31570 < hp < 40002$ km, 40002 km $< ha$
- **GEO:** Geosynchronous Earth Orbit, with $i > 3^\circ$, $35586 < hp < 35986$ km, $35586 < ha < 35986$ km

CCSDS PROPOSED STANDARD FOR ORBIT DATA MESSAGES

- **GSO:** GeoStationary Orbit, with $3^\circ < i < 25^\circ$, $35586 < hp < 35986$ km, $35586 < ha < 35986$ km
- **GTO:** Geosynchronous Transfer Orbit, $i < 90^\circ$, $hp < 2000$ km, $31570 < ha < 40002$ km
- **HAO:** High Altitude Earth Orbit, 40002 km $< hp$, 40002 km $< ha$
- **HEO:** Highly Eccentric Earth Orbit, $hp < 31570$ km, 40002 km $< ha$
- **IGO:** Inclined Geosynchronous Orbit, $37948 < a < 46380$ km, $e < 0.25$, $25^\circ < i < 180^\circ$
- **LEO:** Low Earth Orbit, $hp < 2000$ km, $ha < 2000$ km
- **LMO:** LEO-MEO Crossing Orbits, $hp < 2000$ km, $2000 < ha < 31570$ km
- **MEO:** Medium Earth Orbit, $2000 < hp < 31570$ km, $2000 < ha < 31570$ km
- **MGO:** MEO-GEO Crossing Orbits, $2000 < hp < 31570$ km, $31570 < ha < 40002$ km
- **NSO:** Navigation Satellites Orbit $50^\circ < i < 70^\circ$, $18100 < hp < 24300$ km, $18100 < ha < 24300$ km
- **UFO:** Undefined Orbit

Table 6-3: OCM Metadata

Keyword	Description	Default (if any)	Examples of Values	Mandatory	Any OCM sections relying upon this field ?
COMMENT	Comments (a contiguous set of one or more comment lines are allowed in the OCM Metadata section; see 7.7 for comment formatting rules).	n/a	COMMENT This is a comment	No	No
ORIGINATOR	Creating agency or operator. Select from the accepted set of values indicated in ANNEX B, Section B1 (and note the procedure to propose a new value, if this set of existing ANNEX B values does not accommodate your particular use case).		CNES, ESOC, GSFC, GSOC, JPL, JAXA, INTELSAT, USAF, INMARSAT	Yes	No
ORIGINATOR_POC	Free text field containing originator or programmatic Point-of-Contact (PoC) for OCM		Mr. Rodgers	No	No
ORIGINATOR_POSITION	Free text field containing contact position of the originator PoC		Flight Dynamics Mission Design Lead	No	No
ORIGINATOR_PHONE	Free text field containing originator PoC phone number		+49615130312	No	No
ORIGINATOR_ADDRESS	Free text field containing originator PoC address information for OCM creator (suggest email, website, or physical address, etc.)		JOHN.DOE@ SOMEWHERE.NET	No	No
TECH_ORG	Creating agency or operator (value should be drawn from the abbreviated "Organizations" name column of the SANA registry at https://www.sanaregistry.org/r/organizations)		NASA	No	No
TECH_POC	Free text field containing technical Point-of-Contact (PoC) for OCM		Maxwell Smart	No	No
TECH_POSITION	Free text field containing contact position of the technical PoC		Flight Dynamics Mission Design Lead	No	No
TECH_PHONE	Free text field containing technical PoC phone number		+49615130312	No	No
TECH_ADDRESS	Free text field containing technical PoC address information for OCM creator (suggest email, website, or physical address, etc.)		JOHN.DOE@ SOMEWHERE.NET	No	No
MESSAGE_ID	Free text field containing an ID that uniquely identifies a message from this message originator. The format and content of the message identifier value are at the discretion of the originator.		OCM 201113719185 ABC-12_34	No	No
PREV_MESSAGE_ID	Free text field containing an ID that uniquely identifies the previous message from this message originator for this particular space object. The format and content of the message identifier value are at the discretion of the originator.		OCM 201113719184 ABC-12_33	No	No

CCSDS PROPOSED STANDARD FOR ORBIT DATA MESSAGES

Keyword	Description	Default (if any)	Examples of Values	Mandatory	Any OCM sections relying upon this field ?
NEXT_MESSAGE_ID	Free text field containing an ID that uniquely identifies the next message from this message originator for this particular space object. The format and content of the message identifier value are at the discretion of the originator.		OCM 201113719186 ABC-12_35	No	No
PREV_MESSAGE_EPOCH	Creation epoch of the previous message from this originator for this particular space object. For format specification, see 7.5.9. The time scale of this epoch is controlled via the "DEF_TIME_SYSTEM" keyword.		2001-11-06T11:17:33	No	No
NEXT_MESSAGE_EPOCH	Creation epoch of the next message from this originator for this particular space object. The format and content of the message identifier value are at the discretion of the originator.		2001-11-06T11:17:33	No	No
MESSAGE_CLASSIF	User-defined free-text classification of this OCM		FOUO	No	No
ATT_MSG_LINK	Free text field containing comma-separated file name(s) of Attitude Data Message(s) that are linked (relevant) to this Orbit Data Message		ADM_MSG_35132.txt	No	No
CDM_MSG_LINK	Free text field containing comma-separated file name(s) of Conjunction Data Message(s) that are linked (relevant) to this Orbit Data Message		CDM_MSG_35132.txt	No	No
PRM_MSG_LINK	Free text field containing comma-separated file name(s) of Pointing Request Message(s) that are linked (relevant) to this Orbit Data Message		PRM_MSG_35132.txt	No	No
RDM_MSG_LINK	Free text field containing comma-separated file name(s) of Reentry Data Message(s) that are linked (relevant) to this Orbit Data Message		RDM_MSG_35132.txt	No	No
TDM_MSG_LINK	Free text field containing comma-separated file name(s) of Tracking Data Message(s) that are linked (relevant) to this Orbit Data Message		TDM_MSG_35132.txt	No	No
OBJECT_NAME	Free text field containing the spacecraft name for the object. There is no CCSDS-based restriction on the value for this keyword, but it is recommended to use names from the UN Office of Outer Space Affairs designator index (reference [2]), which include Object name and international designator of the participant.		SPOT ENVISAT IRIDIUM INTELSAT UNKNOWN	No	No

CCSDS PROPOSED STANDARD FOR ORBIT DATA MESSAGES

Keyword	Description	Default (if any)	Examples of Values	Mandatory	Any OCM sections relying upon this field ?
INTERNATIONAL_DESIGNATOR	Free text field containing an international designator for the object as assigned by the UN Committee on Space Research (COSPAR) and the US National Space Science Data Center (NSSDC). Such designator values have the following COSPAR format: YYYY-NNNP{PP}, where: YYYY = Year of launch. NNN = Three digit serial number of launch in year YYYY (with leading zeros). P{PP} = At least one capital letter for the identification of the part brought into space by the launch. In cases where the object has no international designator, the value UNKNOWN may be used.		2000-052A 1996-068A 2000-053A 1996-008A UNKNOWN	No	No
OBJECT_ID	Free text field containing the satellite designator for the object.		22444 UNKNOWN	No	No
OPERATOR	Free text field containing the operator of the space object		INTELSAT	No	No
OWNER	Free text field containing the owner of the space object		SIRIUS	No	No
MISSION	Free text field containing the name of the space object's mission (which other space objects may also be a part of)		EOS	No	No
CONSTELLATION	Free text field containing the name of the constellation to which this space object belongs		SPIRE	No	No
LAUNCH_EPOCH	Epoch of initial launch, specified in the DEF_TIME_SYSTEM time system. See 7.5.10 for formatting rules.		2011-11-06T11:17:33	No	No
LAUNCH_COUNTRY	Free text field containing the name of the launch country.		FRANCE	No	No
LAUNCH_SITE	Free text field containing the name of the launch site.		USAF EASTERN TEST RANGE FRENCH GUIANA	No	No
LAUNCH_PROVIDER	Free text field specifying the name of the launch provider		ULA	No	No
LAUNCH_INTEGRATOR	Free text field specifying the name of the launch integrator		NASA	No	No
LAUNCH_PAD	Free text field containing the name of the launch pad.		LC-41	No	No
LAUNCH_PLATFORM	Free text field containing the name of the launch platform or source.		AIRCRAFT GROUND SUBMARINE SHIP SATELLITE MOBILE_GROUND_TRANSPORT	No	No

CCSDS PROPOSED STANDARD FOR ORBIT DATA MESSAGES

Keyword	Description	Default (if any)	Examples of Values	Mandatory	Any OCM sections relying upon this field ?
RELEASE_EPOCH	Epoch of most recent deployment of this space object in the parent/child deployment sequence, specified in the DEF_TIME_SYSTEM time system. See 7.5.10 for formatting rules.		2051-11-06T11:17:33	No	No
MISSION_START_EPOCH	Epoch of the beginning of mission operations, specified in the DEF_TIME_SYSTEM time system. See 7.5.10 for formatting rules.		2051-11-06T11:17:33	No	No
MISSION_END_EPOCH	Epoch of the cessation of mission operations, specified in the DEF_TIME_SYSTEM time system. See 7.5.10 for formatting rules.		2051-11-06T11:17:33	No	No
REENTRY_EPOCH	Epoch of the actual (historical) or estimated (future) reentry of this space object, specified in the DEF_TIME_SYSTEM time system. See 7.5.10 for formatting rules.		2051-11-06T11:17:33	No	No
LIFETIME	Estimated remaining orbit lifetime this space object measured in days from DEF_EPOCH_TZERO.		22.0	No	No
CATALOG_NAME	Specification of the satellite catalog source (or source agency or operator, value to be drawn from the abbreviated "Organizations" name column of the SANA registry at https://www.sanaregistry.org/r/organizations) from which the international designator and catalog ID were obtained. This is a free-text field.	CSPOC	CSPOC RFSA ESA COMSPOC	No	No
OBJECT_TYPE	Specification of the type of object, confined to the values listed above in 6.2.3.5.		PL RB RD	No	No
OPS_STATUS	Operational status of the space object: OPERATIONAL NONOPERATIONAL PARTIALLY_OPERATIONAL BACKUP STANDBY EXTENDED_MISSION REENTRY_MODE DECAYED UNKNOWN "Active" space objects include OPERATIONAL, PARTIALLY_OPERATIONAL, BACKUP, STANDBY, and EXTENDED_MISSION.		OPERATIONAL	No	No
ORBIT_TYPE	Specification of the type of orbit, confined to the values listed above in 6.2.3.6.		EGO LEO	No	No

CCSDS PROPOSED STANDARD FOR ORBIT DATA MESSAGES

Keyword	Description	Default (if any)	Examples of Values	Mandatory	Any OCM sections relying upon this field ?
OCM_DATA_ELEMENTS	Free text field containing a comma-delimited list of elements of information data blocks included in this message.		ORB, PHYSCHAR, MNVR, COV, OD, PERTS, STM, USER	No	No
DEF_EPOCH_TZERO	Default epoch to which all relative times are referenced in data blocks, unless overridden by block-specific EPOCH_TZERO values (For format specification, see 7.5.9.). The time scale of DEF_EPOCH_TZERO is controlled via the "DEF_TIME_SYSTEM" keyword.		2001-11-06T11:17:33	Yes	Yes
DEF_TIME_SYSTEM	Time system in which DEF_EPOCH_TZERO is specified. Select from the accepted set of values indicated in ANNEX B, Section B3 (and note the procedure to propose a new value, if this set of existing ANNEX B values does not accommodate your particular use case).		UTC	Yes	Yes (defaults to UTC)
SEC_CLK_PER_SI_SEC	Defines the number of clock seconds occurring during one SI second. This is only used if the spacecraft clock (SCLK) timescale is employed by the user.	1.0	2.5 [s]	No	No
SEC_PER_DAY	Defines the number of SI seconds in the chosen central body's "day", representing the approximate spin period of rotation for the chosen central body.	86400.0	88740 [s]	No	Yes (defaults to 86400)
EARLIEST_TIME	Time of the earliest data contained in the OCM, specified as either a relative time (e.g., DT=20157.26) measured in seconds with respect to the DEF_EPOCH_TZERO keyword value or as an absolute time (e.g., T=2018-11-13T11:13:20.5Z as formatted in Section 7.5.9) specified in the "DEF_TIME_SYSTEM" timing system.		DT=0.0 T=2001-11-06T00:00:00	No	No
LATEST_TIME	Time of the latest data contained in the OCM, specified as either a relative time (e.g., DT=20157.26) measured in seconds with respect to the DEF_EPOCH_TZERO keyword value or as an absolute time (e.g., T=2018-11-13T11:13:20.5Z as formatted in Section 7.5.9) specified in the "DEF_TIME_SYSTEM" timing system.		DT=86400.0 T=2001-11-08T00:00:00	No	No
TIME_SPAN	Span of time that the OCM covers, measured in days. TIME_SPAN is defined as (LATEST_TIME - EARLIEST_TIME), measured in days, irrespective of whether EARLIEST_TIME or LATEST_TIME are actually provided by the message creator.		20.0	No	No
TAIMUTC_AT_TZERO	Difference (TAI - UTC) in seconds (i.e. total # leap seconds elapsed since 1958) as modeled by the message originator at epoch "DEF_EPOCH_TZERO".		36 [s]	No	No

CCSDS PROPOSED STANDARD FOR ORBIT DATA MESSAGES

Keyword	Description	Default (if any)	Examples of Values	Mandatory	Any OCM sections relying upon this field ?
UT1MUTC_AT_TZERO	Difference (UT1 – UTC) in seconds, as modeled by the originator at epoch “DEF_EPOCH_TZERO”.		0.357 [s]	No	No
EOP_SOURCE	Free text field specifying the source and version of the message originator’s Earth Orientation Parameters (EOP) used in the creation of this message.		e.g., “CelesTrak EOP file downloaded from http://celestrak.com/SpaceData/EOP-Last5Years.txt at 2001-11-08T00:00:00”	No	No
INTERP_METHOD_EOP	Free text field specifying the method used to select or interpolate sequential EOP data	LINEAR	PRECEDING_VALUE NEAREST_NEIGHBOR LINEAR LAGRANGE_ORDER 5	No	No

6.2.4 OCM DATA: ORBIT STATE TIME HISTORY

6.2.4.1 Table 6-8 provides an overview of the OCM orbit state time history (“ephemeris”) section. Only those keywords shown in Table 6-8 shall be used in the OCM orbit state time history data specification.

6.2.4.2 Keyword values shall be provided in the units specified in the “Units” column of Table 6-8.

6.2.4.3 The order of occurrence of these orbit state time history keywords shall be fixed as shown in Table 6-8.

6.2.4.4 The orbit state time history section is optional; “mandatory” in the context of Table 6-8 denotes those keywords which must be included in this section if this section is included.

6.2.4.5 Each orbit state time history data block must begin with keyword ORB_START and end with keyword ORB_STOP.

6.2.4.6 Each of these keywords shall appear on a line by itself.

6.2.4.7 Multiple orbit state data blocks shall appear in an OCM only if they are delimited by separate ORB_START and ORB_STOP keywords

6.2.4.8 It is recommended that each data block be clearly differentiated from the others by a unique ORB_BASIS value or by one or more preceding explanatory comment(s).

6.2.4.9 It is recommended that each orbit state data block be unique from all others in at least one of the following respects:

- 1) the selected element set (ORB_TYPE) is unique
- 2) the orbit basis (PREDICTED, DETERMINED_OD, DETERMINED_TLM, HYPOTHETICAL)

- 3) the orbit state time history is based upon a unique orbit determination, navigation solution or Monte Carlo simulation
- 4) the reference frame is unique
- 5) the orbit center is unique
- 6) the data interval timespan is unique (i.e., has no overlap with any other data interval(s))

6.2.4.10 Each orbit state time history shall be time-ordered to be monotonically increasing, with the exception that the message creator may indicate a change in state over which interpolation should not be performed by providing exactly two consecutive lines containing a duplicate timestamp (e.g. following application of an impulsive maneuver or spacecraft or orbit event). In the case of such a duplicate timestamp, interpolation prior to the duplicate timestamp shall use the first of the two duplicate timestamp orbit states, and interpolation after the duplicate timestamp shall use the second of the two.

6.2.4.11 While discontinuous orbit state time history spans could be accommodated via duplicate time stamps as noted above, it is recommended that such discontinuous time spans be stored in separate covariance data blocks.

6.2.4.12 If the user includes orbit states at key mission events or times, it is recommended that the times, names and significance for such mission events are listed in the descriptive comment line(s) immediately following the ORB_START keyword.

6.2.4.13 Time tags of consecutive orbit states within the ordered sequence may be separated by uniform or non-uniform step size(s).

6.2.4.14 Orbit state time tags may or may not match those of maneuver, covariance and/or state transition matrix time histories.

6.2.4.15 All orbit state time history values in the OCM data shall be **time-tagged by either a relative time** (e.g., DT=20157.26) measured in seconds with respect to the epoch time specified via the ORB_EPOCH_TZERO keyword (or default epoch in DEF_EPOCH_TZERO if ORB_EPOCH_TZERO is not specified), **or an absolute time** (e.g., T=2018-11-13T11:13:20.5Z as formatted in Section 7.5.9) epoch time.


6.2.4.16 Each line of orbit ephemeris data shall be provided in fixed order as: DT= or T=, followed by the corresponding orbit state elements (as defined by ORB_TYPE; see ANNEX B, Section B7). **Units are km, km/s and degrees.**

6.2.4.17 At least one space character must be used to separate the items in each orbit ephemeris data line.

6.2.4.18 The digits of precision and time steps suitable for interpolation of an orbit ephemeris time history should be chosen according to best practice to avoid positional and interpolation loss of precision [M-8].

6.2.4.19 If an orbit state time history section is included in the message, it is recommended that a corresponding perturbations section be included as well to specify the perturbations incorporated in these orbit states.

Table 6-4: OCM Data: Orbit State Time History



CCSDS PROPOSED STANDARD FOR ORBIT DATA MESSAGES

Keyword	Description	Units	Default (if any)	Examples of Values	Mandatory
ORB_START	Start of an orbit state vector or time history section	n/a		n/a	Yes
COMMENT	Comments (a contiguous set of one or more comment lines are allowed in the Orbit State Time History section only immediately after the ORB_START keyword ; see 7.7 for comment formatting rules).	n/a		COMMENT This is a comment	No
ORB_ID	Optional alphanumeric free-text string containing the identification number for this orbit state time history block	n/a		ORB_20160 402_XYZ	No
ORB_PREV_ID	Optional alphanumeric free-text string containing the identification number for the previous orbit time history. Note: if the message is not part of a sequence of orbit time histories or if this orbit time history is the first in a sequence of orbit time histories, then ORB_PREV_ID should be excluded from this message.	n/a		ORB201603 05A	No
ORB_NEXT_ID	Optional alphanumeric free-text string containing the identification number for the next orbit time history. Note: if the message is not part of a sequence of orbit time histories or if this orbit time history is the last in a sequence of orbit time histories, then ORB_NEXT_ID should be excluded from this message.	n/a		ORB201603 05C	No
ORB_BASIS	Basis of this Orbit State time history data, this is free text field with the following suggested values: <ol style="list-style-type: none"> 1. "PREDICTED" 2. "DETERMINED_OD" when estimated from observation-based orbit determination reconstruction and/or calibration. 3. "DETERMINED_TLM" when read directly from telemetry. 4. "HYPOTHETICAL" for future mission design and optimization studies <p>Note: For definitive OD performed onboard whose solutions have been telemetered to the ground for inclusion in an OCM, the ORB_BASIS shall be considered to be DETERMINED_OD.</p>	n/a		PREDICTE D	No
ORB_BASIS_ID	Optional alphanumeric free-text string containing the identification number for the orbit determination, navigation or Monte Carlo simulation upon which this orbit state time history block is based	n/a		OD_5910	No
ORB_AVERAGING	Free-text keyword specifying whether provided orbit state/elements are either osculating or mean element definitions. If an alternate single- or double-averaging formulation is used than "MEAN_BROUWER" or "MEAN_KOZAI," the user may name it or use "OTHER" to denote specification via ICD.	n/a	OSCULATING	OSCULATING MEAN_BROUWER MEAN_KOZAI (other...)	No

CCSDS PROPOSED STANDARD FOR ORBIT DATA MESSAGES

CENTER_NAME	Origin of reference frame, which may be a natural solar system body (planets, asteroids, comets, and natural satellites), including any planet barycenter or the solar system barycenter, or another spacecraft. Select from the accepted set of values indicated in ANNEX B, Section B2 (and note the procedure to propose a new value, if this set of existing ANNEX B values does not accommodate your particular use case). QUESTION: DO WE WANT THIS TO BE AN OPEN-ENDED LIST (FREE TEXT, EXTENSIBLE WITHOUT COORDINATION), *OR* USE AN ICD TO DEFINE NON-EXISTING NAMES?? *** QUESTION #2: *** Could this center be a non-gravitational center (i.e., a slave/chief relative motion case)?	n/a	EARTH	Earth Moon Solar System Barycenter Sun ISS EROS Earth_sun_l2	No
ORB_EPOCH_TZERO	Reference epoch for all relative times in the orbit state time history block. See 7.5.10 for formatting rules. The time system of ORB_EPOCH_TZERO may be set per Annex B, Section B3 via the "ORB_TIME_SYSTEM" keyword.	§7.5.9	<DEF_EPOCH_TZERO>	2001-11-06T11:17:33	No
ORB_TIME_SYSTEM	Timing system of ORB_EPOCH_TZERO, selected per Annex B, Section B3.	n/a	<DEF_TIME_SYSTEM>	UTC UT1	No
ORB_REF_FRAME	Reference frame of the orbit state time history. Select from the accepted set of values indicated in ANNEX B, Section B4 (and note the procedure to propose a new value, if this set of existing ANNEX B values does not accommodate your particular use case).	n/a	If not intrinsic to selected orbit set, default is ITRF2000	J2000	No
ORB_FRAME_EPOCH	Epoch of the orbit data reference frame, if not intrinsic to the definition of the reference frame. See 7.5.10 for formatting rules.	§7.5.9	<DEF_EPOCH_TZERO>	2001-11-06T11:17:33 2002-204T15:56:23Z	No
ORB_TYPE	Specifies the orbit element set type; selected per ANNEX B, section B7. If set to ORB_TYPE is set to ICD, then ORB_N and ORB_ELEMENTS are mandatory and shall define the orbit elements used.	n/a	CARTPV	n/a	Yes
ORB_N	Number of elements (excluding time) contained in the element set if ORB_TYPE is set to ICD. If ORB_TYPE is not set to ICD, then ORB_N shall be ignored in deference to the number of elements corresponding to the selected ORB_TYPE.	n/a	6	8	No
ORB_ELEMENTS	Free-text definition of each of the orbit elements, if ORB_TYPE is set to ICD. If ORB_TYPE is not set to ICD, then the number of elements coincides with the selected ORB_TYPE. If ORB_TYPE is not set to ICD, then ORB_ELEMENTS shall be ignored in deference to the element definitions corresponding to the selected ORB_TYPE.	n/a	6	8	No
... < Insert orbit lines here>	Orbit time history line(s) shall be formatted as described above in 6.2.4.13 – 6.2.4.16	km, km/s, deg			Yes
ORB_STOP	End of an orbit state vector or time history section	n/a		n/a	Yes

Commented [DL01]: As with CENTER_NAME (above): In the OCM, do we want to allow users to "define" their own elements, or require them to first contact us to implement them in SANA ??

6.2.5 OCM DATA: SPACE OBJECT PHYSICAL CHARACTERISTICS

6.2.5.1 Table 6-4 gives an overview of the OCM space object physical characteristics section. Only those keywords shown in table 6-4 shall be used in OCM space object physical characteristics data.

6.2.5.2 Keyword values shall be provided in the units specified in the “Units” column of Table 6-4.

6.2.5.3 The order of occurrence of these OCM Space Objects Physical Characteristics keywords shall be fixed as shown in Table 6-4.

6.2.5.4 The “OCM Data: Space Object Physical Characteristics” section is optional; “mandatory” in the context of Table 6-4 denotes those keywords which must be included in this section if this section is included.

6.2.5.5 At most, only one space object physical characteristics section shall appear in an OCM.

6.2.5.6 The space object physical characteristics data section in the OCM shall be indicated by two keywords: PHYS_START and PHYS_STOP.

6.2.5.7 The **Space Object Optimally-Encompassing Shape (OES)** parameters are defined in further detail in ANNEX C.

Table 6-5: OCM Data: Space Object Physical Characteristics

Keyword	Description	Units	Default (if any)	Examples of Values	Mandatory
PHYS_START	Start of a Space Object Physical Characteristics specification	n/a			Yes
COMMENT	Comments (a contiguous set of one or more comment lines are allowed in the OCM Space Object Physical Characteristics only immediately after the PHYS_START key word; see 7.7 for comment formatting rules).	n/a		COMMENT This is a comment	No
MANUFACTURER	Free text field containing the satellite manufacturer name			BOEING	No
BUS_MODEL	Free text field containing the satellite manufacturer's spacecraft bus model name			702	No
DESIGNED_LIFETIME	Designed lifetime of the spacecraft, in years	yr		4.85	No
DOCKED_WITH	Free text field containing a comma-separated list of other space objects that this object is docked to			ISS	No
IN_FORMATION_WITH	Free text field containing a comma-separated list of other space objects that this object is formation flying with			TERRA, AQUA	No
DRAG_AREA	Additional Drag Area (A_D) facing the relative wind vector, not already incorporated into the attitude-dependent “AREA_ALONG_OES” parameters	m^2		2.5	No
DRAG_COEFF	Drag Coefficient (C_D). If the atmospheric drag coefficient, C_D , is set to zero, no atmospheric drag shall be taken into account.	n/a		2.2	No

CCSDS PROPOSED STANDARD FOR ORBIT DATA MESSAGES

Keyword	Description	Units	Default (if any)	Examples of Values	Mandatory
DRAG_SCALE	Drag scale factor (1.0 represents no scaling). This factor is intended to allow operators to supply the nominal ballistic coefficient components while accommodating ballistic coefficient uncertainties (i.e. 1.06 represents a +6 percent error)	n/a	1.0	1.0	No
MASS_AT_BOL	S/C total mass at beginning of life	kg		500	No
MASS	S/C total mass at the reference epoch "DEF EPOCH TZERO"	kg		472.3	No
MASS_AT_EOL	S/C total mass at end of life	kg		300	No
OES_TYPE	Type of Optimally-Encompassing Shape (OES) to use, confined to one of the following basic shapes: BOX ELLIPSOID ELLIPTICAL_CYLINDER	n/a	BOX	ELLIPSOID	No
OES_PARENT_FRAME	Reference frame which maps to the OES frame via the Euler sequence OES_ROLL and OES_YAW. Select from the accepted set of values indicated in ANNEX B, Sections B4 and B5 (and note the procedure to propose a new value, if this set of existing ANNEX B values does not accommodate your particular use case).	n/a	RIC	ITRF1997	No
OES_PARENT_FRAME_EPOCH	Epoch of the OES reference frame, if not intrinsic to the definition of the reference frame. (See 7.5.10 for formatting rules.)	n/a	<DEF EPOCH_T ZERO>	2001-11-06T11:17:33 2002-204T15:56:23Z	No
OES_Q1	$q_1 = e_1 * \sin(\theta/2)$, where θ = Euler rotation angle and e_1 = 1st component of Euler rotation axis for the rotation that maps from the OES_PARENT_FRAME (defined above) to the frame aligned with the Optimally-Encompassing Shape (OES) (defined in ANNEX C, Section C1). A value of "-999" denotes a tumbling space object.	n/a		-0.575131822	No
OES_Q2	$q_2 = e_2 * \sin(\theta/2)$, where θ = Euler rotation angle and e_2 = 2nd component of Euler rotation axis for the rotation that maps from the OES_PARENT_FRAME (defined above) to the frame aligned with the Optimally-Encompassing Shape (defined in ANNEX C, Section C1). A value of "-999" denotes a tumbling space object.	n/a		-0.280510532	No
OES_Q3	$q_3 = e_3 * \sin(\theta/2)$, where θ = Euler rotation angle and e_3 = 3rd component of Euler rotation axis for the rotation that maps from the OES_PARENT_FRAME (defined above) to the frame aligned with the Optimally-Encompassing Shape (defined in ANNEX C, Section C1). A value of "-999" denotes a tumbling space object.	n/a		-0.195634856	No
OES_QC	$q_c = \cos(\theta/2)$, where θ = Euler axis/angle rotation angle for the rotation that maps from the OES_PARENT_FRAME (defined above) to the frame aligned with the Optimally-Encompassing Shape (ANNEX C, Section C1). q_c shall be made non-negative by convention. A value of "-999" denotes a tumbling space object.	n/a		0.743144825	No
OES_MAX	Maximum physical dimension (along \hat{X}_{OEB}) of the Optimally-Encompassing Shape (OES) in meters,	m		1	No
OES_MED	Medium physical dimension (along \hat{Y}_{OEB}) of Optimally-Encompassing Shape (OES) normal to OES_MAX direction	m		0.5	No

CCSDS PROPOSED STANDARD FOR ORBIT DATA MESSAGES

Keyword	Description	Units	Default (if any)	Examples of Values	Mandatory
OES_MIN	Minimum physical dimension (along \hat{Z}_{OEB}) of Optimally-Encompassing Shape (OES) in direction normal to both OES_MAX and OES_MED directions	m		0.3	No
AREA_ALONG_OES_MAX	Cross-sectional area of space object when viewed along max OES (\hat{X}_{OEB}) direction as defined in ANNEX C	m**2		0.15	No
AREA_ALONG_OES_MED	Cross-sectional area of space object when viewed along medium OES (\hat{Y}_{OEB}) direction as defined in ANNEX C	m**2		0.3	No
AREA_ALONG_OES_MIN	Cross-sectional area of space object when viewed along minimum OES (\hat{Z}_{OEB}) direction as defined in ANNEX C	m**2		0.5	No
AREA_MIN_FOR_PC	Minimum cross-sectional area for collision probability estimation purposes	m**2		1.0	No
AREA_MAX_FOR_PC	Maximum cross-sectional area for collision probability estimation purposes	m**2		1.0	No
AREA_AVG_FOR_PC	Typical (50 th percentile) cross-sectional area sampled over all space object orientations for collision probability estimation purposes	m**2		1.0	No
RCS	Typical (50 th percentile) effective Radar Cross Section of the space object sampled over all possible viewing angles	m**2		1.0	No
SOLAR_RAD_AREA	Additional total Solar Radiation Pressure Area (A_R) facing the Sun, not already incorporated into the attitude-dependent "AREA_ALONG_OES" parameters (computed from $\{ \text{AREA_ALONG_OES_MAX} \cos(\theta_1) + \text{AREA_ALONG_OES_MED} \cos(\theta_2) + \text{AREA_ALONG_OES_MIN} \cos(\theta_3) \}$ Where θ_i represents the angle between the normal to each MAX/MED/MIN face and the direction to the Sun.	m**2		1.0	No
SOLAR_RAD_COEFF	Solar Radiation Pressure Coefficient (C_R). Note that if the solar radiation coefficient, C_R , is set to zero, no solar radiation pressure shall be taken into account.	n/a		1.7	No
SOLAR_RAD_SCALE	Solar Radiation Pressure scale factor (1.0 represents no scaling)	n/a		1.0	No
VM_ABS	Typical (50 th percentile) absolute Visual Magnitude of the space object sampled over all possible viewing angles and "normalized" as discussed in Annex C, Section C-4 to a 1 AU Sun-to-target distance, a phase angle of 0° and a 40,000 km target-to-sensor distance (equivalent of GEO satellite tracked at 15.6° above local horizon)	n/a		15.0	No
REFLECTIVITY	Typical coefficient of reflectivity of the space object sampled over all possible viewing angles	n/a		15.0	No
CONTROL_MODE	Primary mode of attitude control for the space object. Suggested examples include: - THREE_AXIS - SPIN - DUAL_SPIN - TUMBLING - GRAVITY_GRADIENT - PASSIVE_MAG_TORQUE - ACTIVE_MAG_TORQUE - CMGS - ATT_THRUSTERS	n/a		CMGS	No

CCSDS PROPOSED STANDARD FOR ORBIT DATA MESSAGES

Keyword	Description	Units	Default (if any)	Examples of Values	Mandatory
ATT_KNOWLEDGE	Accuracy of attitude knowledge	deg		0.3	No
ATT_CONTROL	Ability to control attitude/pointing	deg		2.0	No
AVG_MANEUVER_FREQ	Average maneuver frequency, measured in maneuvers per year	per yr		20.0	No
MAX_THRUST	Maximum composite thrust the spacecraft can accomplish in any single body-fixed direction	N		1.0	No
DV_BOL	Total ΔV capability of the spacecraft at beginning of life	m/s		14000.0	No
DV_REMAINING	Total ΔV remaining capability of the spacecraft	m/s		5000.0	No
IXX	Moment of Inertia about the X-axis of the spacecraft's primary body frame (e.g. SC_Body_1)	kg*m**2		1000.0	No
IYY	Moment of Inertia about the Y-axis	kg*m**2		800.0	No
IZZ	Moment of Inertia about the Z-axis	kg*m**2		400.0	No
IXY	Inertia Cross Product of the X & Y axes	kg*m**2		20.0	No
IXZ	Inertia Cross Product of the X & Z axes	kg*m**2		40.0	No
IYZ	Inertia Cross Product of the Y & Z axes	kg*m**2		60.0	No
PHYS_STOP	End of a Space Object Physical Characteristics specification	n/a			Yes

6.2.6 OCM DATA: ORBIT STATE COVARIANCE TIME HISTORY

6.2.6.1 Table 6-9 provides an overview of the OCM orbit state covariance time history section. Only those keywords shown in Table 6-9 shall be used in OCM orbit state covariance time history data specification.

6.2.6.2 Keyword values shall be provided in the units specified in the "Units" column of Table 6-9.

6.2.6.3 The order of occurrence of these orbit state covariance time history keywords shall be fixed as shown in Table 6-9.

6.2.6.4 The orbit state covariance time history section is optional; "mandatory" in the context of Table 6-9 denotes those keywords which must be included in this section if this section is included.

6.2.6.5 Each orbit state covariance time history data block must begin with keyword COV_START and end with keyword COV_STOP.

6.2.6.6 Each of these keywords shall appear on a line by itself.

6.2.6.7 Multiple covariance data blocks shall appear in an OCM only if they are delimited by separate COV_START and COV_STOP keywords

6.2.6.8 It is recommended that each data block be clearly differentiated from the others by a unique COV_BASIS value or by one or more preceding explanatory comment(s).

6.2.6.9 It is recommended that each covariance data block be unique from all others in at least one of the following respects:

- 1) the selected covariance element set (COV_TYPE) is unique
- 2) the covariance time history basis (PREDICTED, DETERMINED_OD, EMPIRICAL, MONTECARLO, HYPOTHETICAL)
- 3) the covariance time history is based upon a unique orbit determination, navigation solution or Monte Carlo simulation
- 4) the reference frame is unique
- 5) the orbit center is unique
- 6) the data interval timespan is unique (i.e., has no overlap with any other data interval(s))

6.2.6.10 The COV_TYPE keyword value shall be selected from Table B4 or B5.

6.2.6.11 Each covariance time history shall be time-ordered to be monotonically increasing, with the exception that the message creator may indicate a change in state over which interpolation should not be performed by providing exactly two consecutive covariance data blocks containing a duplicate timestamp (e.g. following application of an impulsive maneuver or spacecraft or orbit event). In the case of such a duplicate timestamp, interpolation prior to the duplicate timestamp shall use the first of the two duplicate timestamp covariance matrices, and interpolation after the duplicate timestamp shall use the second of the two.

6.2.6.12 While discontinuous covariance time history spans could be accommodated via duplicate time stamps as noted above, it is recommended that such discontinuous time spans be stored in separate covariance data blocks.

6.2.6.13 If the user includes covariances at key mission events or times, it is recommended that the times, names and significance for such mission events be provided in descriptive comment line(s) immediately following the COV_START keyword.

6.2.6.14 Time tags of consecutive covariance information within the ordered sequence may be separated by uniform or non-uniform step size(s).

6.2.6.15 Covariance time tags may or may not match those of maneuver, orbit state and/or state transition matrix time histories.

6.2.6.16 Values in the covariance matrix shall be expressed in the applicable reference frame specified via the 'COV_REF_FRAME' keyword.

6.2.6.17 If an orbit state covariance time history section is included in the message, it is recommended that a corresponding perturbations section be included as well to specify the perturbations incorporated in these orbit state covariances.

6.2.6.18 All orbit state covariance time history values in the OCM data shall be **time-tagged by either a relative time** (e.g., DT=20157.26) measured in seconds with respect to the epoch time specified via the COV_EPOCH_TZERO keyword (or default epoch in DEF_EPOCH_TZERO if COV_EPOCH_TZERO is not specified), **or an absolute time** (e.g., T=2018-11-13T11:13:20.5Z as formatted in Section 7.5.9) epoch time.

6.2.6.19 For COV TYPE = TEIGVAL3EIGVEC3, the covariance time tag and eigenvectors and eigenvalues shall all be presented on a single line, comprised of the time tag, followed by the major, medium and minor eigenvalues and then followed by the major, medium and minor eigenvectors.

6.2.6.20 For all other COV TYPE values:

6.2.6.20.1 The order in which data items are given shall be fixed, with the elements in each row of covariates being commensurate with the specified COV_TYPE value.

6.2.6.20.2 Each covariance shall be preceded by a single line containing the time tag (relative “DT=” or absolute “T=”) of the covariance matrix.

6.2.6.20.3 Directly following the time tag specification line, each of the “N” rows of the lower triangular covariance matrix shall be presented containing from one [1,1] to “N” numerical entries depending on what row of the matrix is being represented (first row has one element, second row has two, continuing in this fashion until the “Nth” row has “N” elements). Units are km, km/s and degrees.

6.2.6.20.4 At least one space character must be used to separate the items in each covariance matrix data line.

6.2.6.21 Variance and covariance values shall be expressed in standard double precision as related in 7.5. The digits of precision and time steps suitable for interpolation of a covariance time history should be chosen according to best practice to avoid covariance and interpolation loss of precision [M-8].

NOTE: Interpolation of covariance matrices at neighboring relative time points shall be done by (1) eigenvalue/vector decomposition; (2) linear (or higher-order) interpolation of neighboring eigenvalues; (3) Euler axis/angle rotation of eigenvectors at intermediate time(s) of interest; and (4) Re-composition of attained eigenvalues and eigenvectors into covariances at time(s) of interest [M-16]. Direct interpolation of covariance matrix components or failure to incorporate sufficient digits of precision on the interpolated covariance elements can produce invalid (non-positive-semidefinite) covariances.

Table 6-6: OCM Data: Covariance Time History

Keyword	Description	Units	Default (if any)	Examples of Values	Mandatory
COV_START	Start of a covariance time history section	n/a		n/a	Yes
COMMENT	Comments (a contiguous set of one or more comment lines are allowed in the OCM Covariance Time History section only immediately after the COV_START key word; see 7.7 for comment formatting rules).	n/a		COMMENT This is a comment	No
COV_ID	Optional alphanumeric free-text string containing the identification number for this covariance time history block	n/a		COV_20160402_XYZ	No
COV_PREV_ID	Optional alphanumeric free-text string containing the identification number for the previous covariance time history. Note: if the message is not part of a sequence of covariance time histories or if this covariance time history is the first in a sequence of covariance time histories, then COV_PREV_ID should be excluded from this message.	n/a		COV_20160305A	No
COV_NEXT_ID	Optional alphanumeric free-text string containing the identification number for the next covariance time history. Note: if the message is not part of a sequence of covariance time histories or if this covariance time history is the last in a sequence of covariance time histories, then COV_NEXT_ID should be excluded from this message.	n/a		COV_20160305C	No
COV_BASIS	Basis of this covariance time history data. This is free text field with the following suggested values: 1. "PREDICTED" 2. "DETERMINED_OD" when estimated from observation-based orbit determination reconstruction and/or calibration. 3. EMPIRICAL (for empirically-determined such as overlap analyses) 4. MONTE_CARLO for Monte Carlo-based simulation estimations. 5. "HYPOTHETICAL" for future mission design and optimization studies Note: For definitive OD performed onboard whose solutions have been telemetered to the ground for inclusion in an OCM, the COV_BASIS shall be considered to be DETERMINED OD.	n/a	PREDICTED	PREDICTED EMPIRICAL DETERMINED MONTE_CARLO	No
COV_BASIS_ID	Optional alphanumeric free-text string containing the identification number for the orbit determination, navigation or Monte Carlo simulation upon which this orbit state time history block is based	n/a		OD_5910	No
COV_EPOCH_TZERO	Reference epoch for all relative times in the covariance time history block. See 7.5.10 for formatting rules. The time system of COV_EPOCH_TZERO may be set per Annex B, Section B3 via the "COV_TIME_SYSTEM" keyword.	§7.5.9	<DEF_EPOCH_TZERO>	2001-11-06T11:17:33	No
COV_TIME_SYSTEM	Timing system of COV_EPOCH_TZERO, selected per Annex B, Section B3.	n/a	<DEF_TIME_SYSTEM>	UTC UT1	No
COV_REF_FRAME	Reference frame of the covariance time history. Select from the accepted set of values indicated in ANNEX B, Section B4 and B5 (and note the procedure to propose a new value, if this set of existing ANNEX B values does not accommodate your particular use case).	n/a	TNW	J2000	No

CCSDS PROPOSED STANDARD FOR ORBIT DATA MESSAGES

Keyword	Description	Units	Default (if any)	Examples of Values	Mandatory
COV_FRAME_EPOCH	Epoch of the covariance data reference frame, if not intrinsic to the definition of the reference frame. See 7.5.10 for formatting rules.	§7.5.9	<DEF EPOCH_TZE RO>	2001-11-06T11:17:33 2002-204T15:56:23Z	No
COV_NNXNN	Number of diagonal elements contained in full covariance if COV_TYPE is set to ICD. If COV_TYPE is <u>not</u> set to ICD, then the number of diagonal elements shall coincide with the selected COV_TYPE (ANNEX B, Sections B7 and B8).	n/a	6	10	No
COV_TYPE	Indicates covariance composition. Select from ANNEX B, Sections B7 and B8 (and note the procedure to propose new values).	n/a	CARTPV	n/a	Yes
COV_SCALE_MIN	Minimum scale factor to apply to this covariance data to achieve realism	n/a	1	0.5	No
COV_SCALE_MAX	Maximum scale factor to apply to this covariance data to achieve realism	n/a	1	5.0	No
COV_CONFIDENCE	A measure of the confidence in the covariance errors matching reality (AWAITING SPECIFIC INPUTS FROM CHERYL)	n/a			No
...< Insert covariance data here>	Covariance data shall be provided as specified in sections 6.2.6.15 – 6.2.6.18.	km, km/s, deg			Yes
COV_STOP	End of a covariance time history section	n/a		n/a	Yes

6.2.7 OCM DATA: STATE TRANSITION MATRIX TIME HISTORY

6.2.7.1 Table 6-10 provides an overview of the OCM state transition matrix time history section. Only those keywords shown in Table 6-10 shall be used in OCM state transition matrix time history data specification.

6.2.7.2 Keyword values shall be provided in the units specified in the “Units” column of Table 6-10.

6.2.7.3 The order of occurrence of these OCM state transition matrix time history keywords shall be fixed as shown in table 6-10.

6.2.7.4 The OCM state transition matrix time history section is optional; “mandatory” in the context of Table 6-10 denotes those keywords which must be included in this section if this section is included.

6.2.7.5 Each state transition matrix time history data block must begin with keyword STM_START and end with keyword STM_STOP.

6.2.7.6 Each of these keywords shall appear on a line by itself.

6.2.7.7 Multiple state transition matrix data blocks shall appear in an OCM only if they are delimited by separate STM_START and STM_STOP keywords

6.2.7.8 It is recommended that each data block be clearly differentiated from the others by a unique STM_BASIS value or by one or more preceding explanatory comment(s).

6.2.7.9 It is recommended that each STM data block be unique from all others in at least one of the following respects:

- 1) the selected orbit state element set (STM_TYPE) is unique;
- 2) the state transition matrix time history is based upon a unique orbit determination, navigation solution or Monte Carlo simulation;
- 3) the reference frame is unique;
- 4) the orbit center is unique;
- 5) the state transition matrix timespan is unique.

6.2.7.10 The STM_TYPE keyword value shall be selected from Table B4.

6.2.7.11 Each state transition matrix time history shall be time-ordered to be monotonically increasing with no duplicate time points permitted within each time history.

6.2.7.12 No interpolation of the state transition matrix time history shall be undertaken, since the state transition matrix pre- and post-multiplies the state (or covariance) in the mapping process to yield states and covariances that may then be properly interpolated.

6.2.7.13 Discontinuous state transition matrix time spans be stored in separate state transition matrix data blocks.

6.2.7.14 If the user includes state transition matrices at key mission events or times, it is recommended that the times, names and significance for such mission events are listed in the descriptive comment line(s) immediately following the STM_START keyword.

6.2.7.15 Time tags of consecutive state transition matrices within the ordered sequence may be separated by uniform or non-uniform step size(s).

6.2.7.16 State transition matrix time tags may or may not match those of maneuver, orbit state and/or covariance time histories.

6.2.7.17 The reference frame of the state transition matrices must be provided via the 'STM_REF_FRAME' keyword.

6.2.7.18 Values in each state transition matrix shall be expressed in the applicable reference frame and shall be presented sequentially from upper to lower and row-by-row from left to right. State transition matrix values shall be expressed in standard double precision as discussed in 7.5.

6.2.7.19 All state transition matrices in the OCM data shall be **time-tagged by either a relative time** (e.g., DT=20157.26) measured in seconds with respect to the epoch time specified via the STM_EPOCH_TZERO keyword (or default epoch in DEF_EPOCH_TZERO if STM_EPOCH_TZERO is not specified), **or an absolute time** (e.g., T=2018-11-13T11:13:20.5Z as formatted in Section 7.5.9) epoch time.

6.2.7.20 Each row of each state transition matrix must be provided on a single line. The order in which data items are given shall be fixed. The elements in each row shall be defined commensurate with the STM_TYPE keyword specification. The "N" rows of the state transition matrix shall each contain "N" numbers. **Units are km, km/s and degrees.**

6.2.7.21 At least one space character must be used to separate the items in each state transition matrix data line.

6.2.7.22 The digits of precision and time steps suitable for state transition matrix time history should be chosen to avoid STM propagation loss of precision.

6.2.7.23 If an STM time history section is included in the message, it is recommended that a corresponding perturbations section be included as well to specify the perturbations incorporated in the STM data.

NOTE: State Transition Matrices (STMs) can be very useful in mapping both an initial state, and (separately) differences about that state, to other time(s) of interest. Following the terminology and definitions of reference [M-9], pp. 82, 778-780 and 809) allows the analyst to map states, or alternatively state differences, at time t_0 to another time t_i . As noted in reference [M-9], these are distinctly different in definition and content from each other. Both types of State Transition Matrices are supported, as specified by the STM_MAP_MODE keyword.

Table 6-7: OCM Data: State Transition Matrix Time History

Keyword	Description	Units	Default (if any)	Examples of Values	Mandatory
STM_START	Start of a state transition matrix time history	n/a		n/a	Yes

CCSDS PROPOSED STANDARD FOR ORBIT DATA MESSAGES

Keyword	Description	Units	Default (if any)	Examples of Values	Mandatory
COMMENT	Comments (a contiguous set of one or more comment lines are allowed in the OCM State Transition Matrix Time History section only immediately after the STM_START key word; see 7.7 for comment formatting rules).	n/a		COMMENT This is a comment	No
STM_ID	Optional alphanumeric free-text string containing the identification number for this state transition matrix time history block.	n/a		STM_20160402_XYZ	No
STM_PREV_ID	Optional alphanumeric free-text string containing the identification number for the previous state transition matrix time history block. Note: if the message is not part of a sequence of state transition matrix time history blocks or if this state transition matrix time history block is the first in a sequence of state transition matrix time history blocks, then STM_PREV_ID should be excluded from this message.	n/a		STM_20160305A	No
STM_NEXT_ID	Optional alphanumeric free-text string containing the identification number for the next state transition matrix time history block. Note: if the message is not part of a sequence of state transition matrix time history blocks or if this state transition matrix time history block is the last in a sequence of state transition matrix time history blocks, then EC_NEXT_ID should be excluded from this message.	n/a		STM_20160305C	No
STM_MAP_MODE	Indicates whether state transition matrix maps: <ul style="list-style-type: none"> - An initial state to later states (STATE) or - Initial state differences (or uncertainties) to later differences (DIFFERENCES) 	n/a	DIFFERENCES	STATE DIFFERENCES	Yes
STM_ORB_STATE	Initial orbit state at STM_EPOCH_TZERO from which the state transition mapping is derived and referenced	km, km/s, deg	(consistent with "STM_TYP E")	2789600.0 -280000.0 -1746800.0 4730.0 -2500.0 -1040.0	No
STM_BASIS	Basis of this covariance time history data. This is free text field with the following suggested values: <ol style="list-style-type: none"> 1. "PREDICTED" 2. "DETERMINED_OD" when estimated from observation-based orbit determination reconstruction and/or calibration. 3. EMPIRICAL (for empirically-determined such as overlap analyses) 4. MONTE_CARLO for Monte Carlo-based simulation estimations. 5. "HYPOTHETICAL" for future mission design and optimization studies <p>Note: For definitive OD performed onboard whose solutions have been telemetered to the ground for inclusion in an OCM, the COV_BASIS shall be considered to be DETERMINED_OD.</p>	n/a	PREDICTED	PREDICTED EMPIRICAL DETERMINED MONTE_CARLO	No
STM_BASIS_ID	Optional alphanumeric free-text string containing the identification number for the orbit determination, navigation or Monte Carlo simulation upon which this STM time history block is based	n/a		OD_5910	No

CCSDS PROPOSED STANDARD FOR ORBIT DATA MESSAGES

Keyword	Description	Units	Default (if any)	Examples of Values	Mandatory
STM_CENTER_NAME	Origin of reference frame, which may be a natural solar system body (planets, asteroids, comets, and natural satellites), including any planet barycenter or the solar system barycenter, or another spacecraft. Select from the accepted set of values indicated in ANNEX B, Section B2 (and note the procedure to propose a new value, if this set of existing ANNEX B values does not accommodate your particular use case).	n/a	EARTH	EARTH MOON SOLAR SYSTEM BARYCENTER SUN ISS EROS EARTH SUN L2	No
STM_EPOCH_TZERO	The epoch to which the STM_ORB_STATE and any state transition matrix relative times are referenced in the STM block, and at which time the STM = the identity matrix. The time system of STM_EPOCH_TZERO may be set per Annex B, Section B3 via the "STM_TIME_SYSTEM" keyword.	§7.5.9	<DEF_EPOCH_TZERO>	2001-11-06T11:17:33	Yes
STM_TIME_SYSTEM	Timing system of STM_EPOCH_TZERO, selected per Annex B, Section B3.	n/a	<DEF_TIME_SYSTEM>	UTC UT1	No
STM_REF_FRAME	Reference frame to which the state transition matrix is referenced, if not intrinsic to the definition of the STM data. Select from the accepted set of values indicated in ANNEX B, Section B4 and B5 (and note the procedure to propose a new value, if this set of existing ANNEX B values does not accommodate your particular use case).	n/a	ICRF3	J2000	No
STM_FRAME_EPOCH	Epoch of the state transition matrix data reference frame, if not intrinsic to the definition of the reference frame. (Sec 7.5.10 for formatting rules.)	§7.5.9	<DEF_EPOCH_TZERO>	2001-11-06T11:17:33 2002-204T15:56:23Z	No
STM_N	Dimension "N" of the "N x N" state transition matrix if STM_TYPE is set to ICD. If STM_TYPE is not set to ICD, then the dimension "N" coincides with the number of elements implied by STM_TYPE (ANNEX B, Section B7 and B8).	n/a	6	6	No
STM_TYPE	Indicates state transition matrix composition; selected from ANNEX B, Section B7 and B8, or alternately, "ICD" denotes state transition matrix composition definition via ICD.	n/a	CARTPV	CARTPV	Yes
...< Insert STM data here>	State transition matrices shall be provided as specified in sections 6.2.7.17 – 6.2.7.20.	km, km/s, deg			Yes
STM_STOP	End of a state transition matrix time history section	n/a		n/a	Yes

6.2.8 OCM DATA: MANEUVER SPECIFICATION

6.2.8.1 The “OCM Data: Maneuver Specification” section is optional; “mandatory” in the context of Table 6-10 denotes those keywords which must be included in this section if this section is included.

6.2.8.2 Table 6-10 provides an overview of the OCM maneuver specification section. Only those keywords shown in Table 6-10 shall be used as Key Value Notation keywords in the OCM maneuver specification.

6.2.8.3 Each of these keywords shall appear on a line by itself.

6.2.8.4 Keyword values shall be provided in the units specified in the “Units” column of Table 6-10 (m/s, m/s², N, kg and degrees).

6.2.8.5 The order of occurrence of these OCM Maneuver Specification keywords shall be fixed as shown in Table 6-10.

6.2.8.6 Maneuver data in the OCM shall be indicated by two keywords: MAN_START and MAN_STOP.

6.2.8.7 Multiple maneuver data blocks shall appear in an OCM only if they are delimited by separate MAN_START and MAN_STOP keywords.

6.2.8.8 It is recommended that each data block be clearly differentiated from the others by either having a unique THR_ID or by one or more preceding explanatory comment(s).

6.2.8.9 The time intervals of multiple maneuver data blocks may abut, overlap and/or be otherwise unsorted, to accommodate multiple thrusters in simultaneous operation, or to accommodate changes in thrust direction, efficiency, mass change, etc.

6.2.8.10 Discontinuous maneuver sequence time spans be stored in separate maneuver data blocks.

6.2.8.11 Each maneuver data block shall be assigned an integer thruster ID (THR_ID) value.

- Non-zero THR_ID values specify the unique thruster identification number to which this maneuver data block belongs.
- A THR_ID value of “0” (zero) designates that this maneuver block applies generically to the space object as a whole and is not the result of a specific thruster unit.

6.2.8.12 The basis of each maneuver data block is set via MAN_BASIS. Per Table 6-10, MAN_BASIS shall be one of the following values:

- CANDIDATE

- PLANNED
- ANTICIPATED
- DETERMINED_TLM
- DETERMINED_OD

6.2.8.13 Maneuver descriptions shall be designated as either MAN_IS_ADDITIVE="YES" or "NO".

- "YES" designates that this described maneuver "constituent" shall be added to any/all other additive-designated maneuver descriptions within the same MAN_BASIS category to arrive at the total composite maneuver description.
- "NO" designates that this described maneuver shall be interpreted as being the aggregated/total composite maneuver and that no other additive maneuver constituents are to be added to it.

Pairing these two possibilities with the five MAN_BASIS categories, there are ten possible maneuver description cases as shown in Table 6-8:

Table 6-8: OCM Data: Maneuver specification cases

Maneuver Basis	MAN_IS_ADDITIVE Setting:	
	YES	NO
CANDIDATE	Case 1	Case 2
PLANNED	Case 3	Case 4
ANTICIPATED	Case 5	Case 6
DETERMINED_TLM	Case 7	Case 8
DETERMINED_OD	Case 9	Case 10

Commented [DL02]: Do we need these? Perhaps "FUTURE"? Still mulling this over.

6.2.8.13.1 The message recipient should exercise caution whenever maneuvers are additive (MAN_IS_ADDITIVE=YES), to prevent the unintentional accumulation of maneuver contributions across disparate maneuver basis values (MAN_BASIS), orbit determination solutions (MAN_OD_ID), reference frames (MAN_REF_FRAME) or orbit centers (MAN_CENTER_NAME).

6.2.8.14 It is recommended that each maneuver data block be unique from all other maneuver data blocks in at least one of the following respects:

- 1) the thruster ID is different (THR_ID)
- 2) the maneuver basis (MAN_BASIS)
- 3) the maneuver is based upon a unique orbit determination, navigation solution or Monte Carlo simulation (e.g., MAN_OD_ID)
- 4) the reference frame is unique (MAN_REF_FRAME)
- 5) the orbit center is unique (MAN_CENTER_NAME)

6) the data interval timespan is unique (i.e., has no overlap with any other data interval(s))

6.2.8.15 All maneuver events in the OCM shall be **time-tagged by either a relative time** (e.g., DT=20157.26) measured in seconds with respect to the epoch time specified via the MAN_EPOCH_TZERO keyword (or default epoch in DEF_EPOCH_TZERO if MAN_EPOCH_TZERO is not specified), **or an absolute time** (e.g., T=2018-11-13T11:13:20.5Z as formatted in Section 7.5.9) epoch time.

6.2.8.16 The message creator shall specify the maneuver time history elements of information (MAN_EOI) that follow the maneuver time tag (DT= or T= as discussed above) on each and every maneuver time history line, stipulated in comma-delimited format from any combination of the options shown in Table 6-9:

Table 6-9: OCM Data: Selectable maneuver fields in the maneuver time history data

CCSDS PROPOSED STANDARD FOR ORBIT DATA MESSAGES

Keyword	Description	Units	Examples of Values
MAN_DURA	The maneuver duration (0=impulsive; non-zero for ΔV , thrust and/or acceleration-imparted event)	s	200.0
DV_X	Velocity increment ΔV_X in the selected maneuver reference frame. The actual ΔV should be impulsively applied at a time of (DT= or T= <time tag> + ½ (DV_DUR)).	m/s	1.0
DV_Y	Velocity increment ΔV_Y in the selected maneuver reference frame. The actual ΔV should be impulsively applied at a time of (DT= or T= <time tag> + ½ (DV_DUR)).	m/s	2.0
DV_Z	Velocity increment ΔV_Z in the selected maneuver reference frame. The actual ΔV should be impulsively applied at a time of (DT= or T= <time tag> + ½ (DV_DUR)).	m/s	3.0
DV_SIGMA	One-sigma percent error on ΔV magnitude	%	2.0
DV_DMASS	The mass change to the <u>host</u> (where a NEGATIVE VALUE denotes a mass decrement/loss) associated with this ΔV event	kg	-1.0
DEPLOY_ID	Free-text identifier of the resulting “child” object deployed from this host during TIME_SPAN. Setting DEPLOY_ID to zero “0” indicates that a deployment did not occur at this time tag.	n/a	CubeSat_001
DEPLOY_DV_X	Velocity increment ΔV_X of the deployed “child” object measured in the selected maneuver reference frame. The actual ΔV should be impulsively applied at a time of (DT= or T= <time tag> + ½ (DV_DUR)).	m/s	1.0
DEPLOY_DV_Y	Velocity increment ΔV_Y of the deployed “child” object measured in the selected maneuver reference frame. The actual ΔV should be impulsively applied at a time of (DT= or T= <time tag> + ½ (DV_DUR)).	m/s	2.0
DEPLOY_DV_Z	Velocity increment ΔV_Z of the deployed “child” object measured in the selected maneuver reference frame. The actual ΔV should be impulsively applied at a time of (DT= or T= <time tag> + ½ (DV_DUR)).	m/s	3.0
DEPLOY_MASS	Mass of the deployed “child” object post-deployment	kg	1.0
THR_ID	Thruster ID (non-negative integer number)	n/a	1
THR_X	Thrust component T_X measured in the selected maneuver reference frame	N	1.0
THR_Y	Thrust component T_Y measured in the selected maneuver reference frame	N	2.0
THR_Z	Thrust component T_Z measured in the selected maneuver reference frame	N	3.0
THR_SIGMA	One-sigma percent error on thrust magnitude	%	1.0
THR_INTERP	Thrust vector Euler axis/angle interpolation mode between current and next thrust line	n/a	OFF ON
THR_ISP	Thrust specific impulse	s	330.0
THR_EFFIC	Thrust efficiency “ η ” ranging between 0.0 and 1.0	n/a	0.95
THR_DMASS	Additional mass change (where a negative number denotes a mass decrement/loss to the host) associated with this thrust interval, beyond the mass change already prescribed by the rocket equation	Kg	-5.0
ACC_X	Acceleration component A_X in the selected maneuver frame	m/s ²	.01
ACC_Y	Acceleration component A_Y in the selected maneuver frame	m/s ²	.02
ACC_Z	Acceleration component A_Z in the selected maneuver frame	m/s ²	.03
ACC_SIGMA	One-sigma percent error on acceleration magnitude	%	1.0
ACC_INTERP	Acceleration vector Euler axis/angle interpolation mode between current and next acceleration line	n/a	OFF ON
ACC_DMASS	Additional mass change (where a negative number denotes a mass decrement/loss to the host) associated with this acceleration interval	kg	-5.0

6.2.8.17 Specification of **ΔV parameters** allows modeling of impulsive maneuvers, i.e., maneuvers where the space object's velocity is instantaneously changed. Importantly, note that such impulsive maneuvers can and should be accompanied by the duration of the actual maneuver if/when known.

6.2.8.17.1 Maneuver time history lines shall be based upon only one host/parent space object.

6.2.8.17.2 Associated with this single host, the mass and impulsive ΔV of any deployed "child" objects of a parent/child deployment sequence may also be characterized in the OCM maneuver time history.

6.2.8.17.3 Such objects shall be identified by the Deployed Object Number (DON), a positive number starting at "1" and incrementing through all deployed objects until "N" objects have separated.

6.2.8.17.4 Where appropriate (e.g. with spring deployment mechanisms), the OCM creator shall provide both host and deployed object impulsive ΔV s to model/incorporate both the child's deployment ΔV as well as the retrograde ΔV imparted to the host by the spring (e.g., as a ratio of the host and deployed object relative masses such that momentum is conserved).

6.2.8.18 Specification of **thrusting parameters** provides a finite burn capability. In the case of low-thrust, long-duration burns, sequential low-thrust interval maneuver lines can be used to reflect the evolution of the low-thrust maneuver thrust parameters.

6.2.8.18.1 Multiple thruster maneuver contributions may only be represented as separate maneuver time history data blocks.

6.2.8.18.2 Thrust for any thruster shall be presumed to be "OFF" until explicitly turned "ON" by setting one or more of that thruster's maneuver thrust components (THR_X, THR_Y and/or THR_Z) to a non-zero value.

6.2.8.18.3 Thrusters may be subsequently turned "OFF" by setting all of that thruster's maneuver thrust components to zero (i.e., THR_X = THR_Y = THR_Z = 0.0).


6.2.8.18.4 The thrusting maneuver specifications include the ability to specify duty cycles (DUTY_CYCLE_TYPE \neq NONE) based on either a reference direction or reference time. **Relationships between such duty cycle parameters is described in ANNEX C, Section C3.** When a duty cycle is invoked, specification of the reference direction, reference time and any/all other duty cycle parameters relevant to that duty cycle type is mandatory. Optionally, "Minimum number of repeats" and "Maximum number of repeats" may be specified.

6.2.8.19 Specification of **acceleration parameters** allows aggregate modeling of both maneuvers and any additional non-conservative perturbations that are not already specified in the "OCM Perturbations Specification" section (above). This allows the OCM originator to model and share such maneuver and perturbations information without the OCM recipient needing to do such modeling. Note that since additional non-conservative perturbations are

CCSDS PROPOSED STANDARD FOR ORBIT DATA MESSAGES

allowed, thrust or ΔV specifications on the same line may be inconsistent with the accompanying acceleration parameters.

Table 6-10: OCM Data: Maneuver Specification



CCSDS PROPOSED STANDARD FOR ORBIT DATA MESSAGES

Keyword	Description	Units	Default (if any)	Examples of Values	Mandatory
MAN_START	Start of a maneuver data block specification	n/a			Yes
COMMENT	Comments (a contiguous set of one or more comment lines are allowed in the OCM Maneuver Specification only immediately after the MAN_START key word; see 7.7 for comment formatting rules).	n/a		COMMENT This is a comment	No
MAN_ID	Optional alphanumeric free-text string containing the identification number for this maneuver	n/a		E_W_20160305B	No
MAN_OD_ID	Optional alphanumeric free-text string containing the identification number of the orbit determination upon which this maneuver data is based	n/a		OD_20181122A	No
MAN_BASIS	Basis of this maneuver time history data, which shall be selected from one of the following values: <ol style="list-style-type: none"> 1. "CANDIDATE" for a proposed operational or a hypothetical (i.e., mission design and optimization studies) future maneuver 2. "PLANNED" for a currently planned future maneuver 3. "ANTICIPATED" for a non-cooperative future maneuver that is anticipated (i.e. likely) to occur. 4. "DETERMINED_TLM" when a past maneuver is determined from propulsion and attitude system telemetry in near-real-time for reconstruction 5. "DETERMINED_OD" when a past maneuver is estimated from observation-based orbit determination reconstruction and/or calibration. 	n/a	PLANNED	DETERMINED_TLM CANDIDATE	No
MAN_IS_ADDITIVE	Specifies (by either YES or NO) whether this maneuver is additive with other specified time-overlapping maneuvers when they share the same maneuver basis (MAN_BASIS). Note that if "NO" is selected, such time-overlapping maneuvers are to be interpreted as being multiple approaches to characterize the same composite (total) maneuver profile.	n/a	NO	YES NO	Yes (defaults to "NO")
MAN_PREV_ID	Optional alphanumeric free-text string containing the identification number of the previous maneuver for this MAN_BASIS. Note: if the message is not part of a sequence of maneuver messages or if this maneuver is the first in a sequence of maneuvers, then MAN_PREV_ID should be excluded from this message.	n/a		E_W_20160305A	No
MAN_PREV_TIME	Identifies the completion time of the previous maneuver for this MAN_BASIS. This time may be specified as either "DT=YYY", where "YYY" contains relative time in seconds (relative to MAN_EPOCH_TZERO if specified or DEF_EPOCH_TZERO if not), or "T=<epoch>" (see 7.5.10 for formatting rules.).	n/a		DT=50.0 T=2001-11-06T11:17:33 T=2002-204T15:56:23Z	No
MAN_NEXT_ID	Optional alphanumeric free-text string containing the identification number of the next maneuver for this MAN_BASIS. Note: if the message is not part of a sequence of maneuver messages or if this maneuver is the last in a sequence of maneuvers, then MAN_NEXT_ID should be excluded from this message.	n/a		E_W_20160305C	No
MAN_NEXT_TIME	Identifies the start time of the next maneuver for this MAN_BASIS. This time may be specified as either "DT=YYY", where "YYY" contains relative time in seconds (relative to MAN_EPOCH_TZERO if specified or DEF_EPOCH_TZERO if not), or "T=<epoch>" (see 7.5.10 for formatting rules.).	n/a		DT=50.0 T=2001-11-06T11:17:33 T=2002-204T15:56:23Z	No

CCSDS PROPOSED STANDARD FOR ORBIT DATA MESSAGES

Keyword	Description	Units	Default (if any)	Examples of Values	Mandatory
MAN_PURPOSE	The user can specify the intention(s) of the maneuver. Multiple maneuver purposes can be provided as a comma-delimited list. While there is no CCSDS-based restriction on the value for this free-text keyword, it is suggested to use: Aerobraking (AEROBRAKE) Attitude adjust (ATT_ADJUST) Collision avoidance (COLA) Deployment (DEPLOY) Disposal (DISPOSAL) Gravity assist flyby targeting (GRAV_ASSIST) Launch & Early Orbit (LEOP) Maneuver cleanup (MNVN_CLEANUP) Mass adjust (MASS_ADJUST) Momentum desaturation (MOM_DESAT) Orbit adjust (ORBIT_ADJUST) Orbit trim (TRIM) Other (OTHER) Period adjustment (PERIOD_ADJ) Pointing Request Message (PRM_ID_xxxx) Relocation (RELOCATION) Science objective (SCI_OBJ) Spin rate adjust (SPIN_RATE_ADJUST) Station-keeping (SK) Trajectory correction (TRAJ_CORR)	n/a		DISPOSAL	No
MAN_EOI	The comma-delimited ordered set of maneuver elements of information to follow the maneuver time tag (DT= or T= as discussed above) on every maneuver time history line, with elements of information as listed in 6.2.8.1.	n/a		THR_ID, THR_X, THR_Y, THR_Z, THR_ISP, THR_EFFIC, THR_DMASS, DV_X, DV_Y, DV_Z	Yes
MAN_PRED_SOURCE	For future maneuvers, specifies the source of the orbit and/or attitude state(s) upon which the maneuver is based. While there is no CCSDS-based restriction on the value for this free-text keyword, it is suggested to consider using ORB_ID and OD_ID keywords as described in Tables 6-4 and 6-10 respectively, or a combination thereof.	n/a		OD_5	No
MAN_CENTER_NAME	Origin of maneuver central body, which may be a natural solar system body (planets, asteroids, comets, and natural satellites), including any planet barycenter or the solar system barycenter, or another spacecraft. See ANNEX B, Section B2, for acceptable values (and the procedure to propose new values).	n/a	EARTH	EARTH MOON SOLAR SYSTEM BARYCENTER SUN ISS EROS EARTH SUN L2	No
MAN_EPOCH_TZERO	Reference epoch for all relative times in the maneuver time history block. See 7.5.10 for formatting rules. The time system of MAN_EPOCH_TZERO may be set per Annex B, Section B3 via the "MAN_TIME_SYSTEM" keyword.	§7.5.9	<DEF_EPOCH_TZERO>	2001-11-06T11:17:33	No
MAN_TIME_SYSTEM	Timing system of MAN_EPOCH_TZERO, selected per Annex B, Section B3.	n/a	<DEF_TIME_SYSTEM>	UTC UT1	No

CCSDS PROPOSED STANDARD FOR ORBIT DATA MESSAGES

Keyword	Description	Units	Default (if any)	Examples of Values	Mandatory
MAN_REF_FRAME	Reference frame in which the maneuver vector direction data is provided, if not intrinsic to the definition of the maneuver data. Select from the accepted set of values indicated in ANNEX B, Section B4 (and note the procedure to propose a new value, if this set of existing ANNEX B values does not accommodate your particular use case). The reference frame must be the same for all data elements within a given Maneuver Time History block.	n/a	TNW	J2000	No
MAN_FRAME_EPOCH	Epoch of the maneuver data reference frame, if not intrinsic to the definition of the reference frame. See 7.5.10 for formatting rules.	§7.5.9		2001-11-06T11:17:33 2002-204T15:56:23Z	No
GRAV_ASSIST_NAME	Origin of maneuver gravitational assist body, which may be a natural solar system body (planets, asteroids, comets, and natural satellites), including any planet barycenter or the solar system barycenter, or another spacecraft. See ANNEX B, Section B2, for acceptable CENTER_NAME values (and the procedure to propose new values).	n/a	EARTH	EARTH MOON SOLAR SYSTEM BARYCENTER SUN ISS EROS EARTH SUN L2	No

CCSDS PROPOSED STANDARD FOR ORBIT DATA MESSAGES

Keyword	Description	Units	Default (if any)	Examples of Values	Mandatory
DUTY_CYCLE_TYPE	<p>Specifies the type of duty cycle type to use for these maneuver time history section:</p> <ul style="list-style-type: none"> NONE denotes full/continuous thrust; TIME denotes a time-based duty cycle driven by time past a reference time and the duty cycle ON and OFF durations; PHASE_ANGLE denotes a duty cycle driven by the phasing/clocking of a space object body frame "trigger" direction past a reference direction CONE_ANGLE denotes a duty cycle driven by the passage of a space object body frame "trigger" direction past ON and OFF conical angles about a reference direction. 	n/a	NONE	NONE TIME PHASE_ANGLE CONE_ANGLE	No
DC_WIN_OPEN	<p>For ALL duty cycle types, specifies the start time of the duty cycle-based maneuver window that occurs on or prior to the actual maneuver execution start time. For example, this may identify the time at which the satellite is first placed into a special duty-cycle-based maneuver mode.</p> <p>This start time may be specified as either "DT=YYY", where "YYY" contains relative time in seconds (relative to MAN_EPOCH_TZERO if specified or DEF_EPOCH_TZERO if not), or "T=<epoch>" (see 7.5.10 for formatting rules.).</p> <p>Note 1: DC_WIN_OPEN is mandatory if DUTY_CYCLE_TYPE ≠ NONE</p>	n/a		DT=50.0 T=2001-11-06T11:17:33 T=2002-204T15:56:23Z	(see Note 1)
DC_WIN_CLOSE	<p>Specifies the end time of the duty cycle-based maneuver window that occurs on or after the actual maneuver execution end time. For example, this may identify the time at which the satellite is taken out of a special duty-cycle-based maneuver mode.</p> <p>This end time may be specified as either "DT=YYY", where "YYY" contains relative time in seconds (relative to MAN_EPOCH_TZERO if specified or DEF_EPOCH_TZERO if not), or "T=<epoch>" (see 7.5.10 for formatting rules.).</p> <p>Note 1: DC_WIN_CLOSE is mandatory if DUTY_CYCLE_TYPE ≠ NONE</p>	n/a		DT=100.0 T=2001-11-07T51:17:33 T=2002-204T15:58:03Z	(see Note 1)
DC_MIN_CYCLES	<p>Minimum number of "ON" duty cycles (may override MAN_WIN_CLOSE).</p> <p>Note 1: DC_WIN_CLOSE is mandatory if DUTY_CYCLE_TYPE ≠ NONE</p>	DCs	0	5	No (has default value of "0")
DC_MAX_CYCLES	<p>Maximum number of "ON" duty cycles (may override MAN_WIN_CLOSE).</p> <p>Note 1: DC_WIN_CLOSE is mandatory if DUTY_CYCLE_TYPE ≠ NONE</p>	DCs	(unlimited)	5	No (defaults to no limiting value)

CCSDS PROPOSED STANDARD FOR ORBIT DATA MESSAGES

Keyword	Description	Units	Default (if any)	Examples of Values	Mandatory
DC_EXEC_BEGIN	<p>(Provided for informational purposes only): The actual start time of the initial duty cycle-based maneuver sequence execution. DC_EXEC_BEGIN occurs on or after DC_WIN_OPEN.</p> <p>This maneuver execution start time may be specified as either "DT=YYY", where "YYY" contains relative time in seconds (relative to MAN_EPOCH_TZERO if specified or DEF_EPOCH_TZERO if not), or "T=<epoch>" (see 7.5.10 for formatting rules.).</p>	n/a		DT=50.0 T=2001-11-06T11:17:33 T=2002-204T15:56:23Z	No
DC_EXEC_END	<p>(Provided for informational purposes only): The actual end time of the final duty cycle-based maneuver sequence execution. DC_EXEC_END occurs on or prior to DC_WIN_CLOSE.</p> <p>This maneuver execution end time may be specified as either "DT=YYY", where "YYY" contains relative time in seconds (relative to MAN_EPOCH_TZERO if specified or DEF_EPOCH_TZERO if not), or "T=<epoch>" (see 7.5.10 for formatting rules.).</p>	n/a		DT=100.0 T=2001-11-07T15:17:33 T=2002-204T15:58:03Z	No
DC_REF_TIME	<p>Specifies the THRUST duty cycle "on" reference time tag specified either as "DT=YYY", where "YYY" contains relative time in seconds (relative to MAN_EPOCH_TZERO if specified or DEF_EPOCH_TZERO if not), or "T=<epoch>".</p> <p>Note 1: DC_REF_TIME is mandatory if DUTY_CYCLE_TYPE is set to "TIME"</p> <p>Note 2: Depending upon the EPOCH_TZERO definition, DC_REF_TIME relative times may be negative.</p>	s		DT=8000.0 T=2001-11-06T11:17:33	(see Note 1)
DC_ON_DURA	<p>For time-based thruster duty cycle (DUTY_CYCLE_TYPE=TIME), specifies duty cycle "ON" duration, initiated at first satisfaction of the burn "ON" time or phase angle constraints or at completion of a Duty Cycle "OFF" duration (in seconds).</p> <p>Note 1: DC_ON_DURA is mandatory if DUTY_CYCLE_TYPE is set to "TIME"</p>	s		200.0	(see Note 1)
DC_OFF_DURA	<p>For time-based thruster duty cycle (DUTY_CYCLE_TYPE=TIME), specifies duty cycle "OFF" duration, initiated at the completion of a burn "ON" duration or upon a phase angle constraint violation.</p> <p>Note 1: DC_OFF_DURA is mandatory if DUTY_CYCLE_TYPE is set to "TIME"</p>	s		200.0	(see Note 1)

CCSDS PROPOSED STANDARD FOR ORBIT DATA MESSAGES

Keyword	Description	Units	Default (if any)	Examples of Values	Mandatory
DC_REF_DIR	For phase angle or cone-based thruster duty cycles (DUTY_CYCLE_TYPE=PHASE_ANGLE or CONE_ANGLE), specifies the "ON" reference unit vector direction in the "MAN_REF_FRAME" reference frame (i.e., the <u>start</u> of the duty cycle "ON" and <u>NOT</u> the duty cycle midpoint). Note 1: DC_REF_DIR is mandatory if DUTY_CYCLE_TYPE is set to "PHASE_ANGLE" or "CONE_ANGLE"	n/a		1.0 0.0 0.0	(see Note 1)
DC_BODY_TRIGGER	Specifies the body frame reference unit vector direction which, when it clocks past the DC_REF_DIR direction, initiates thrusting. Note 1: DC_BODY_TRIGGER is mandatory if DUTY_CYCLE_TYPE is set to "PHASE_ANGLE" or "CONE_ANGLE"	n/a		.707 0.0 .707	(see Note 1)
DC_PA_START	Thrust phase angle start. Note 1: DC_PA_START is mandatory if DUTY_CYCLE_TYPE is set to "PHASE_ANGLE"	deg		25.0	(see Note 1)
DC_PA_STOP	Thrust phase angle stop. Note 1: DC_PA_STOP is mandatory if DUTY_CYCLE_TYPE is set to "PHASE_ANGLE"	deg		35.0	(see Note 1)
DC_CONE_ON	Thrust conical angle start. Note 1: DC_CONE_ON is mandatory if DUTY_CYCLE_TYPE is set to "CONE_ANGLE"	deg		35.0	(see Note 1)
DC_CONE_OFF	Thrust conical angle stop. Note 1: DC_CONE_OFF is mandatory if DUTY_CYCLE_TYPE is set to "CONE_ANGLE"	deg		35.0	(see Note 1)
... < Insert maneuver lines here >	Maneuver time history data/content shall be provided as specified in sections 6.2.8.16.				Yes
MAN_STOP	End maneuver data block specification	n/a			Yes

6.2.9 OCM DATA: PERTURBATIONS SPECIFICATION

6.2.9.1 Table 6-5 provides an overview of the OCM Perturbations Specification section. Only those keywords shown in Table 6-5 shall be used in OCM perturbations specification.

6.2.9.2 Keyword values shall be provided in the units specified in the "Units" column of Table 6-5.

6.2.9.3 The order of occurrence of these OCM Perturbations Specification keywords shall be fixed as shown in Table 6-5.

CCSDS PROPOSED STANDARD FOR ORBIT DATA MESSAGES

6.2.9.4 The OCM Perturbations Specification section is optional; “mandatory” in the context of Table 6-5 denotes those keywords which must be included in this section if this section is included.

6.2.9.5 Only one OCM Perturbations Specification section shall appear in an OCM.

6.2.9.6 The OCM Perturbations Specification section shall be delimited by two keywords: PERT_START and PERT_STOP.

Table 6-11: OCM Data: Perturbations Specification

Keyword	Description	Units	Default (if any)	Examples of Values	Mandatory
PERT_START	Start of the perturbations specification	n/a			Yes
COMMENT	Comments (a contiguous set of one or more comment lines are allowed in the OCM Perturbations Specification only immediately after the PERT_START key word; see 7.7 for comment formatting rules).	n/a		COMMENT This is a comment	No
PERT_CENTER_NAME	Origin of the perturbations central bodies, which may be a natural solar system body (planets, asteroids, comets, and natural satellites), including any planet barycenter or the solar system barycenter, or another spacecraft. Select from the accepted set of values indicated in ANNEX B, Section B2 (and note the procedure to propose a new value, if this set of existing ANNEX B values does not accommodate your particular use case).	n/a	EARTH	EARTH MOON SOLAR SYSTEM BARYCENTER SUN ISS EROS EARTH_SUN_L2	No
ATMOSPHERIC_MODEL	Name of atmosphere model. This is a free text field, so if the examples on the right are insufficient, others may be used.	n/a		MSISE90 NRLMSIS00 J70 J71 JRob DTM JB2008 ...	No
GRAVITY_MODEL	The name of the geopotential model for central body, followed by the degree and order of the spherical harmonic coefficients applied. Note that specifying a zero value for “order” (i.e. 2 0) denotes zonals (J ₂ ... J _D) only. This is a free text field, so if the examples on the right are insufficient, others may be used.	n/a		EGM-96: 36 36 WGS-84: 8 8 GGM-01: 12 12 TEG-4: 8 2	No
EQUATORIAL_RADIUS	Oblate spheroid equatorial radius	m		6378137.0	No
GM	Gravitational Coefficient of attracting body (Gravitational Constant x Central Mass)	km ³ /s ²		3.986004e5	No
N_BODY_PERTURBATIONS	One OR MORE (N-body) gravitational perturbations bodies used. Values, listed serially in comma-delimited fashion, denote a natural solar or extra-solar system body (stars, planets, asteroids, comets, and natural satellites), or another spacecraft. Note that only those entries (or those procedurally added to the CENTER_NAME content as specified in ANNEX B) that are denoted as an “ Attracting Body ” in ANNEX B, Section B2 are acceptable values.	n/a		MOON, SUN, JUPITER	No

Commented [DL03]: Should this become a SANA entry?

Commented [DL04]: Should this become a SANA entry?

CCSDS PROPOSED STANDARD FOR ORBIT DATA MESSAGES

Keyword	Description	Units	Default (if any)	Examples of Values	Mandatory
CENTRAL_BODY_ROTA	Central body angular rotation rate, measured about the major principal axis of the inertia tensor of the central body, relating inertial and central-body-fixed reference frames.	deg/s		4.17807421629e-3	No
OBLATE_FLATTENING	Inverse of the central body's oblate spheroid oblateness for the polar-symmetric oblate central body model.	n/a		298.257223563	No
OCEAN_TIDES_MODEL	Name of ocean tides model (optionally specify order or constituent effects, diurnal, semi-diurnal, etc.)	n/a		DIURNAL SEMI-DIURNAL	No
SOLID_TIDES_MODEL	Name of solid tides model (optionally specify order or constituent effects, diurnal, semi-diurnal, etc.)	n/a		DIURNAL SEMI-DIURNAL	No
REDUCTION_THEORY	Specification of the reduction theory used for precession and nutation modeling. This is a free text field, so if the examples on the right are insufficient, others may be used.	n/a		IAU1976/FK5 IAU2010 IERS1996	No
ALBEDO	Name of the albedo model	n/a		STK	No
ALBEDO_GRID_SIZE	# of grid points used in the albedo model	n/a		100	No
SHADOW_MODEL	Shadow modeling for Solar Radiation Pressure; dual cone uses both umbra/penumbra regions. Selected option should be one of "NONE", "CYLINDRICAL" or "DUAL CONE"	n/a		NONE CYLINDRICAL DUAL CONE	No
SHADOW_BODIES	Comma-separated list of planetary bodies for which SRP shadowing is modeled. See ANNEX B for acceptable PERT_CENTER_NAME values (and the procedure to propose new values).	n/a	Earth	Earth, Moon	No
SRP_MODEL	Name of SRP model. This is a free text field, so if the examples on the right are insufficient, others may be used.	n/a		GPS_ROCK BOX_WING CANNONBALL COD ...	No
SPACE_WX_SOURCE	Free text field specifying the source and version of the Space Weather data used in the creation of this message. Multiple space weather sources can be specified in a comma-delimited fashion.	n/a		e.g., "CelesTrak space weather file downloaded from http://celestrak.com/SpaceData/SW-Last5Years.txt at 2001-11-08T00:00:00"	No
INTERP_METHOD_SPWX	Free text field specifying the method used to select or interpolate any and all sequential space weather data (K_p a_p Dst $F_{10.7}$ $M_{10.7}$ $S_{10.7}$ $Y_{10.7}$)	n/a		PRECEDING_VALUE NEAREST_NEIGHBOR LINEAR LAGRANGE_ORDER 5	No
FIXED_GEOMAG_KP	A fixed (time invariant) value of the planetary 3-hour-range geomagnetic index K_p used to override the normal time-varying 3-hourly K_p values (e.g., obtained from SPACE_WX_SOURCE) for drag perturbations estimation throughout this message's timespan. K_p is the planetary 3-hour-range mean standardized index derived from the K-index of 13 geomagnetic observatories between 44 degrees and 60 degrees northern or southern geomagnetic latitude. The scale is 0 to 9 expressed in thirds of a unit, e.g. 5- is 4 2/3, 5 is 5 and 5+ is 5 1/3. This planetary index is designed to measure solar particle radiation by its magnetic effects.	nT		3.2	No

CCSDS PROPOSED STANDARD FOR ORBIT DATA MESSAGES

Keyword	Description	Units	Default (if any)	Examples of Values	Mandatory
FIXED_GEOMAG_AP	<p>A fixed (time invariant) value of the 3-hourly (equivalent range) geomagnetic index a_p used to override the normal time-varying 3-hourly a_p values (e.g., obtained from SPACE_WX_SOURCE) for drag perturbations estimation throughout this message's timespan.</p> <p>The 3-hourly (equivalent range) geomagnetic index a_p reports the amplitude of planetary geomagnetic activity for a given day and is translated from the K_p index.</p>	nT		21	No
FIXED_GEOMAG_DST	<p>A fixed (time invariant) value of the planetary 1-hour-range geomagnetic index Dst used to override the normal time-varying daily Dst values (e.g., obtained from SPACE_WX_SOURCE) for drag perturbations estimation throughout this message's timespan.</p> <p>The Disturbance Storm Time (Dst) index is a proxy for magnetic activity derived from a network of near-equatorial geomagnetic observatories that measures the intensity of the globally symmetrical equatorial electrojet (the storm-time "ring current" in the inner magnetosphere).</p>	nT		-20	No
FIXED_F10P7	A fixed (time invariant) value of the solar flux daily proxy $F_{10.7}$ used to override the normal time-varying daily $F_{10.7}$ values (e.g., obtained from SPACE_WX_SOURCE) for drag perturbations estimation throughout this message's timespan.	Solar Flux Units = 10^4 Jansky = 10^{-22} W/(m ² *Hz)		120.0	No
FIXED_F10P7_MEAN	A fixed (time invariant) value of the solar flux 81-day running center-averaged proxy $F_{10.7}$ used to override the normal time-varying averaged $F_{10.7}$ values (e.g., obtained from SPACE_WX_SOURCE) for drag perturbations estimation throughout this message's timespan.	Solar Flux Units = 10^4 Jansky = 10^{-22} W/(m ² *2*Hz)		132.0	No
FIXED_M10P7	<p>A fixed (time invariant) value of the solar flux daily proxy $M_{10.7}$ used to override the normal time-varying daily $M_{10.7}$ values (e.g., obtained from SPACE_WX_SOURCE) for drag perturbations estimation throughout this message's timespan.</p> <p>$M_{10.7}$ is derived from the Mg II core---o---wing ratio that originated from the NOAA series operational satellites, e.g., NOAA---16,---17,---18, which host the Solar Backscatter Ultraviolet (SBUV) spectrometer</p>	10^{-22} W/(m ² *2*Hz)		120.0	No
FIXED_M10P7_MEAN	A fixed (time invariant) value of the solar flux 81-day running center-averaged proxy $M_{10.7}$ used to override the normal time-varying averaged $M_{10.7}$ values (e.g., obtained from SPACE_WX_SOURCE) for drag perturbations estimation throughout this message's timespan.	10^{-22} W/(m ² *2*Hz)		120.0	No

CCSDS PROPOSED STANDARD FOR ORBIT DATA MESSAGES

Keyword	Description	Units	Default (if any)	Examples of Values	Mandatory
FIXED_S10P7	A fixed (time invariant) value of the solar flux daily proxy $S_{10.7}$ used to override the normal time-varying daily $S_{10.7}$ values (e.g., obtained from SPACE_WX_SOURCE) for drag perturbations estimation throughout this message's timespan. $S_{10.7}$ is the integrated 26–34 nm solar irradiance measured by the Solar Extreme Ultraviolet Monitor (SEM) instrument on the NASA/ESA Solar and Heliospheric Observatory (SOHO) research satellite	10^{-22} W/(m ² *Hz)		120.0	No
FIXED_S10P7_MEAN	A fixed (time invariant) value of the solar flux 81-day running center-averaged proxy $S_{10.7}$ used to override the normal time-varying averaged $S_{10.7}$ values (e.g., obtained from SPACE_WX_SOURCE) for drag perturbations estimation throughout this message's timespan.	10^{-22} W/(m ² *Hz)		120.0	No
FIXED_Y10P7	A fixed (time invariant) value of the solar flux daily proxy $Y_{10.7}$ used to override the normal time-varying daily $Y_{10.7}$ values (e.g., obtained from SPACE_WX_SOURCE) for drag perturbations estimation throughout this message's timespan. $Y_{10.7}$ is a composite index of the X_{b10} and Lyman- α solar indices, weighted to represent mostly X_{b10} during solar maximum and to represent mostly Lyman- α during moderate and low solar activity.	10^{-22} W/(m ² *Hz)		120.0	No
FIXED_Y10P7_MEAN	A fixed (time invariant) value of the solar flux 81-day running center-averaged proxy $Y_{10.7}$ used to override the normal time-varying averaged $Y_{10.7}$ values (e.g., obtained from SPACE_WX_SOURCE) for drag perturbations estimation throughout this message's timespan.	10^{-22} W/(m ² *Hz)		120.0	No
PERT_STOP	End of the perturbations specification	n/a			Yes

6.2.10 OCM DATA: ORBIT DETERMINATION DATA

6.2.10.1 Table 6-6 provides an overview of the OCM orbit determination data section. Only those keywords shown in Table 6-6 shall be used in OCM orbit determination data specification.

6.2.10.2 Keyword values shall be provided in the units specified in the “Units” column of Table 6-6.

6.2.10.3 The order of occurrence of these OCM Orbit Determination Data keywords shall be fixed as shown in Table 6-6.

6.2.10.4 The “OCM Data: Orbit Determination Data” section is optional; “mandatory” in the context of Table 6-6 denotes those keywords which must be included in this section if this section is included.

6.2.10.5 At most, only one Orbit Determination Data section shall appear in an OCM.

6.2.10.6 Orbit determination data in the OCM shall be indicated by two keywords: OD_START and OD_STOP.

6.2.10.7 All orbit determination event times shall be specified relative to the orbit determination epoch specified via the OD_EPOCH keyword (in SI days, with one day = 86400.0 s) as a double precision number. Event times may be negative, zero or positive, depending upon the definition of the event time (i.e., OD_EPOCH with respect to event time versus event time with respect to OD_EPOCH).


6.2.10.8 A “Track” is defined above in Section 1.6.

6.2.10.9 This orbit determination parameters section should reflect the orbit determination settings used to generate all orbit, covariance and state transition matrix sections of the message that are based upon “determined” orbit solutions.

6.2.10.10 If an orbit determination parameters section is included in the message, it is recommended that a corresponding perturbations section be included as well to specify the perturbations incorporated in the orbit determination.

NOTE: THIS SECTION APPLIES TO ALL ORBIT AND COVAR DATA BASED UPON “DETERMINED” ORBIT SOLUTIONS

Table 6-12: OCM Data: Orbit Determination Data



CCSDS PROPOSED STANDARD FOR ORBIT DATA MESSAGES

Keyword	Description	Units	Default (if any)	Examples of Values	Mandatory
OD_START	Start of an orbit determination data section	n/a		n/a	Yes
COMMENT	Comments (a contiguous set of one or more comment lines are allowed in the OCM Orbit Determination Data section only immediately after the OD_START key word; see 7.7 for comment formatting rules).	n/a		COMMENT This is a comment	No
OD_ID	Optional identification number for this orbit determination	n/a		OD_20160402	No
OD_PREV_ID	Optional identification number for the previous orbit determination. Note: if this orbit determination is the first one, then OD_PREV_ID should be excluded from this message.	n/a		OD_20160401	No
OD_METHOD	Type of orbit determination method used to produce the orbit estimate. This is a free-text field, but commonly used methods could include Batch Weighted Least Squares (BWLS), Extended Kalman Filter (EKF), Sequential Filter (SF), Square Root Information Filter (SRIF), Sequential Simultaneous Estimation Method (SSEM).	n/a		BWLS, EKF, SF	Yes
OD_EPOCH	UTC epoch of the orbit determination solved-for state (See 7.5.10 for formatting rules.).	n/a		2001-11-06T11:17:33 2002-204T15:56:23Z	Yes
DAYS_SINCE_FIRST_OBS	Days (defined by SEC_PER_DAY duration in the OCM metadata section) elapsed between first accepted observation and OD_EPOCH	d		3.5	No
DAYS_SINCE_LAST_OBS	Days (defined by SEC_PER_DAY duration in the OCM metadata section) elapsed between last accepted observation and OD_EPOCH	d		1.2	No
RECOMMENDED_OD_SPAN	Number of days (defined by SEC_PER_DAY duration in the OCM metadata section) of observations recommended for the OD of the object (<i>useful only for Batch OD systems</i>)	d		5.2	No
ACTUAL_OD_SPAN	Actual time span in days (defined by SEC_PER_DAY duration in the OCM metadata section) used for the OD of the object (NOTE: should equal (DAYS_SINCE_FIRST_OBS - DAYS_SINCE_LAST_OBS))	d		2.3	No
OBS_AVAILABLE	The number of observations available within the actual OD time span	n/a		100	No
OBS_USED	The number of observations accepted within the actual OD time span	n/a		90	No
TRACKS_AVAILABLE	The number of sensor tracks, for the actual time span, that were available for the OD	n/a		33	No
TRACKS_USED	The number of sensor tracks, for the actual time span, that were accepted for the OD	n/a		30	No
MAXIMUM_OBS_GAP	The maximum time between observations in the OD of the object	d		1.0	No
OD_EPOCH_EIGMAJ	Positional error ellipsoid 1σ major eigenvalue at the epoch of the OD	m		58.73	No
OD_EPOCH_EIGMED	Positional error ellipsoid 1σ medium eigenvalue at the epoch of the OD	m		35.7	No
OD_EPOCH_EIGMIN	Positional error ellipsoid 1σ minor eigenvalue at the epoch of the OD	m		21.5	No
OD_MIN_EIGMAJ	The resulting minimum predicted major eigenvalue of the 1σ positional error ellipsoid over the entire TIME_SPAN of the OCM, stemming from this OD	m		21.5	No

CCSDS PROPOSED STANDARD FOR ORBIT DATA MESSAGES

Keyword	Description	Units	Default (if any)	Examples of Values	Mandatory
OD_MAX_EIGMAJ	The resulting maximum predicted major eigenvalue of the 1σ positional error ellipsoid over the entire TIME_SPAN of the OCM, stemming from this OD	m		21.5	No
OD_CONFIDENCE	OD confidence metric, which by definition spans 0 to 100%. (useful only for Filter-based OD systems). The OD confidence metric should be defined by ICD.	Percent		95.3	No
GDOP	Generalized Dilution Of Precision for this orbit determination, based on the observability grammian as defined in Kaplan "Understanding GPS: Principles and Applications". GDOP provides a rating metric of the observability of the element set from the OD. (AWAITING SPECIFIC INPUTS FROM CHERYL)	n/a		.857	No
SOLVE_N	The number of solve-for states in the orbit determination	n/a		6	No
SOLVE_STATES	Free-text comma-delimited description of the state elements solved for in the orbit determination	n/a		POS(3), VEL(3)	No
CONSIDER_N	The number of consider parameters used in the orbit determination	n/a		3	No
CONSIDER_PARAMS	Free-text comma-delimited description of the consider parameters used in the orbit determination	n/a		DRAG, SRP	No
SENSORS_N	The number of sensors used in the orbit determination	n/a		3	No
SENSORS	Free-text comma-delimited description of the sensors used in the orbit determination	n/a		EGLIN, FYLINGDALES	No
INTEG_STEP_SIZE	Integration step size. A value of zero '0' shall be used to denote a variable integration step size, if this optional parameter is specified.	s		60.0	No
CONSIDER_PARAMS	Measurement update interval. A value of zero '0' shall be used to denote a variable measurement update interval, if this optional parameter is specified.	s		86400.0	No
WEIGHTED_RMS	<p>(Useful / valid only for Batch OD systems).</p> <p>The weighted RMS residual ratio, defined as:</p> $\text{Weighted RMS} = \sqrt{\frac{\sum_{i=1}^N w_i (y_i - \hat{y}_i)^2}{N}}$ <p>Where y_i is the observation measurement at the ith time</p> <p>\hat{y}_i is the current estimate of y_i,</p> <p>$w_i = \frac{1}{\sigma_i^2}$ is the weight (sigma) associated with the measurement at the ith time and N is the number of observations.</p> <p>This is a value that can generally identify the quality of the most recent vector update, and is used by the analyst in evaluating the OD process. A value of 1.00 is ideal.</p>	(measurement units)		1.3	No
TDM_IDS	An alphanumeric free-text string containing a comma-separated list of file name(s) and/or associated identification number(s) of Tracking Data Message (TDM) [9] observations upon which this OD is based.	n/a		TDM_0005.txt	No

CCSDS PROPOSED STANDARD FOR ORBIT DATA MESSAGES

Keyword	Description	Units	Default (if any)	Examples of Values	Mandatory
DATA_TYPES	Comma-separated list of observation data types utilized in this orbit determination. Although this is a free-text field, it is recommended at a minimum to use data type descriptor(s) as provided in Table 3-5 of the TDM standard [9] (excluding the DATA_START, DATA_STOP, and COMMENT keywords). Orbit determine event times are in double precision days. Additional descriptors/detail is encouraged if the descriptors of Table 3-5 are not sufficiently clear, e.g., could replace ANGLE_1 and ANGLE_2 with RADEC (e.g., from a telescope), AZEL (e.g., from a ground radar), RANGE (whether from radar or laser ranging), etc.	n/a		n/a	No
OD_STOP	End of an orbit determination data section	n/a		n/a	Yes

6.2.11 OCM DATA: USER-DEFINED PARAMETERS

6.2.11.1 A section of User Defined Parameters may be provided if necessary. In principle, this provides flexibility, but also introduces complexity, non-standardization, potential ambiguity, and potential processing errors. Accordingly, if used, the keywords and their meanings must be described in an ICD. User Defined Parameters, if included in an OCM, should be used as sparingly as possible; their use is not encouraged.

6.2.11.2 The “OCM Data: User-Defined Parameters” section is optional; “mandatory” in the context of Table 6-13 denotes those keywords which must be included in this section if this section is included.

6.2.11.3 At most, only one User-Defined Parameters section shall appear in an OCM.

6.2.11.4 Each user-defined user parameter line may be preceded by one or more comment lines.

6.2.11.5 Table 6-13 provides an overview of the OCM user-defined data section. Only those keywords shown in Table 6-12 shall be used in OCM user-defined data specification.

Table 6-13: OCM Data: User-Defined Parameters

Keyword	Description	Units	Examples of Values	Mandatory
USER_START	Start of a User-defined parameters data block	n/a		Yes
COMMENT	Comments (a contiguous set of one or more comment lines are allowed immediately following the USER_START keyword (See 7.7 for formatting rules.)	n/a	COMMENT This is a comment	No
(USER-DEFINED)	User-defined keyword(s) paired with user-specified variable length character string values. Multiple user-defined parameters may be specified in this manner, but only as necessary to provide essential information that cannot be otherwise conveyed in standard OCM content and accompanying comments.	n/a	EARTH_MODEL = WGS-84	No
USER_STOP	End of a User-defined parameters data block	n/a		Yes

6.3 OCM EXAMPLES AND SUPPLEMENTARY INFORMATION

Example OCMs and associated supplementary (non-normative) information are provided in G-1.

7 ORBIT DATA MESSAGE SYNTAX

7.1 OVERVIEW

This section details the syntax requirements for each of the Orbit Data Messages.

7.2 GENERAL

The Orbit Data Messages (OPM, OMM, OEM or OCM) shall observe the syntax described in 7.3 through 7.7.

7.3 ODM LINES

7.3.1 Each OPM, OMM, OEM or OCM line shall be one of the following:

- Header line;
- Metadata line;
- Data line;
- Comment line; or
- Blank line.

7.3.2 Each OPM, OMM, or OEM line must not exceed 254 ASCII characters and spaces (excluding line termination character[s]).

7.3.3 OCM lines may be of arbitrary length. If exchange between the two parties requires a maximum line length, that limit should be negotiated and specified in an ICD.

7.3.4 Only printable ASCII characters and blanks shall be used. Control characters (such as TAB, etc.) shall not be used, with the exception of the line termination characters specified below.

7.3.5 Blank lines may be used at any position within the file. Blank lines shall have no assignable meaning, and may be ignored.

7.3.6 The first header line must be the first non-blank line in the file.

7.3.7 All lines shall be terminated by a single Carriage Return or a single Line Feed, or a Carriage Return/Line Feed pair or a Line Feed/Carriage Return pair.

7.4 KEYWORD = VALUE NOTATION (I.E., NON-XML) AND ORDER OF ASSIGNMENT STATEMENTS

7.4.1 For the OPM and OMM, all header, metadata, and data lines shall use ‘keyword = value’ notation, abbreviated as KVN.

7.4.1.1 For the OEM, all header and metadata elements shall use KVN notation.

7.4.1.2 OEM ephemeris data lines shall not use KVN format; rather, the OEM ephemeris data line has a fixed structure containing seven required fields (epoch time, three position components, three velocity components), and three optional acceleration components. (See 5.2.4.)

7.4.1.3 OEM covariance matrix epoch and covariance reference frame (if used) shall use KVN format. The OEM covariance data lines shall not use KVN format; rather, the OEM covariance data line has a fixed structure containing from one to six required fields (a row from the 6x6 lower triangular form covariance matrix). (See 5.2.5.)

7.4.1.4 For the OCM, all header and metadata elements shall use KVN notation.

7.4.1.5 All OCM KVN keyword-specified lines can contain interspersed blank lines as desired, for example to enhance message clarity and readability.

7.4.1.6 OCM orbit state time history data lines shall not use KVN format; rather, the structure of such OCM orbit state time history data lines shall be comprised of a contiguous set of lines containing time tag followed by the parameters corresponding to the selected orbit set (See 6.2.4).

7.4.1.7 OCM covariance matrix epoch and covariance reference frame (if used) shall use KVN format. The OCM covariance data lines shall not use KVN format; rather, the OCM covariance data line has a fixed structure which shall be comprised of a contiguous set of lines containing from one to “N” required fields (a row from the N x N lower triangular form of a square covariance matrix) or a single line containing epoch, eigenvalues and eigenvectors. (See 6.2.5.)

7.4.1.8 OCM state transition matrix data lines shall not use KVN format; rather, OCM state transition matrix data shall be comprised of a contiguous set of lines containing a fixed structure as presented in Sec. 6.2.7.

7.4.1.9 OCM maneuver data lines shall not use KVN format; rather, OCM maneuver data shall be comprised of a contiguous set of lines containing a fixed structure as presented in Sec. 6-316.2.8.

7.4.2 The keywords ‘COMMENT’, [wild card]‘_START’ and [wild card]‘_STOP’ are exceptions to the KVN syntax assignment.

7.4.3 Only a single ‘keyword = value’ assignment shall be made on a line.

7.4.4 Keywords must be uppercase and must not contain blanks.

7.4.5 Any white space immediately preceding or following the keyword shall not be significant.

7.4.6 Any white space immediately preceding or following the 'equals' sign shall not be significant.

7.4.7 Any white space immediately preceding the end of line shall not be significant.

7.4.8 The order of occurrence of mandatory and optional KVN assignments shall be fixed as shown in the tables in sections 3, 4, 5 and 6 that describe the OPM, OMM, OEM and OCM keywords.

7.5 VALUES

7.5.1 A non-empty value field must be specified for each mandatory keyword except as noted in §7.4.2 above.

7.5.2 Non-numeric values may contain a mix of lowercase and uppercase letters OR Text value fields must be constructed using only all uppercase. An exception is made for comment values (see 6.2.5 for formatting rules).

Commented [DL05]: To discuss

7.5.3 Integer values shall consist of a sequence of decimal digits with an optional leading sign ('+' or '-'). If the sign is omitted, '+' shall be assumed. Leading zeroes may be used. The range of values that may be expressed as an integer is:

$$-2,147,483,648 \leq x \leq +2,147,483,647 \quad (\text{i.e., } -2^{31} \leq x \leq 2^{31}-1).$$

NOTE – The commas in the range of values above are thousands separators and are used only for readability. They should not appear in an actual message.

7.5.4 Non-integer numeric values may be expressed in either fixed-point or floating-point notation. Both representations may be used within an OPM, OMM, OEM or OCM.

7.5.5 Non-integer numeric values expressed in fixed-point notation shall consist of a sequence of decimal digits separated by a period as a decimal point indicator, with an optional leading sign ('+' or '-'). If the sign is omitted, '+' shall be assumed. Leading and trailing zeroes may be used. At least one digit shall appear before and after a decimal point.

7.5.6 Non-integer numeric values expressed in floating point notation shall consist of a sign, a mantissa, an alphabetic character indicating the division between the mantissa and exponent, and an exponent, constructed according to the following rules:

- a) The sign may be '+' or '-'. If the sign is omitted, '+' shall be assumed.

- b) The mantissa must be a string of no more than 16 decimal digits with a decimal point (‘.’) in the second position of the ASCII string, separating the integer portion of the mantissa from the fractional part of the mantissa.
- c) The character used to denote exponentiation shall be ‘E’ or ‘e’. If the character indicating the exponent and the following exponent are omitted, an exponent value of zero shall be assumed (essentially yielding a fixed point value).
- d) The exponent must be an integer, and may have either a ‘+’ or ‘-’ sign (if the sign is omitted, then ‘+’ shall be assumed).
- e) The maximum positive floating point value is approximately 1.798E+308, with 16 significant decimal digits precision. The minimum positive floating point value is approximately 4.94E-324, with 16 significant decimal digits precision.

7.5.7 Text value fields must be constructed using only **all uppercase or all lowercase**.

7.5.8 Blanks shall not be permitted within numeric values and time strings.

7.5.9 In value fields that are text, an underscore shall be equivalent to a single blank. Individual blanks shall be retained (shall be significant), but multiple contiguous blanks shall be equivalent to a single blank.

7.5.10 In value fields that represent an absolute time tag or epoch, times shall be given in one of the following two formats:

YYYY-MM-DDThh:mm:ss[.d→d][Z]

or

YYYY-DDDThh:mm:ss[.d→d][Z]

where ‘YYYY’ is the year, ‘MM’ is the two-digit month, ‘DD’ is the two-digit day, ‘DDD’ is the three-digit day of year, ‘T’ is constant, ‘hh:mm:ss[.d→d]’ is the time in hours, minutes seconds, and optional fractional seconds; ‘Z’ is an optional time code terminator (the only permitted value is ‘Z’ for Zulu, i.e., UTC). As many ‘d’ characters to the right of the period as required may be used to obtain the required precision, up to the maximum allowed for a fixed point number. All fields shall have leading zeros. (See reference [1], ASCII Time Code A or B.). Where such epochs occur within one second after leap second introduction, the hh:mm:ss portion of the above time specification shall use the convention XX:XX:60.XXXX.

7.5.11 The time system for CREATION_DATE is UTC; for all other keywords representing times or epochs, the time system is determined by the TIME_SYSTEM metadata keyword.

7.6 UNITS IN THE ORBIT DATA MESSAGES

7.6.1 OPM/OMM/OCM UNITS

7.6.1.1 For documentation purposes and clarity only, units may be included as ASCII text after a value in the OPM, OMM and OCM. If units are displayed, they must exactly match the units (including lower/upper case) as specified in tables 3-3, 4-3, 5-3 and 6-4 through 6-12. If units are displayed, then:

- a) there must be at least one blank character between the value and the units text;
- b) the units must be enclosed within square brackets (e.g., '[km]');
- c) multiplication shall be denoted by a single asterisk (e.g., '[N*m]');
- d) division shall be denoted by a single forward slash (e.g., meters per second is m/s);
- e) exponents of units shall be denoted with a double asterisk (i.e., '**', for example, $m^2=m**2$);
- f) The usual order of operations ordering applies (e.g., exponents before multiplication).

7.6.1.2 Some of the items in the applicable tables are dimensionless. The table shows a unit value of 'n/a', which in this case means that there is no applicable units designator for these items (e.g., for ECCENTRICITY). The notation '[n/a]' should not appear in an OPM, OCM or OMM.

7.6.2 OEM UNITS

7.6.2.1 In an OEM ephemeris data line, units shall be km, km/s, and km/s**2 for position, velocity, and acceleration components, respectively, but the units shall not be displayed.

7.6.2.2 In an OEM covariance matrix line, units shall be km**2, km**2/s, or km**2/s**2 depending on whether the element is computed from two position components, one position component and one velocity component, or two velocity components. The units shall not be displayed.

7.6.3 OCM UNITS

7.6.3.1 In an OCM orbit state data line, units shall be degrees for angular quantities, kilometers for distance quantities and seconds for time quantities. The units shall not be displayed.

7.6.3.2 In an OCM covariance matrix line, units shall be comprised of the requisite combination of degrees for angular quantities, kilometers for distance quantities and seconds for time quantities. The units shall not be displayed.

7.6.3.3 In an OCM state transition matrix data section, units shall be compatible with the corresponding orbit type's requisite combination of degrees for angular quantities, kilometers for distance quantities and seconds for time quantities. The units shall not be displayed.

7.6.3.4 In an OCM ephemeris compression data section, units shall be compatible with the corresponding orbit type's requisite combination of degrees for angular quantities, kilometers for distance quantities and seconds for time quantities. The units shall not be displayed.

7.6.3.5 Units for all other OCM quantities are as specified in section 6.2.

7.7 COMMENTS IN THE ORBIT DATA MESSAGES

7.7.1 There are certain pieces of information that provide clarity and remove ambiguity about the interpretation of the information in a file, yet are not standardized so as to fit cleanly into the 'keyword = value' paradigm. Rather than force the information to fit into a space limited to one line, the ODM producer should put certain information into comments and use the ICD to provide further specifications.

7.7.2 Comments may be used to provide provenance information or to help describe dynamical events or other pertinent information associated with the data. This additional information is intended to aid in consistency checks and elaboration where needed, but shall not be required for successful processing of a file.

7.7.3 For the OPM, OMM, OEM and OCM, comment lines shall be optional.

7.7.4 All comment lines shall begin with the 'COMMENT' keyword followed by at least one space. This keyword must appear on every comment line, not just the first such line. The remainder of the line shall be the comment value. White space shall be retained (shall be significant) in comment values.

7.7.5 Placement of comments shall be as specified in the tables in sections 3, 4, 5 and 6 that describe the OPM, OMM, OEM and OCM keywords.

7.7.6 Comments in the OPM may appear in the OPM Header immediately after the 'CCSDS_OPM_VERS' keyword, at the very beginning of the OPM Metadata section, and at the beginning of a logical block in the OPM Data section. Comments must not appear between the components of any logical block in the OPM Data section.

NOTE – The logical blocks in the OPM Data section are indicated in table 3-3.

7.7.7 Comments in the OMM may appear in the OMM Header immediately after the 'CCSDS_OMM_VERS' keyword, at the very beginning of the OMM Metadata section, and

at the beginning of a logical block in the OMM Data section. Comments must not appear between the components of any logical block in the OMM Data section.

NOTE – The logical blocks in the OMM Data section are indicated in table 4-3.

7.7.8 Comments in the OEM may appear in the OEM Header immediately after the ‘CCSDS_OEM_VERS’ keyword, at the very beginning of the OEM Metadata section (after the ‘META_START’ keyword), at the beginning of the OEM Ephemeris Data Section, and at the beginning of the OEM Covariance Data section (after the ‘COV_START’ keyword). Comment lines must not appear within any block of ephemeris lines or covariance matrix lines.

7.7.9 Comments in the OCM may appear in the OCM Header, Metadata, Space Object Physical Characteristics, Force Model, Maneuver, Orbit State Time History, Covariance Time History, State Transition Matrix Time History, Ephemeris Compression and User-Defined Parameters data sections only at the positions shown in the defining Tables (generally at the top of each section).

7.7.10 Extensive comments in an ODM are recommended in cases where there is insufficient time to negotiate an ICD.

7.7.11 The following comments should be provided:

- a) Information regarding the genesis, history, interpretation, intended use, etc., of the state vector, spacecraft, maneuver, or ephemeris that may be of use to the receiver of the OPM, OMM, or OEM:

COMMENT Source: File created by JPL Multi-Mission Navigation Team as part
COMMENT of Launch Operations Readiness Test held on 20 April 2001.

- b) Natural body ephemeris information: When the Earth is not the center of motion, the ephemerides of the planets, satellites, asteroids, and/or comets (including associated constants) consistent with the ODM should be identified so that the recipient can, in a consistent manner, make computations involving other centers:

COMMENT Based on latest orbit solution which includes observations
COMMENT through 2000-May-15 relative to planetary ephemeris DE-0405.

- c) OEM accuracy vs. efficiency: If the covariance data section of the OEM is not utilized, the producer of an OEM should report in comment lines what the expected accuracy of the ephemeris is, so the user can smooth or otherwise compress the data without affecting the accuracy of the trajectory. The OEM producer also should strive to achieve not only the best accuracy possible, taking into account prediction errors, but also consider the efficiency of the trajectory representation (e.g., step sizes of fractional seconds between ephemeris lines may be necessary for precision scientific reconstruction of an orbit, but are excessive from the standpoint of antenna pointing predicts generation).

7.8 ORBIT DATA MESSAGE KEYWORDS

7.8.1 VERSION KEYWORDS

The Header of the OPM, OMM, OEM and OCM shall provide a CCSDS Orbit Data Message version number that identifies the format version; this is included to anticipate future changes. The version keywords for the OPM, OMM, OEM and OCM shall be `CCSDS_OPM_VERS`, `CCSDS_OMM_VERS`, `CCSDS_OEM_VERS` and `CCSDS_OCM_VERS`, respectively. The value shall have the form of 'x.y', where 'y' shall be incremented for corrections and minor changes, and 'x' shall be incremented for major changes. Version x.0 shall be reserved for versions accepted by the CCSDS as an official Recommended Standard ('Blue Book'). Testing shall be conducted using OPM, OMM, OEM and OCM version numbers less than 1.0 (e.g., 0.x). Exchange participants should specify in the ICD the specific OPM, OMM, OEM and OCM version numbers they will support. The following version numbers are supported (Blue Book) or have been supported in the past (Silver Book):

Version Keyword	Version Number	Applicable Recommendation
<code>CCSDS_OPM_VERS</code>	1.0	Silver Book 1.0, 09/2004
<code>CCSDS_OPM_VERS</code>	2.0	Silver Book 2.0, 09/2009
<code>CCSDS_OPM_VERS</code>	3.0	Blue Book 3.0 (this document)
<code>CCSDS_OMM_VERS</code>	2.0	Silver Book 2.0, 09/2009
<code>CCSDS_OMM_VERS</code>	3.0	Blue Book 3.0 (this document)
<code>CCSDS_OEM_VERS</code>	1.0	Silver Book 1.0, 09/2004
<code>CCSDS_OEM_VERS</code>	2.0	Silver Book 2.0, 09/2009
<code>CCSDS_OEM_VERS</code>	3.0	Blue Book 3.0 (this document)
<code>CCSDS_OCM_VERS</code>	3.0	Blue Book 3.0 (this document)

7.8.2 GENERAL KEYWORDS

7.8.2.1 Only those keywords shown in table 3-1, table 3-2, and table 3-3 shall be used in an OPM. Some keywords represent mandatory items and some are optional. KVN assignments representing optional items may be omitted.

7.8.2.2 Only those keywords shown in table 4-1, table 4-2, and table 4-3 shall be used in an OMM. Some keywords represent mandatory items and some are optional. KVN assignments representing optional items may be omitted.

7.8.2.3 Only those keywords shown in table 5-2 and table 5-3 shall be used in an OEM. Some keywords represent mandatory items and some are optional. KVN assignments representing optional items may be omitted.

7.8.2.4 Only those keywords shown in tables 6-2, table 6-3, table 6-4, table 6-5, table 6-6, table 6-7, table 6-8, table 6-9, table 6-10 and table 6-11 shall be used in an OCM. Some keywords represent mandatory items and some are optional. KVN assignments representing optional items may be omitted.

8 CONSTRUCTING AN ODM/XML INSTANCE

8.1 OVERVIEW

This section provides detailed instructions for the user on how to create an XML message based on one of the ASCII-text KVN-formatted messages described in Section 3, Section 4, Section 5 and Section 6.

8.2 XML VERSION

The first line of each instantiation shall specify the XML version, exactly as follows:

```
<?xml version="1.0" encoding="UTF-8"?>
```

8.3 BEGINNING THE INSTANTIATION: ROOT ELEMENT TAG

8.3.1 Each instantiation shall have a ‘root element tag’ that identifies the message type and other information such as where to find the applicable schema, required attributes, etc.

8.3.2 The root element tag in an ODM/XML instantiation shall be one of those listed in Table 8-1.

Table 8-1: ODM/XML Root Element Tags

Root Element Tag	Message Type
<opm></opm>	Orbit Parameter Message
<omm></omm>	Orbit Mean Elements Message
<oem></oem>	Orbit Ephemeris Message
<ocm></ocm>	Orbit Comprehensive Message

8.3.3 The XML Schema Instance namespace attribute must appear in the root element tag of all ODM/XML instantiations, exactly as shown:

```
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
```

If it is desired to validate an instantiation against the CCSDS Web-based schema, the `xsi:noNamespaceSchemaLocation` attribute must be coded as a single string of non-blank characters, with no line breaks exactly as shown:

```
xsi:noNamespaceSchemaLocation="http://sanaregistry.org/r/ndmxml/ndmxml-1.0-master.xsd"
```

NOTE – The value associated with the `xsi:noNamespaceSchemaLocation` attribute shown in this document is too long to appear on a single line.

8.3.4 For use in a local operations environment, the schema set may be downloaded from the CCSDS Web site to a local server that meets local requirements for operations robustness.

8.3.5 If a local version is used, the value associated with the `xsi:noNamespaceSchemaLocation` attribute must be changed to a URL that is accessible to the local server.

8.3.6 Two attributes shall appear in the root element tag of an ODM/XML single message instantiation, specifically, the `CCSDS_XXX_VERS` keyword that is also part of the standard KVN header, and the Blue Book version number.

8.3.7 The `CCSDS_XXX_VERS` keyword shall be supplied via the 'id' attribute of the root element tag (xxx = OPM, OMM, OEM, OCM).

8.3.8 The version number of the Blue Book to which the schema applies shall be supplied via the 'version' attribute.

NOTE – The following example root element tag for an OPM instantiation combines all the directions in the preceding several Sections:

```
<?xml version="1.0" encoding="UTF-8"?>
<opm xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
     xsi:noNamespaceSchemaLocation="http://sanaregistry.org/r/ndmxml/ndmxml-
     1.0-master.xsd"
     id="CCSDS_OPM_VERS" version="3.0">
```

8.4 THE STANDARD ODM/XML HEADER SECTION

8.4.1 The ODMs shall share a standard header format, with tags `<header>` and `</header>`.

8.4.2 Immediately following the `<header>` tag the message may have any number of `<COMMENT></COMMENT>` tag pairs.

8.4.3 The standard ODM header shall contain the `<CREATION_DATE>` and the `<ORIGINATOR>` tags.

NOTE – An example `<header>` section is shown immediately below.

```
<header>
  <COMMENT>This is the common ODM/XML header</COMMENT>
  <COMMENT>I can put as many comments here as I want,</COMMENT>
  <COMMENT>including none.</COMMENT>
  <CREATION_DATE>2004-281T17:26:06</CREATION_DATE>
  <ORIGINATOR>AGENCY-X</ORIGINATOR>
</header>
```


8.5 THE ODM BODY SECTION

8.5.1 After coding the `<header>`, the instantiation must include a `<body></body>` tag pair.

8.5.2 Inside the `<body></body>` tag pair must appear at least one `<segment></segment>` tag pair.

8.5.3 Each segment must be made up of one or more `<metadata></metadata>` and `<data></data>` tag pairs.

8.6 THE ODM METADATA SECTION

8.6.1 All ODMs must have a metadata section.

8.6.2 The metadata section shall be set off by the `<metadata></metadata>` tag combination.

8.6.3 Between the `<metadata>` and `</metadata>` tags, the keywords shall be the same as those in the metadata sections in Section 3, Section 4, Section 5 and Section 6, with exceptions as noted in the Sections that discuss creating instantiations of the specific messages.

8.7 THE ODM DATA SECTION

8.7.1 All ODMs must have a data section.

8.7.2 The data section shall follow the metadata section and shall be set off the by the `<data></data>` tag combination.

8.7.3 Between the `<data>` and `</data>` tags, the keywords shall be the same as those in the data sections in Section 3, Section 4, Section 5 and Section 6, with exceptions as noted in the Sections that discuss creating instantiations of the specific messages.

8.8 CREATING AN OPM INSTANTIATION

8.8.1 An OPM instantiation shall be delimited with the `<opm></opm>` root element tags using the standard attributes documented in **8.3**.

8.8.2 The final attributes of the `<opm>` tag shall be 'id' and 'version'.

8.8.3 The 'id' attribute shall be 'id="CCSDS_OPM_VERS"'.

8.8.4 The 'version' attribute shall be 'version="3.0"'.

8.8.5 The standard NDM header shall follow the `<opm>` tag (see **8.4**).

8.8.6 The OPM `<body>` shall consist of a single `<segment>`.

CCSDS PROPOSED STANDARD FOR ORBIT DATA MESSAGES

8.8.7 The <segment> shall consist of a <metadata> section and a <data> section.

8.8.8 The keywords in the <metadata> and <data> sections shall be those specified in Section 3. The rules for including any of the keyword tags in the OPM/XML are the same as those specified for the OPM/KVN.

8.8.9 Tags for keywords specified in Section 3 shall be all uppercase.

8.8.10 Several of the OPM/XML keywords may have a unit attribute, if desired by the OPM producer.

8.8.11 In all cases, the units shall match those defined in Section 3.

8.8.12 The following table lists the keyword tags for which units may be specified.

Keyword	Units	Example
X	km	<X units="km">numeric-value</X>
Y	km	<Y units="km">numeric-value</Y>
Z	km	<Z units="km">numeric-value</Z>
X_DOT	km/s	<X_DOT units="km/s">numeric-value</X_DOT>
Y_DOT	km/s	<Y_DOT units="km/s">numeric-value</Y_DOT>
Z_DOT	km/s	<Z_DOT units="km/s">numeric-value</Z_DOT>
SEMI_MAJOR_AXIS	km	<SEMI_MAJOR_AXIS units="km">numeric-value</SEMI_MAJOR_AXIS>
INCLINATION	deg	<INCLINATION units="deg">numeric-value</INCLINATION>
RA_OF_ASC_NODE	deg	<RA_OF_ASC_NODE units="deg">numeric-value</RA_OF_ASC_NODE>
ARG_OF_PERICENTER	deg	<ARG_OF_PERICENTER units="deg">numeric-value</ARG_OF_PERICENTER>
TRUE_ANOMALY	deg	<TRUE_ANOMALY units="deg">numeric-value</TRUE_ANOMALY>
MEAN_ANOMALY	deg	<MEAN_ANOMALY units="deg">numeric-value</MEAN_ANOMALY>
GM	km ³ /s ²	<GM units="km ³ /s ² ">numeric-value</GM>
MASS	kg	<MASS units="kg">numeric-value</MASS>
SOLAR_RAD_AREA	m ²	<SOLAR_RAD_AREA units="m ² ">numeric-value</SOLAR_RAD_AREA>
DRAG_AREA	m ²	<DRAG_AREA units="m ² ">numeric-value</DRAG_AREA>
CX_X, CY_X, CY_Y, CZ_X, CZ_Y, CZ_Z	km ²	<CX_X units="km ² ">numeric-value</CX_X>
CX_DOT_X, CX_DOT_Y, CX_DOT_Z, CY_DOT_X, CY_DOT_Y, CY_DOT_Z, CZ_DOT_X, CZ_DOT_Y, CZ_DOT_Z	km ² /s	<CX_DOT_X units="km ² /s">numeric-value</CX_DOT_X>
CX_DOT_X_DOT, CY_DOT_X_DOT, CY_DOT_Y_DOT, CZ_DOT_X_DOT, CZ_DOT_Y_DOT, CZ_DOT_Z_DOT	km ² /s ²	<CX_DOT_X_DOT units="km ² /s ² ">numeric-value</CX_DOT_X_DOT>
MAN_DURATION	s	<MAN_DURATION units="s">numeric-value</MAN_DURATION>
MAN_DELTA_MASS	kg	<MAN_DELTA_MASS units="kg">numeric-value</MAN_DELTA_MASS>

CCSDS PROPOSED STANDARD FOR ORBIT DATA MESSAGES

Keyword	Units	Example
MAN_DV_1	km/s	<MAN_DV_1 units="km/s">numeric-value</MAN_DV_1>
MAN_DV_2	km/s	<MAN_DV_2 units="km/s">numeric-value</MAN_DV_2>
MAN_DV_3	km/s	<MAN_DV_3 units="km/s">numeric-value</MAN_DV_3>

8.8.13 In addition to the OPM keywords specified in Section 3, there are several special tags associated with the OPM body as described in the next few Sections. The information content in the OPM is separated into 'logical blocks'. Special tags in the OPM are used to encapsulate the information in the logical blocks of the OPM.

8.8.14 The ODM/XML tags used to delimit the logical blocks of the OPM shall be drawn from the following table:

OPM Logical Block	Associated ODM/XML OPM Tag
State Vector	<stateVector>
Keplerian Elements	<keplerianElements>
Spacecraft Parameters	<spacecraftParameters>
Covariance Matrix	<covarianceMatrix>
Maneuver Parameters	<maneuverParameters>
User Defined Parameters	<userDefinedParameters>

8.8.15 Between the begin tag and end tag (e.g., between <spacecraftParameters> and </spacecraftParameters>), the user shall place the keywords required by the specific logical block as specified in Section 3.

8.9 CREATING AN OMM INSTANTIATION

8.9.1 An OMM instantiation shall be delimited with the `<omm></omm>` root element tags using the standard attributes documented in 8.3.

8.9.2 The final attributes of the `<omm>` tag shall be 'id' and 'version'.

8.9.3 The 'id' attribute shall be 'id="CCSDS_OMM_VERS"'.

8.9.4 The 'version' attribute for the version of the OMM described in Section 4 shall be 'version="3.0"'.

8.9.5 The standard NDM header shall follow the `<omm>` tag (see 8.4).

8.9.6 The OMM `<body>` shall consist of a single `<segment>`.

8.9.7 The `<segment>` shall consist of a `<metadata>` section and a `<data>` section.

8.9.8 The keywords in the `<metadata>` and `<data>` sections shall be those specified in Section 4. The rules for including any of the keyword tags in the OMM/XML are the same as those specified for the OMM/KVN in Section 4.

8.9.9 Tags for keywords specified in Section 4 shall be all uppercase.

8.9.10 Several of the OMM/XML keywords may have a unit attribute, if desired by the OMM producer.

8.9.11 In all cases, the units shall match those defined in Section 4.

8.9.12 The following table lists the keyword tags for which units may be specified.

Keyword	Units	Example
SEMI_MAJOR_AXIS	km	<code><SEMI_MAJOR_AXIS units="km">numeric-value</SEMI_MAJOR_AXIS></code>
MEAN_MOTION	rev/day	<code><MEAN_MOTION units="rev/day">numeric-value</MEAN_MOTION></code>
INCLINATION	deg	<code><INCLINATION units="deg">numeric-value</INCLINATION></code>
RA_OF_ASC_NODE	deg	<code><RA_OF_ASC_NODE units="deg">numeric-value</RA_OF_ASC_NODE></code>
ARG_OF_PERICENTER	deg	<code><ARG_OF_PERICENTER units="deg">numeric-value</ARG_OF_PERICENTER></code>
MEAN_ANOMALY	deg	<code><MEAN_ANOMALY units="deg">numeric-value</MEAN_ANOMALY></code>
GM	km ³ /s ²	<code><GM units="km**3/s**2">numeric-value</GM></code>
MASS	kg	<code><MASS units="kg">numeric-value</MASS></code>
SOLAR_RAD_AREA	m ²	<code><SOLAR_RAD_AREA units="m**2">numeric-value</SOLAR_RAD_AREA></code>
DRAG_AREA	m ²	<code><DRAG_AREA units="m**2">numeric-value</DRAG_AREA></code>
BSTAR	1/ER	<code><BSTAR units="1/ER">numeric-value</BSTAR></code>
MEAN_MOTION_DOT	rev/day ²	<code><MEAN_MOTION_DOT units="rev/day**2">numeric-value</MEAN_MOTION_DOT></code>

CCSDS PROPOSED STANDARD FOR ORBIT DATA MESSAGES

Keyword	Units	Example
MEAN_MOTION_DDOT	rev/day**3	<MEAN_MOTION_DDOT units="rev/day**3">numeric-value</MEAN_MOTION_DDOT>
CX_X, CY_X, CY_Y, CZ_X, CZ_Y, CZ_Z	km**2	<CX_X units="km**2">numeric-value</CX_X>
CX_DOT_X, CX_DOT_Y, CX_DOT_Z, CY_DOT_X, CY_DOT_Y, CY_DOT_Z, CZ_DOT_X, CZ_DOT_Y, CZ_DOT_Z	km**2/s	<CX_DOT_X units="km**2/s">numeric-value</CX_DOT_X>
CX_DOT_X_DOT, CY_DOT_X_DOT, CY_DOT_Y_DOT, CZ_DOT_X_DOT, CZ_DOT_Y_DOT, CZ_DOT_Z_DOT	km**2/s**2	<CX_DOT_X_DOT units="km**2/s**2">numeric-value</CX_DOT_X_DOT>

8.9.13 In addition to the OMM keywords specified in Section 4, there are several special tags associated with the OMM body as described in the next few Sections. The information content in the OMM is separated into constructs described in Section 4 as ‘logical blocks’. Special tags in the OMM are used to encapsulate the information in the logical blocks of the OMM.

8.9.14 The ODM/XML tags used to delimit the logical blocks of the OMM shall be drawn from the following table:

OMM Logical Block	Associated ODM/XML OMM Tag
Mean Keplerian Elements	<meanElements>
Spacecraft Parameters	<spacecraftParameters>
TLE Parameters	<tleParameters>
Covariance Matrix	<covarianceMatrix>
User Defined Parameters	<userDefinedParameters>

8.9.15 Between the begin tag and end tag (e.g., between <spacecraftParameters> and </spacecraftParameters>), the user must place the keywords required by the specific logical block as specified in Section 4.

8.10 CREATING AN OEM INSTANTIATION

8.10.1 An OEM instantiation shall be delimited with the `<oem></oem>` root element tags using the standard attributes documented in 8.3.

8.10.2 The final attributes of the `<oem>` tag shall be 'id' and 'version'.

8.10.3 The 'id' attribute shall be 'id="CCSDS_OEM_VERS"'.

8.10.4 The 'version' attribute for the version of the OEM described in Section 5 shall be 'version="3.0"'.

8.10.5 The standard NDM header shall follow the `<oem>` tag (see 8.4).

8.10.6 The OEM `<body>` shall consist of one or more `<segment>` constructs.

8.10.7 Each `<segment>` shall consist of a `<metadata>` section and a `<data>` section.

8.10.8 The keywords in the `<metadata>` and `<data>` sections shall be those specified in Section 5. The rules for including any of the keyword tags in the OEM/XML are the same as those specified for the OEM in Section 5.

8.10.9 Tags for keywords specified in Section 5 shall be all uppercase.

8.10.10 In addition to the OEM keywords specified in Section 5, there are some special tags associated with the OEM body as described in the next Sections.

8.10.11 The `<stateVector>` tag shall encapsulate the keywords associated with one of the ephemeris data lines in the OEM.

8.10.12 In the XML representation of the OEM, the components of the `<stateVector>` ephemeris data line must be represented with keywords (i.e., a tag).

8.10.13 The `<stateVector>` keywords shall be the same as those defined for the same construct in the OPM.

8.10.14 The ODM/XML tags used within the `<stateVector>` structure shall be drawn from the following table:

CCSDS PROPOSED STANDARD FOR ORBIT DATA MESSAGES

OEM Tag	Represents	Example
<EPOCH>	time tag of the state	<EPOCH>2007-09-20T17:41:00</EPOCH>
<X>	x component of position	<X units="km">6678.0</X>
<Y>	y component of position	<Y units="km">0.0</Y>
<Z>	z component of position	<Z units="km">0.0</Z>
<X_DOT>	x component of velocity	<X_DOT units="km/s">0</X_DOT>
<Y_DOT>	y component of velocity	<Y_DOT units="km/s">7.73</Y_DOT>
<Z_DOT>	z component of velocity	<Z_DOT units="km/s">0.0</Z_DOT>
<X_DDOT>	x component of acceleration	<X_DDOT units="km/s**2">0.0</X_DDOT>
<Y_DDOT>	y component of acceleration	<Y_DDOT units="km/s**2">0.50</Y_DDOT>
<Z_DDOT>	z component of acceleration	<Z_DDOT units="km/s**2">0.0</Z_DDOT>

8.10.15 Between the begin tag and end tag (i.e., between <stateVector> and </stateVector>), the user shall place the values required by the ephemeris data line as specified in Section 5.

8.10.16 Since the state vector structure is shared by the OPM schema and OEM schema, units may optionally appear in the XML version of the OEM ephemeris data line.

8.10.17 The <covarianceMatrix> tag shall encapsulate the keywords associated with the covariance matrix lines in the OEM.

8.10.18 In the XML representation of the OEM, the covariance data line must be represented with keywords (i.e., a tag).

8.10.19 The OEM <covarianceMatrix> keywords shall be the same as those defined for the same construct in the OPM and OMM.

NOTE – In the KVN representations of the OEM covariance matrix data lines, keywords are not used. Rather, the components of the covariance matrix data line appear in an order defined in Section 5. Similarly, units are not used in the KVN version of the OEM covariance matrix; however, they are optional in the OPM and OMM.

8.10.20 Since the covariance matrix structure is shared by the OPM, OMM and OEM, units may optionally appear in the XML version of the OEM covariance matrix line.

8.10.21 The OEM/XML tags used within the <covarianceMatrix> structure shall be drawn from the following table:

CCSDS PROPOSED STANDARD FOR ORBIT DATA MESSAGES

Keyword	Units	Example
CX_X, CY_X, CY_Y, CZ_X, CZ_Y, CZ_Z	km**2	<CX_X units="km**2">numeric-value</CX_X>
CX_DOT_X, CX_DOT_Y, CX_DOT_Z, CY_DOT_X, CY_DOT_Y, CY_DOT_Z, CZ_DOT_X, CZ_DOT_Y, CZ_DOT_Z	km**2/s	<CX_DOT_X units="km**2/s">numeric-value</CX_DOT_X>
CX_DOT_X_DOT, CY_DOT_X_DOT, CY_DOT_Y_DOT, CZ_DOT_X_DOT, CZ_DOT_Y_DOT, CZ_DOT_Z_DOT	km**2/s**2	<CX_DOT_X_DOT units="km**2/s**2">numeric-value</CX_DOT_X_DOT>

8.10.22 Between the begin tag and end tag (i.e., between <covarianceMatrix> and </covarianceMatrix>), the user shall place the values required by the covariance matrix line type as specified in Section 5.

8.11 CREATING AN OCM INSTANTIATION

8.11.1 An OCM instantiation shall be delimited with the `<ocm></ocm>` root element tags using the standard attributes documented in 8.3.

8.11.2 The final attributes of the `<ocm>` tag shall be 'id' and 'version'.

8.11.3 The 'id' attribute shall be 'id="CCSDS_OCM_VERS"'.

8.11.4 The 'version' attribute for the version of the OCM described in Section 6 shall be 'version="3.0"'.

8.11.5 The standard NDM header shall follow the `<ocm>` tag (see 8.4).

8.11.6 The OCM `<body>` shall consist of a single `<segment>` construct.

8.11.7 The `<segment>` shall consist of a `<metadata>` section and a `<data>` section.

8.11.8 The keywords in the `<metadata>` and `<data>` sections shall be those specified in Section 6. The rules for including any of the keyword tags in the OCM/XML are the same as those specified for the OCM in Section 6.

8.11.9 Tags for keywords specified in Section 6 shall be all uppercase.

8.11.10 In addition to the OCM keywords specified in Section 6, there are some special tags associated with the OCM body as described in the next Sections.

8.11.11 TBD

8.11.12 TBD

8.11.13 TBD

8.11.14 The OCM/XML tags used within the `<tbd>` structure shall be drawn from the following table:

OCM Tag	Represents	Example
<code><tbd></code>	tbd	<code><tbd units="tbd">tbd</tbd></code>

8.10.23 Between the begin tag and end tag (e.g., between `<tbd>` and `</tbd>`), the user shall place the values required by the TBD data line as specified in Section 6.

8.10.24 In the XML representation of the OCM, the tbd data line must be represented with keywords (i.e., a tag).

8.10.25 A sample OCM/XML follows:

```
<?xml version="1.0" encoding="UTF-8"?>
<ocm xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
```

CCSDS PROPOSED STANDARD FOR ORBIT DATA MESSAGES

```
xsi:noNamespaceSchemaLocation="http://sanaregistry.org/r/ndmxml/ndmxml-1.0-master.xsd"
id="CCSDS_OEM_VERS" version="3.0">

<header>
<COMMENT>THIS EXAMPLE IS TBD</COMMENT>
<CREATION_DATE>2017-11-04T17:22:31</CREATION_DATE>
<ORIGINATOR>NASA</ORIGINATOR>
</header>
<body>
  <segment>
    <metadata>
    </metadata>
    <data>
    </data>
  </segment>
</body>
</ocm>
```

ANNEX A

IMPLEMENTATION CONFORMANCE

STATEMENT PRO FORMA

(NORMATIVE)

A1 INTRODUCTION

A1.1 OVERVIEW

This annex provides the Implementation Conformance Statement (ICS) Requirements List (RL) for an implementation of the Orbit Data Messages (CCSDS 502.0). The ICS for an implementation is generated by completing the RL in accordance with the instructions below. An implementation shall satisfy the mandatory conformance requirements referenced in the RL.

- The RL in this annex is blank. An implementation's completed RL is called the ICS. The ICS states which capabilities and options have been implemented. The following can use the ICS:
 - the implementer, as a checklist to reduce the risk of failure to conform to the standard through oversight;
 - a supplier or potential acquirer of the implementation, as a detailed indication of the capabilities of the implementation, stated relative to the common basis for understanding provided by the standard ICS proforma;
 - a user or potential user of the implementation, as a basis for initially checking the possibility of interworking with another implementation (it should be noted that, while interworking can never be guaranteed, failure to interwork can often be predicted from incompatible ICS lists);
 - a tester, as the basis for selecting appropriate tests against which to assess the claim for conformance of the implementation.

A1.2 ABBREVIATIONS AND CONVENTIONS

The RL consists of information in tabular form. The status of features is indicated using the abbreviations and conventions described below.

Item Column

The item column contains sequential numbers for items in the table.

Feature Column

The feature column contains a brief descriptive name for a feature. It implicitly means “Is this feature supported by the implementation?”

Status Column

The status column uses the following notations:

- M mandatory;
- O optional;
- C conditional;
- X prohibited;
- I out of scope;
- N/A not applicable.

Support Column Symbols

The support column is to be used by the implementer to state whether a feature is supported by entering Y, N, or N/A, indicating:

- Y Yes, supported by the implementation.
- N No, not supported by the implementation.
- N/A Not applicable.

The support column should also be used, when appropriate, to enter values supported for a given capability.

A1.3 INSTRUCTIONS FOR COMPLETING THE RL

An implementer shows the extent of compliance to the Recommended Standard by completing the RL; that is, the state of compliance with all mandatory requirements and the options supported are shown. The resulting completed RL is called an ICS. The implementer shall complete the RL by entering appropriate responses in the support or values supported column, using the notation described in A1.2. If a conditional requirement is inapplicable, N/A should be used. If a mandatory requirement is not satisfied, exception information must be supplied by entering a reference X_i , where i is a unique identifier, to an accompanying rationale for the noncompliance.

A2 ICS PROFORMA FOR ORBIT DATA MESSAGES

A2.1 IDENTIFICATION OF ICS

Date of Statement (DD/MM/YYYY)	
ICS serial number	
System Conformance statement cross-reference	

A2.2 IDENTIFICATION OF IMPLEMENTATION UNDER TEST (IUT)

Implementation name	
Implementation version	
Special Configuration	
Other Information	

A2.3 IDENTIFICATION OF SUPPLIES

Supplier	
Contact Point for Queries	
Implementation Name(s) and Versions	
Other information necessary for full identification, e.g., name(s) and version(s) for machines and/or operating systems; System Name(s)	

A2.4 DOCUMENT VERSIONS

CCSDS 502.0 Document Version	P2.38
<p>Have any exceptions been required?</p> <p>(Note: A YES answer means that the implementation does not conform to the Recommended Standard. Non-supported mandatory capabilities are to be identified in the ICS, with an explanation of why the implementation is non-conforming.)</p>	<p>Yes _____ No _____</p>

A2.5 REQUIREMENTS LISTS

[See CCSDS A20.1-Y-1, *CCSDS Implementation Conformance Statements* (Yellow Book, Issue 1, April 2014).]

Item	Feature	Keyword	Reference (Blue book)	Status (M/O/...)	Support

ANNEX B

NORMATIVE VALUES AND REFERENCES FOR TIMING SYSTEM, REFERENCE FRAME, ORBITAL ELEMENT, AND COVARIANCE- RELATED KEYWORDS

(NORMATIVE)

The set of accepted values for Originators, Orbit Centers, time systems, reference frames, orbit-relative reference frames, spacecraft and attitude control reference frames, orbital elements and additional covariance element sets for all Orbit Data Messages (i.e., OPM, OMM, OEM and OCM) are discussed in this annex. These acceptable values are stored on the SANA Registry, globally accessible on the CCSDS SANA registry website located at: https://sanaregistry.org/r/navigation_standard_normative_annexes

Exchange partners may submit additional (new) keywords for consideration of future inclusion into the SANA registry by submitting a detailed email request (mailto:info@sanaregistry.org) per ANNEX L, Section L2. The CCSDS Area or Working Group responsible for the maintenance of the ODM at the time of the request is the approval authority. Until a suggested value is included in the SANA registry, exchange partners may define and use values that are not listed in the SANA registry only if mutually agreed and properly documented by an accompanying ICD.

B1 MESSAGE ORIGINATORS

The set of acceptable values for the **ORIGINATOR** keyword are provided in ANNEX B normative reference [B-1].

B2 REFERENCE FRAME CENTER AND THIRD-BODY PERTURBATIONS

The set of acceptable values for the reference frame center keywords (**CENTER_NAME** for OPM, OEM, OMM and OCM, as well as **N_BODY_PERTURBATIONS**, **PERT_CENTER_NAME**, **MAN_CENTER_NAME**, **STM_CENTER_NAME**, **EC_CENTER_NAME**) are provided in ANNEX B normative reference [B-2].

Note that this values may also be useful to specify another platform (satellite, airframe, ground vehicle, etc.) as the reference frame origin to permit the specification of relative positional state time history data. In this case, message authors shall clearly communicate to recipients by ICD (as noted above) that the orbit center is not a gravitational center, that propagation of ephemeris vectors or extrapolation of ephemeris start/stop states is not advisable, and that interpolation of state time histories should not be accomplished using classical orbit propagation forces, e.g., gravitational constants, drag.

B3 TIME SYSTEMS

The set of acceptable values for the **TIME_SYSTEM** keyword are provided in ANNEX B normative reference [B-3].

For further details and description of time systems, see references [M-1] and [M-4].

B4 REFERENCE FRAMES

The set of acceptable non-orbit-relative reference frame values for ***_REF_FRAME** keyword are provided in ANNEX B normative reference [B-4].

B5 ADDITIONAL ORBIT-RELATIVE REFERENCE FRAMES

In addition to the above reference frames, maneuver and covariance data can be specified in orbit-relative reference frames using ***_REF_FRAME** keyword values provided in ANNEX B normative reference [B-5].

Note that two types of orbit-relative local reference frames exist: inertial and rotating. When transforming velocity terms between inertial and rotating frames, remember to properly incorporate the $(\bar{\omega} \times \bar{r})$ contribution.

B6 ADDITIONAL SPACECRAFT AND ATTITUDE REFERENCE FRAMES

An additional set of spacecraft and attitude control reference frames are acceptable as provided in ANNEX B normative reference [B-6]. Note that for many of these frames (particularly those that are spacecraft hardware-dependent), an ICD will likely be necessary to fully define and convey understanding of these frames.

B7 ORBITAL ELEMENTS

The set of acceptable values for the **ORB_TYPE** keyword are provided in ANNEX B normative reference [B-7].

Unique to the Orbit Comprehensive Message (OCM), orbit element states and/or time histories may be specified in the following multiple element sets.

Orbit elements shall be interpreted as osculating elements unless either explicitly specified via the **ORB_AVERAGING** keyword or pre-coordinated between the message originator and recipient to contain mean elements (e.g. singly- or doubly-averaged elements based upon Kozai, Brouwer or other theories).

Non-inertial reference frames shall not be specified when employing inertial element sets.

Conversely, inertial reference frames shall not be specified when employing non-inertial element sets.

B8 ADDITIONAL COVARIANCE REPRESENTATIONS

In addition to the above orbit element sets, covariance data can be specified in certain augmented element sets provided in ANNEX B normative reference [B-8].

B9 NORMATIVE REFERENCES FOR TIMING SYSTEM, REFERENCE FRAME, ORBITAL ELEMENT, AND COVARIANCE-RELATED KEYWORDS

[B-1] SANA Registry of Organizations: <https://sanaregistry.org/r/organizations>

[B-2] SANA Registry of Orbit Centers: https://sanaregistry.org/r/orbit_centers

[B-3] SANA Registry of Time Systems: https://sanaregistry.org/r/time_systems

[B-4] SANA Registry of Reference Frames: https://sanaregistry.org/r/absolute_reference_frames

[B-5] SANA Registry of Orbit-Relative Reference Frames:
https://sanaregistry.org/r/orbit_relative_reference_frames

[B-6] SANA Registry of Spacecraft and Attitude Control Reference Frames:
https://sanaregistry.org/r/spacecraft_reference_frames

[B-7] SANA Registry of Orbital Elements: https://sanaregistry.org/r/orbital_elements

[B-8] SANA Registry of Covariance Representations: https://sanaregistry.org/r/covariance_representations_frames

ANNEX C

TECHNICAL MATERIAL

(INFORMATIVE)

C1 SATELLITE PHYSICAL CHARACTERISTICS SPECIFICATION (INFORMATIVE)

This section of the informative technical annex defines satellite dimensional and orientational parameters of the OCM's satellite physical characteristics specification.

To facilitate improved modeling of space object attitude, hard body collision, and drag and SRP acceleration forces, the OCM allows the specification of an “**Optimally-Encompassing Shape**” (OES). Allowable OES types include BOX, ELLIPTICAL_CYLINDER and ELLIPSOID.

For a box-shaped satellite (e.g., a CubeSat) without appendages, the satellite and a corresponding box-shaped OES would be a one-to-one mapping.

For a satellite having solar arrays that extend from the spacecraft body structure, the OES would extend from the main satellite body to encompass the deployed solar arrays as well.

The BOX and ELLIPSOID shapes are shown in Fig. C- 1 below. As illustrated, the OES reference frame axes (depicted in **RED**) are defined by convention as follows:

- The OES x-axis is along the **longest** dimension of the OES (\hat{X}_{OES_MAX}). This is sometimes referred to the “span” of the space object.
- The OES y-axis is along the **intermediate** orthonormal dimension (\hat{Y}_{OES_MED})
- The OES z-axis is along the **shortest** orthonormal dimension (\hat{Z}_{OES_MIN}).

The BOX shape can easily represent a cube by setting all orthonormal dimensions equal. In the event that the longest two or three orthonormal dimensions are equivalent, the user shall select \hat{X}_{OES_MAX} as the direction along one of those longest dimensions and the next as \hat{Y}_{OES_MED} .

For the ELLIPSOID shape, note that the longest dimension (x-axis) corresponds to the major principal axis of the ellipsoid and the z-axis corresponds to the minor principal axis. This ellipsoid shape can easily represent a sphere by setting all principal axis dimensions equal.

In the event that the longest two or three principal axis dimensions of the ellipsoid are equivalent, the user shall select \hat{X}_{OES_MAX} as the direction along one of those longest principal dimensions and the next as \hat{Y}_{OES_MED} .

The OES z-axis shall always be defined as: $\hat{z}_{OES_MIN} = \hat{x}_{OES_MAX} \times \hat{y}_{OES_MED}$.




Fig. C- 1 Depiction of BOX and ELLIPSOID shape type and definitions of MAX, MED and MIN orientation vectors relative to OES parent frame

The ELLIPTICAL_CYLINDER shape type is shown in Fig. C- 2 below. As illustrated, the OES reference frame axes (depicted in RED) are defined by convention as follows:

- The OES x-axis aligns with the cylindrical axis of rotation (\hat{x}_{OES_MAX}). Note that this direction may not coincide with the longest (span) direction, as was the case for the BOX and ELLIPSOID shapes.
- The OES y-axis aligns with the longest of the two ellipse principal axes (\hat{y}_{OES_MED})
- The OES z-axis is along the **shortest** of the two ellipse principal axes (\hat{z}_{OES_MIN}).




Fig. C- 2 Depiction of ELLIPTICAL_CYLINDER shape type and definitions of MAX, MED and MIN orientation vectors relative to OES parent frame

As was the case for the BOX and ELLIPSOID shapes, the ELLIPTICAL_CYLINDER OES z-axis shall always be defined as: $\hat{z}_{OES_MIN} = \hat{x}_{OES_MAX} \times \hat{y}_{OES_MED}$.

A fixed orientation of the Optimally-Encompassing Shape with respect to the user-specified "OES_PARENT_FRAME" is defined using an ordered sequence of Euler rotations that map from the user-specified OES_PARENT_FRAME to the Optimally-Encompassing Shape vector directions. The above figure shows the proper definitions and adopted sign conventions for Yaw, Pitch and Roll angles. The resulting transformation sequence is:

$$\begin{bmatrix} x \\ y \\ z \end{bmatrix}_{OES} = [M] \begin{bmatrix} x \\ y \\ z \end{bmatrix}_{OES_PARENT_FRAME}$$

Where the frame transformation matrix [M] is a function of the quaternion components

$$[M] = \begin{bmatrix} q_1^2 - q_2^2 - q_3^2 + q_c^2 & 2(q_1q_2 + q_3q_c) & 2(q_1q_3 - q_2q_c) \\ 2(q_1q_2 - q_3q_c) & -q_1^2 + q_2^2 - q_3^2 + q_c^2 & 2(q_2q_3 + q_1q_c) \\ 2(q_1q_3 + q_2q_c) & 2(q_2q_3 - q_1q_c) & -q_1^2 - q_2^2 + q_3^2 + q_c^2 \end{bmatrix}$$

The physical dimensions of the OES (long, intermediate and short dimensions) are specified via OES_MAX, OES_MED and OES_MIN respectively.

The cross-sectional area as viewed along the OES x, y and z axes (long, intermediate and short dimension directions) are specified via AREA_ALONG_OES_MAX, AREA_ALONG_OES_MED and AREA_ALONG_OES_MIN, respectively.

C2 APPARENT-TO-ABSOLUTE VISUAL MAGNITUDE RELATIONSHIP (INFORMATIVE)

This section of the informative technical annex presents the relationships to be used to map apparent to absolute visual magnitude for inclusion in an OCM. These equations, based on reference [M-12], examine signal magnitude for reflected illumination by a Resident Space Object (RSO) that is exoatmospheric, meaning that its illumination by the Sun is not reduced or impeded by atmospheric transmission losses. The equations do not account for spatial distribution across multiple detectors, which involves characterizing the Point Spread Function of the system.

The equation for VM_{absolute} is not provided.

Definitions:

$E_{\text{EntranceAperture}}$	Target's specific entrance aperture radiance [W/m^2]
I_{Sun}	Solar Intensity $\approx 3.088374161 \times 10^{25}$ [W]
$d_{\text{SunToTarget}}$	Distance from the sun to the target (e.g. 1 AU = $1.4959787066 \times 10^{11}$ m)
E_{Sun}	Exoatmospheric solar irradiance, nominally 1380 [W/m^2] at 1 AU
φ	Phase or Critical Angle to the Sun (CATS) from sun to the sensor, as shown in Fig. C- 3 and measured at the observed target [rad]
$Phase(\varphi)$	Geometric reflectance function [between 0 and 1]
F	General shadowing term accounting for the penumbra region's influence [unitless ratio between 0 = umbra and 1 = full Sun illumination]
A_{Target}	Effective area of the target [m^2]
π	Pi constant
ρ	Reflectance of the target [between 0 (none) and 1 (perfect reflectance)]
I_{Target}	Intensity of reflected energy from target treated as a point source [W]
E_{Target}	Target Irradiance at Sensor without atmospheric loss [W/m^2]
r_{Target}	Effective radius of the target [m^2]
$d_{\text{TargetToSensor}}$	Distance from target to sensor [m]
$\tau_{\text{Atmosphere}}$	Atmospheric transmission [unitless between 0 and 1]
E_0	Ref. Visual Magnitude (Vega) Irradiance [$2.77894 \times 10^{-8} W/m^2$]

Commented [DL06]: Remove?

Commented [DL07]: Remove ?

Given an optical sensor's measured target entrance aperture radiance:

$$VM_{\text{apparent}} = -2.5 \log_{10} \frac{E_{\text{target}}}{E_0}, \text{ measured on the visual magnitude scale}$$

$$E_{\text{target}} = \frac{E_{\text{EntranceAperture}}}{\tau_{\text{Atmosphere}}(\theta)} [\text{W}/\text{m}^2]$$

or if VM_{apparent} known: $E_{\text{target}} = E_0 10^{\left[-\frac{VM_{\text{apparent}}}{2.5}\right]}$

$$I_{\text{target}} = E_{\text{target}} d_{\text{TargetToSensor}}^2 [\text{W}]$$

$$E_{Sun} = \frac{I_{Sun}}{d_{SunToTarget}^2} \text{ [W/m}^2\text{]}$$

$$Phase(\varphi) = \frac{\sin \varphi + (\pi - \varphi) \cos \varphi}{\pi}$$

$$\rho A_{Target} = \frac{\pi I_{Target}}{E_{Sun} F Phase(\varphi)} \text{ [m}^2\text{]}$$

From the above equations, $VM_{absolute}$ “normalized” to a 1 AU Sun-to-target distance, a phase angle of 0° and a 40,000 km target-to-sensor distance (equivalent to a GEO satellite tracked at 15.6° elevation above the optical site’s local horizon), is obtained as:

$$VM_{absolute} = -2.5 \log_{10} \left\{ \frac{[E_{Sun1AU=1380 \text{ W/m}^2}][Phase(0 \text{ rad})=1.0][\rho A_{Target} \text{ from above, in m}^2]}{\pi [E_0 = 2.77894 \times 10^{-8} \text{ W/m}^2][1.6 \times 10^{15} \text{ m}^2]} \right\}$$




Fig. C-3 Depiction of optical viewing Critical Angle To the Sun (CATS) phase angle geometry

C3 MANEUVER AND DUTY CYCLE DIAGRAMS (INFORMATIVE)

This section of the informative technical annex defines the relationships between time-based duty cycle parameters (

Time-based duty cycle parameters define a window of duty cycle operations, the actual execution interval and “ON” and “OFF” intervals, as shown in Fig. C- 4.





Fig. C- 4 Diagram of time-based duty cycle (*MAN_DUTY_CYCLE_TYPE* = “TIME”)



Angle-based duty cycle parameters also define a window of duty cycle operations and actual execution interval and “ON” and “OFF” intervals, but this time the “ON” and “OFF” intervals are triggered by angular limits as shown in Fig. C- 5.

Fig. C- 5 Diagram of angle-based duty cycle (*MAN_DUTY_CYCLE_TYPE* = “PHASE_ANGLE”)

Conical angle-based duty cycle parameters also define a conical window of duty cycle operations and actual execution interval and “ON” and “OFF” intervals triggered by conical angle limits as shown in Fig. C- 5.




Fig. C- 6 Diagram of Cone angle-based duty cycle (*MAN_DUTY_CYCLE_TYPE* = *CONE*)

ANNEX D

OPM EXAMPLES

(INFORMATIVE)

The following are examples of Orbit Parameter Messages (OPMs).

OPM examples in KVN:

The following figures are examples of OPMs in Keyword Value Notation (KVN) format. The first has only a state; the second has state, Keplerian elements, and maneuvers; the third and fourth include the position/velocity covariance matrix.

Annex Fig. D-3 and Annex Fig. D-4 include unique features of ODM version 2.0, and thus 'CCSDS_OPM_VERS = 2.0' (at a minimum) must be specified.

```

CCSDS_OPM_VERS = 3.0
CREATION_DATE = 1998-11-06T09:23:57
ORIGINATOR = JAXA

COMMENT      GEOCENTRIC, CARTESIAN, EARTH FIXED
OBJECT_NAME  = GODZILLA 5
OBJECT_ID    = 1998-999A
CENTER_NAME  = EARTH
REF_FRAME    = ITRF2000
TIME_SYSTEM  = UTC

EPOCH =      1998-12-18T14:28:15.1172
X =          6503.514000
Y =          1239.647000
Z =          -717.490000
X_DOT =      -0.873160
Y_DOT =       8.740420
Z_DOT =      -4.191076
MASS =       3000.000000
SOLAR_RAD_AREA = 18.770000
SOLAR_RAD_COEFF = 1.000000
DRAG_AREA =   18.770000
DRAG_COEFF =  2.500000
    
```

Annex Fig. D-1: Simple OPM file example

CCSDS PROPOSED STANDARD FOR ORBIT DATA MESSAGES

```

CCSDS_OPM_VERS      = 3.0

COMMENT  Generated by GSOC, R. Kiehling
COMMENT  Current intermediate orbit IO2 and maneuver planning data

CREATION_DATE       = 2000-06-03T05:33:00.000
ORIGINATOR          = GSOC

OBJECT_NAME         = EUTELSAT W4
OBJECT_ID           = 2000-028A
CENTER_NAME         = EARTH
REF_FRAME           = TOD
TIME_SYSTEM         = UTC

COMMENT  State Vector
EPOCH               = 2006-06-03T00:00:00.000
X                   = 6655.9942      [km]
Y                   = -40218.5751    [km]
Z                   = -82.9177      [km]
X_DOT               = 3.11548208    [km/s]
Y_DOT               = 0.47042605    [km/s]
Z_DOT               = -0.00101495    [km/s]

COMMENT  Keplerian elements
SEMI_MAJOR_AXIS     = 41399.5123     [km]
ECCENTRICITY        = 0.020842611
INCLINATION         = 0.117746      [deg]
RA_OF_ASC_NODE      = 17.604721     [deg]
ARG_OF_PERICENTER   = 218.242943    [deg]
TRUE_ANOMALY        = 41.922339    [deg]
GM                  = 398600.4415    [km**3/s**2]

COMMENT  Spacecraft parameters
MASS                 = 1913.000      [kg]
SOLAR_RAD_AREA      = 10.000        [m**2]
SOLAR_RAD_COEFF     = 1.300
DRAG_AREA           = 10.000        [m**2]
DRAG_COEFF          = 2.300

COMMENT  2 planned maneuvers

COMMENT  First maneuver: AMF-3
COMMENT  Non-impulsive, thrust direction fixed in inertial frame
MAN_EPOCH_IGNITION = 2000-06-03T09:00:34.1
MAN_DURATION        = 132.60        [s]
MAN_DELTA_MASS      = -18.418       [kg]
MAN_REF_FRAME       = J2000
MAN_DV_1            = -0.02325700    [km/s]
MAN_DV_2            = 0.01683160    [km/s]
MAN_DV_3            = -0.00893444    [km/s]

COMMENT  Second maneuver: first station acquisition maneuver
COMMENT  impulsive, thrust direction fixed in RTN frame
MAN_EPOCH_IGNITION = 2000-06-05T18:59:21.0
MAN_DURATION        = 0.00          [s]
MAN_DELTA_MASS      = -1.469        [kg]
MAN_REF_FRAME       = RTN
MAN_DV_1            = 0.00101500    [km/s]
MAN_DV_2            = -0.00187300    [km/s]
MAN_DV_3            = 0.00000000    [km/s]

```

Annex Fig. D-2: OPM file example with optional Keplerian elements and two maneuvers

CCSDS PROPOSED STANDARD FOR ORBIT DATA MESSAGES

```
CCSDS_OPM_VERS = 3.0

CREATION_DATE = 1998-11-06T09:23:57
ORIGINATOR = JAXA

COMMENT      GEOCENTRIC, CARTESIAN, EARTH FIXED
OBJECT_NAME  = GODZILLA 5
OBJECT_ID    = 1998-999A
CENTER_NAME  = EARTH
REF_FRAME    = ITRF1997
TIME_SYSTEM  = UTC

EPOCH =      1998-12-18T14:28:15.1172
X =          6503.514000
Y =          1239.647000
Z =          -717.490000
X_DOT =      -0.873160
Y_DOT =       8.740420
Z_DOT =      -4.191076

MASS =       3000.000000
SOLAR_RAD_AREA = 18.770000
SOLAR_RAD_COEFF = 1.000000
DRAG_AREA =  18.770000
DRAG_COEFF =  2.500000

CX_X = 3.331349476038534e-04
CY_X = 4.618927349220216e-04
CY_Y = 6.782421679971363e-04
CZ_X = -3.070007847730449e-04
CZ_Y = -4.221234189514228e-04
CZ_Z = 3.231931992380369e-04
CX_DOT_X = -3.349365033922630e-07
CX_DOT_Y = -4.686084221046758e-07
CX_DOT_Z = 2.484949578400095e-07
CX_DOT_X_DOT = 4.296022805587290e-10
CY_DOT_X = -2.211832501084875e-07
CY_DOT_Y = -2.864186892102733e-07
CY_DOT_Z = 1.798098699846038e-07
CY_DOT_X_DOT = 2.608899201686016e-10
CY_DOT_Y_DOT = 1.767514756338532e-10
CZ_DOT_X = -3.041346050686871e-07
CZ_DOT_Y = -4.989496988610662e-07
CZ_DOT_Z = 3.540310904497689e-07
CZ_DOT_X_DOT = 1.869263192954590e-10
CZ_DOT_Y_DOT = 1.008862586240695e-10
CZ_DOT_Z_DOT = 6.224444338635500e-10
```

Annex Fig. D-3: OPM file example with covariance matrix

CCSDS PROPOSED STANDARD FOR ORBIT DATA MESSAGES

```

CCSDS_OPM_VERS = 3.0
COMMENT Generated by GSOC, R. Kiehling
COMMENT Current intermediate orbit IO2 and maneuver planning data
CREATION_DATE = 2000-06-03T05:33:00.000
ORIGINATOR = GSOC
OBJECT_NAME = EUTELSAT W4
OBJECT_ID = 2000-028A
CENTER_NAME = EARTH
REF_FRAME = TOD
TIME_SYSTEM = UTC
COMMENT State Vector
EPOCH = 2006-06-03T00:00:00.000
X = 6655.9942 [km]
Y = -40218.5751 [km]
Z = -82.9177 [km]
X_DOT = 3.11548208 [km/s]
Y_DOT = 0.47042605 [km/s]
Z_DOT = -0.00101495 [km/s]
COMMENT Keplerian elements
SEMI_MAJOR_AXIS = 41399.5123 [km]
ECCENTRICITY = 0.020842611
INCLINATION = 0.117746 [deg]
RA_OF_ASC_NODE = 17.604721 [deg]
ARG_OF_PERICENTER = 218.242943 [deg]
TRUE_ANOMALY = 41.922339 [deg]
GM = 398600.4415 [km**3/s**2]
COMMENT Spacecraft parameters
MASS = 1913.000 [kg]
SOLAR_RAD_AREA = 10.000 [m**2]
SOLAR_RAD_COEFF = 1.300
DRAG_AREA = 10.000 [m**2]
DRAG_COEFF = 2.300
COV_REF_FRAME = RTN
CX_X = 3.331349476038534e-04
CY_X = 4.618927349220216e-04
CY_Y = 6.782421679971363e-04
CZ_X = -3.070007847730449e-04
CZ_Y = -4.221234189514228e-04
CZ_Z = 3.231931992380369e-04
CX_DOT_X = -3.349365033922630e-07
CX_DOT_Y = -4.686084221046758e-07
CX_DOT_Z = 2.484949578400095e-07
CX_DOT_X_DOT = 4.296022805587290e-10
CY_DOT_X = -2.211832501084875e-07
CY_DOT_Y = -2.864186892102733e-07
CY_DOT_Z = 1.798098699846038e-07
CY_DOT_X_DOT = 2.608899201686016e-10
CY_DOT_Y_DOT = 1.767514756338532e-10
CZ_DOT_X = -3.041346050686871e-07
CZ_DOT_Y = -4.989496988610662e-07
CZ_DOT_Z = 3.540310904497689e-07
CZ_DOT_X_DOT = 1.869263192954590e-10
CZ_DOT_Y_DOT = 1.008862586240695e-10
CZ_DOT_Z_DOT = 6.224444338635500e-10
USER_DEFINED_EARTH_MODEL = WGS-84
    
```

Annex Fig. D-4: OPM file example with optional Keplerian elements, covariance matrix, and a user defined parameter

OPM example in XML:

Annex Fig. D-5 contains an example of an OPM in Extensible Markup Language (XML) format.

CCSDS PROPOSED STANDARD FOR ORBIT DATA MESSAGES

```

<?xml version="1.0" encoding="UTF-8"?>
<opm xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xsi:noNamespaceSchemaLocation="http://sanaregistry.org/r/ndmxml/ndmxml-1.0-master.xsd"
  id="CCSDS_OPM_VERS" version="3.0">
  <header>
    <COMMENT>THIS EXAMPLE CONFORMS TO FIGURE 3-1 IN 502.0-B-2</COMMENT>
    <CREATION_DATE>2001-11-06T09:23:57</CREATION_DATE>
    <ORIGINATOR>JAXA</ORIGINATOR>
  </header>
  <body>
    <segment>
      <metadata>
        <COMMENT>GEOCENTRIC, CARTESIAN, EARTH FIXED</COMMENT>
        <OBJECT_NAME>GODZILLA 5</OBJECT_NAME>
        <OBJECT_ID>1998-999A</OBJECT_ID>
        <CENTER_NAME>EARTH</CENTER_NAME>
        <REF_FRAME>ITRF1997</REF_FRAME>
        <TIME_SYSTEM>UTC</TIME_SYSTEM>
      </metadata>
      <data>
        <COMMENT>OBJECT_ID: 1998-057A</COMMENT>
        <stateVector>
          <EPOCH>1996-12-18T14:28:15.1172</EPOCH>
          <X>6503.514000</X>
          <Y>1239.647000</Y>
          <Z>-717.490000</Z>
          <X_DOT>-0.873160</X_DOT>
          <Y_DOT>8.740420</Y_DOT>
          <Z_DOT>-4.191076</Z_DOT>
        </stateVector>
        <spacecraftParameters>
          <MASS>3000.000000</MASS>
          <SOLAR_RAD_AREA>18.770000</SOLAR_RAD_AREA>
          <SOLAR_RAD_COEFF>1.000000</SOLAR_RAD_COEFF>
          <DRAG_AREA>18.770000</DRAG_AREA>
          <DRAG_COEFF>2.500000</DRAG_COEFF>
        </spacecraftParameters>
        <covarianceMatrix>
          <COV_REF_FRAME>ITRF1997</COV_REF_FRAME>
          <CX_X>0.316</CX_X>
          <CY_X>0.722</CY_X>
          <CY_Y>0.518</CY_Y>
          <CZ_X>0.202</CZ_X>
          <CZ_Y>0.715</CZ_Y>
          <CZ_Z>0.002</CZ_Z>
          <CX_DOT_X>0.912</CX_DOT_X>
          <CX_DOT_Y>0.306</CX_DOT_Y>
          <CX_DOT_Z>0.276</CX_DOT_Z>
          <CX_DOT_X_DOT>0.797</CX_DOT_X_DOT>
          <CY_DOT_X>0.562</CY_DOT_X>
          <CY_DOT_Y>0.899</CY_DOT_Y>
          <CY_DOT_Z>0.022</CY_DOT_Z>
          <CY_DOT_X_DOT>0.079</CY_DOT_X_DOT>
          <CY_DOT_Y_DOT>0.415</CY_DOT_Y_DOT>
          <CZ_DOT_X>0.245</CZ_DOT_X>
          <CZ_DOT_Y>0.965</CZ_DOT_Y>
          <CZ_DOT_Z>0.950</CZ_DOT_Z>
          <CZ_DOT_X_DOT>0.435</CZ_DOT_X_DOT>
          <CZ_DOT_Y_DOT>0.621</CZ_DOT_Y_DOT>
          <CZ_DOT_Z_DOT>0.991</CZ_DOT_Z_DOT>
        </covarianceMatrix>
      </data>
    </segment>
  </body>
</opm>

```

Annex Fig. D-5: OPM file example in XML format

ANNEX E

OMM EXAMPLES

(INFORMATIVE)

The following are examples of Orbit Mean-Element Messages (OMMs). All of these examples are based on the TLE shown in Annex Fig. E-1.

```
GOES 9 [P]
1 23581U 95025A 07064.44075725 -.00000113 00000-0 10000-3 0 9250
2 23581 3.0539 81.7939 0005013 249.2363 150.1602 1.00273272 43169
```

Annex Fig. E-1: Example Two Line Element Set (TLE)

OMM examples in KVN:

The following figures are examples of OMMs in Keyword Value Notation (KVN) format .

```
CCSDS_OMM_VERS = 3.0
CREATION_DATE = 2007-065T16:00:00
ORIGINATOR = NOAA/USA

OBJECT_NAME = GOES 9
OBJECT_ID = 1995-025A
CENTER_NAME = EARTH
REF_FRAME = TEME
TIME_SYSTEM = UTC
MEAN_ELEMENT_THEORY = SGP/SGP4

EPOCH = 2007-064T10:34:41.4264
MEAN_MOTION = 1.00273272
ECCENTRICITY = 0.0005013
INCLINATION = 3.0539
RA_OF_ASC_NODE = 81.7939
ARG_OF_PERICENTER = 249.2363
MEAN_ANOMALY = 150.1602
GM = 398600.8
EPHEMERIS_TYPE = 0
CLASSIFICATION_TYPE = U
NORAD_CAT_ID = 23581
ELEMENT_SET_NO = 0925
REV_AT_EPOCH = 4316
BSTAR = 0.0001
MEAN_MOTION_DOT = -0.00000113
MEAN_MOTION_DDOT = 0.0
```

Annex Fig. E-2: OMM file example without covariance matrix

CCSDS PROPOSED STANDARD FOR ORBIT DATA MESSAGES

```
CCSDS_OMM_VERS = 3.0
CREATION_DATE = 2007-065T16:00:00
ORIGINATOR = NOAA/USA

OBJECT_NAME = GOES 9
OBJECT_ID = 1995-025A
CENTER_NAME = EARTH
REF_FRAME = TEME
TIME_SYSTEM = UTC
MEAN_ELEMENT_THEORY = SGP/SGP4

EPOCH = 2007-064T10:34:41.4264
MEAN_MOTION = 1.00273272
ECCENTRICITY = 0.0005013
INCLINATION = 3.0539
RA_OF_ASC_NODE = 81.7939
ARG_OF_PERICENTER = 249.2363
MEAN_ANOMALY = 150.1602
GM = 398600.8

EPHEMERIS_TYPE = 0
CLASSIFICATION_TYPE = U
NORAD_CAT_ID = 23581
ELEMENT_SET_NO = 0925
REV_AT_EPOCH = 4316
BSTAR = 0.0001
MEAN_MOTION_DOT = -0.00000113
MEAN_MOTION_DDOT = 0.0

COV_REF_FRAME = TEME
CX_X = 3.331349476038534e-04
CY_X = 4.618927349220216e-04
CZ_X = 6.782421679971363e-04
CX_Y = -3.070007847730449e-04
CY_Y = -4.221234189514228e-04
CZ_Y = 3.231931992380369e-04
CX_Z = -3.349365033922630e-07
CY_Z = -4.686084221046758e-07
CZ_Z = 2.484949578400095e-07
CX_DOT_X_DOT = 4.296022805587290e-10
CY_DOT_X_DOT = -2.211832501084875e-07
CZ_DOT_X_DOT = -2.864186892102733e-07
CX_DOT_Y_DOT = 1.798098699846038e-07
CY_DOT_Y_DOT = 2.608899201686016e-10
CZ_DOT_Y_DOT = 1.767514756338532e-10
CX_DOT_Z_DOT = -3.041346050686871e-07
CY_DOT_Z_DOT = -4.989496988610662e-07
CZ_DOT_Z_DOT = 3.540310904497689e-07
CX_DOT_X_DOT_DOT = 1.869263192954590e-10
CY_DOT_X_DOT_DOT = 1.008862586240695e-10
CZ_DOT_X_DOT_DOT = 6.224444338635500e-10
```

Annex Fig. E-3: OMM file example with covariance matrix

CCSDS PROPOSED STANDARD FOR ORBIT DATA MESSAGES

```
CCSDS_OMM_VERS = 3.0
CREATION_DATE = 2007-065T16:00:00
ORIGINATOR = NOAA/USA

OBJECT_NAME = GOES 9
OBJECT_ID = 1995-025A
CENTER_NAME = EARTH
REF_FRAME = TEME
TIME_SYSTEM = UTC
MEAN_ELEMENT_THEORY = SGP/SGP4

EPOCH = 2007-064T10:34:41.4264
MEAN_MOTION = 1.00273272 [rev/day]
ECCENTRICITY = 0.0005013
INCLINATION = 3.0539 [deg]
RA_OF_ASC_NODE = 81.7939 [deg]
ARG_OF_PERICENTER = 249.2363 [deg]
MEAN_ANOMALY = 150.1602 [deg]
GM = 398600.8 [km**3/s**2]
EPHEMERIS_TYPE = 0
CLASSIFICATION_TYPE = U
NORAD_CAT_ID = 23581
ELEMENT_SET_NO = 0925
REV_AT_EPOCH = 4316
BSTAR = 0.0001 [1/ER]
MEAN_MOTION_DOT = -0.00000113 [rev/day**2]
MEAN_MOTION_DDOT = 0.0 [rev/day**3]

USER_DEFINED_EARTH_MODEL = WGS-84
```

Annex Fig. E-4: OMM with units and a user defined parameter

OMM example in XML:

Annex Fig. E-5 contains an example of an OMM in Extensible Markup Language (XML) format.

CCSDS PROPOSED STANDARD FOR ORBIT DATA MESSAGES

```

<?xml version="1.0" encoding="UTF-8"?>
<omm xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xsi:noNamespaceSchemaLocation="http://sanaregistry.org/r/ndmxml/ndmxml-1.0-master.xsd"
  id="CCSDS_OMM_VERS" version="3.0">
  <header>
    <COMMENT>THIS EXAMPLE CONFORMS TO FIGURE 4-3 IN 502.0-B-2</COMMENT>
    <CREATION_DATE>2007-065T16:00:00</CREATION_DATE>
    <ORIGINATOR>NOAA/USA</ORIGINATOR>
  </header>

  <body>
    <segment>
      <metadata>
        <OBJECT_NAME>GOES-9</OBJECT_NAME>
        <OBJECT_ID>1995-025A</OBJECT_ID>
        <CENTER_NAME>EARTH</CENTER_NAME>
        <REF_FRAME>TEME</REF_FRAME>
        <TIME_SYSTEM>UTC</TIME_SYSTEM>
        <MEAN_ELEMENT_THEORY>TLE</MEAN_ELEMENT_THEORY>
      </metadata>

      <data>
        <meanElements>
          <EPOCH>2007-064T10:34:41.4264</EPOCH>
          <MEAN_MOTION>1.00273272</MEAN_MOTION>
          <ECCENTRICITY>0.0005013</ECCENTRICITY>
          <INCLINATION>3.0539</INCLINATION>
          <RA_OF_ASC_NODE>81.7939</RA_OF_ASC_NODE>
          <ARG_OF_PERICENTER>249.2363</ARG_OF_PERICENTER>
          <MEAN_ANOMALY>150.1602</MEAN_ANOMALY>
          <GM>398600.8</GM>
        </meanElements>
        <tleParameters>
          <NORAD_CAT_ID>23581</NORAD_CAT_ID>
          <ELEMENT_SET_NO>0925</ELEMENT_SET_NO>
          <REV_AT_EPOCH>4316</REV_AT_EPOCH>
          <BSTAR>0.0001</BSTAR>
          <MEAN_MOTION_DOT>-0.00000113</MEAN_MOTION_DOT>
          <MEAN_MOTION_DDOT>0.0</MEAN_MOTION_DDOT>
        </tleParameters>
        <covarianceMatrix>
          <COV_REF_FRAME>TEME</COV_REF_FRAME>
          <CX_X>0.316</CX_X>
          <CY_X>0.722</CY_X>
          <CY_Y>0.518</CY_Y>
          <CZ_X>0.202</CZ_X>
          <CZ_Y>0.715</CZ_Y>
          <CZ_Z>0.002</CZ_Z>
          <CX_DOT_X>0.912</CX_DOT_X>
          <CX_DOT_Y>0.306</CX_DOT_Y>
          <CX_DOT_Z>0.276</CX_DOT_Z>
          <CX_DOT_X_DOT>0.797</CX_DOT_X_DOT>
          <CY_DOT_X>0.562</CY_DOT_X>
          <CY_DOT_Y>0.899</CY_DOT_Y>
          <CY_DOT_Z>0.022</CY_DOT_Z>
          <CY_DOT_X_DOT>0.079</CY_DOT_X_DOT>
          <CY_DOT_Y_DOT>0.415</CY_DOT_Y_DOT>
          <CZ_DOT_X>0.245</CZ_DOT_X>
          <CZ_DOT_Y>0.965</CZ_DOT_Y>
          <CZ_DOT_Z>0.950</CZ_DOT_Z>
          <CZ_DOT_X_DOT>0.435</CZ_DOT_X_DOT>
          <CZ_DOT_Y_DOT>0.621</CZ_DOT_Y_DOT>
          <CZ_DOT_Z_DOT>0.991</CZ_DOT_Z_DOT>
        </covarianceMatrix>
      </data>
    </segment>
  </body>
</omm>

```

Annex Fig. E-5: OMM file example in XML format

ANNEX F

OEM EXAMPLES

(INFORMATIVE)

The following are examples of Orbit Ephemeris Messages (OEMs).

OEM examples in KVN:

The following figures are examples of OEMs in Keyword Value Notation (KVN) format. Annex Fig. F-2 and Annex Fig. F-3 contain features unique to the ODM version 2, and thus 'CCSDS_OEM_VERS = 2.0' must be specified. Some ephemeris data lines have been omitted to save space.

CCSDS PROPOSED STANDARD FOR ORBIT DATA MESSAGES

```
CCSDS_OEM_VERS = 3.0
CREATION_DATE = 1996-11-04T17:22:31
ORIGINATOR = NASA/JPL

META_START
OBJECT_NAME      = MARS GLOBAL SURVEYOR
OBJECT_ID        = 1996-062A
CENTER_NAME      = MARS BARYCENTER
REF_FRAME        = J2000
TIME_SYSTEM      = UTC
START_TIME       = 1996-12-18T12:00:00.331
USEABLE_START_TIME = 1996-12-18T12:10:00.331
USEABLE_STOP_TIME  = 1996-12-28T21:23:00.331
STOP_TIME        = 1996-12-28T21:28:00.331
INTERPOLATION    = HERMITE
INTERPOLATION_DEGREE = 7
META_STOP

COMMENT This file was produced by M.R. Somebody, MSOO NAV/JPL, 1996NOV 04. It is
COMMENT to be used for DSN scheduling purposes only.

1996-12-18T12:00:00.331 2789.619 -280.045 -1746.755 4.73372 -2.49586 -1.04195
1996-12-18T12:01:00.331 2783.419 -308.143 -1877.071 5.18604 -2.42124 -1.99608
1996-12-18T12:02:00.331 2776.033 -336.859 -2008.682 5.63678 -2.33951 -1.94687

< intervening data records omitted here >

1996-12-28T21:28:00.331 -3881.024 563.959 -682.773 -3.28827 -3.66735 1.63861

META_START
OBJECT_NAME      = MARS GLOBAL SURVEYOR
OBJECT_ID        = 1996-062A
CENTER_NAME      = MARS BARYCENTER
REF_FRAME        = J2000
TIME_SYSTEM      = UTC
START_TIME       = 1996-12-28T21:29:07.267
USEABLE_START_TIME = 1996-12-28T22:08:02.5
USEABLE_STOP_TIME  = 1996-12-30T01:18:02.5
STOP_TIME        = 1996-12-30T01:28:02.267
INTERPOLATION    = HERMITE
INTERPOLATION_DEGREE = 7
META_STOP

COMMENT This block begins after trajectory correction maneuver TCM-3.

1996-12-28T21:29:07.267 -2432.166 -063.042 1742.754 7.33702 -3.495867 -1.041945
1996-12-28T21:59:02.267 -2445.234 -878.141 1873.073 1.86043 -3.421256 -0.996366
1996-12-28T22:00:02.267 -2458.079 -683.858 2007.684 6.36786 -3.339563 -0.946654

< intervening data records omitted here >

1996-12-30T01:28:02.267 2164.375 1115.811 -688.131 -3.53328 -2.88452 0.88535
```

Annex Fig. F-1: OEM Example With No Acceleration, No Covariance

CCSDS PROPOSED STANDARD FOR ORBIT DATA MESSAGES

```
CCSDS_OEM_VERS = 3.0

COMMENT OEM WITH OPTIONAL ACCELERATIONS

CREATION_DATE = 1996-11-04T17:22:31
ORIGINATOR = NASA/JPL

META_START
OBJECT_NAME      = MARS GLOBAL SURVEYOR
OBJECT_ID        = 2000-028A
CENTER_NAME      = MARS BARYCENTER
REF_FRAME        = J2000
TIME_SYSTEM      = UTC
START_TIME       = 1996-12-18T12:00:00.331
USEABLE_START_TIME = 1996-12-18T12:10:00.331
USEABLE_STOP_TIME  = 1996-12-28T21:23:00.331
STOP_TIME        = 1996-12-28T21:28:00.331
INTERPOLATION     = HERMITE
INTERPOLATION_DEGREE = 7
META_STOP

COMMENT This file was produced by M.R. Somebody, MSOO NAV/JPL, 2000 NOV 04. It is
COMMENT to be used for DSN scheduling purposes only.

1996-12-18T12:00:00.331 2789.6 -280.0 -1746.8 4.73 -2.50 -1.04 0.008 0.001 -0.159
1996-12-18T12:01:00.331 2783.4 -308.1 -1877.1 5.19 -2.42 -2.00 0.008 0.001 0.001
1996-12-18T12:02:00.331 2776.0 -336.9 -2008.7 5.64 -2.34 -1.95 0.008 0.001 0.159

  < intervening data records omitted here >

1996-12-28T21:28:00.331 -3881.0 564.0 -682.8 -3.29 -3.67 1.64 -0.003 0.000 0.000
```

Annex Fig. F-2: OEM Example with Optional Accelerations

CCSDS PROPOSED STANDARD FOR ORBIT DATA MESSAGES

```
CCSDS_OEM_VERS = 3.0
CREATION_DATE = 1996-11-04T17:22:31
ORIGINATOR = NASA/JPL

META_START
OBJECT_NAME      = MARS GLOBAL SURVEYOR
OBJECT_ID        = 1996-062A
CENTER_NAME      = MARS BARYCENTER
REF_FRAME        = J2000
TIME_SYSTEM      = UTC
START_TIME       = 1996-12-28T21:29:07.267
USEABLE_START_TIME = 1996-12-28T22:08:02.5
USEABLE_STOP_TIME  = 1996-12-30T01:18:02.5
STOP_TIME        = 1996-12-30T01:28:02.267
INTERPOLATION    = HERMITE
INTERPOLATION_DEGREE = 7
META_STOP

COMMENT This block begins after trajectory correction maneuver TCM-3.

1996-12-28T21:29:07.267 -2432.166 -063.042 1742.754 7.33702 -3.495867 -1.041945
1996-12-28T21:59:02.267 -2445.234 -878.141 1873.073 1.86043 -3.421256 -0.996366
1996-12-28T22:00:02.267 -2458.079 -683.858 2007.684 6.36786 -3.339563 -0.946654

< intervening data records omitted here >

1996-12-30T01:28:02.267 2164.375 1115.811 -688.131 -3.53328 -2.88452 0.88535

COV_START
EPOCH = 1996-12-28T21:29:07.267
COV_REF_FRAME = J2000
  3.3313494e-04
  4.6189273e-04  6.7824216e-04
-3.0700078e-04 -4.2212341e-04  3.2319319e-04
-3.3493650e-07 -4.6860842e-07  2.4849495e-07  4.2960228e-10
-2.2118325e-07 -2.8641868e-07  1.7980986e-07  2.6088992e-10  1.7675147e-10
-3.0413460e-07 -4.9894969e-07  3.5403109e-07  1.8692631e-10  1.0088625e-10  6.2244443e-10

EPOCH = 1996-12-29T21:00:00
COV_REF_FRAME = J2000
  3.4424505e-04
  4.5078162e-04  6.8935327e-04
-3.0600067e-04 -4.1101230e-04  3.3420420e-04
-3.2382549e-07 -4.5750731e-07  2.3738384e-07  4.3071339e-10
-2.1007214e-07 -2.7530757e-07  1.6870875e-07  2.5077881e-10  1.8786258e-10
-3.0302350e-07 -4.8783858e-07  3.4302008e-07  1.7581520e-10  1.0077514e-10  6.2244443e-10
COVARIANCE_STOP
```

Annex Fig. F-3: OEM Example with Optional Covariance Matrices

OEM example in XML:

Annex Fig. F-4 contains an example of an Orbit Ephemeris Message in Extensible Markup Language (XML) format.

```
<?xml version="1.0" encoding="UTF-8"?>
<oem xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
     xsi:noNamespaceSchemaLocation="http://sanaregistry.org/r/ndmxml/ndmxml-1.0-master.xsd"
     id="CCSDS_OEM_VERS" version="3.0">

  <header>
    <COMMENT>OEM WITH OPTIONAL ACCELERATIONS</COMMENT>
    <CREATION_DATE>1996-11-04T17:22:31</CREATION_DATE>
    <ORIGINATOR>NASA/JPL</ORIGINATOR>
  </header>
  <body>
```

CCSDS PROPOSED STANDARD FOR ORBIT DATA MESSAGES

```

<segment>
  <metadata>
    <OBJECT_NAME>MARS GLOBAL SURVEYOR</OBJECT_NAME>
    <OBJECT_ID>2000-028A</OBJECT_ID>
    <CENTER_NAME>MARS BARYCENTER</CENTER_NAME>
    <REF_FRAME>J2000</REF_FRAME>
    <TIME_SYSTEM>UTC</TIME_SYSTEM>
    <START_TIME>1996-12-18T12:00:00.331</START_TIME>
    <USEABLE_START_TIME>1996-12-18T12:10:00.331</USEABLE_START_TIME>
    <USEABLE_STOP_TIME>1996-12-28T21:23:00.331</USEABLE_STOP_TIME>
    <STOP_TIME>1996-12-28T21:28:00.331</STOP_TIME>
    <INTERPOLATION>HERMITE</INTERPOLATION>
    <INTERPOLATION_DEGREE>7</INTERPOLATION_DEGREE>
  </metadata>
  <data>
    <COMMENT>Produced by M.R. Sombedody, MSOO NAV/JPL, 1996 OCT 11. It is</COMMENT>
    <COMMENT>to be used for DSN scheduling purposes only.</COMMENT>
    <stateVector>
      <EPOCH>1996-12-18T12:00:00.331</EPOCH>
      <X>2789.6</X>
      <Y>-280.0</Y>
      <Z>-1746.8</Z>
      <X_DOT>4.73</X_DOT>
      <Y_DOT>-2.50</Y_DOT>
      <Z_DOT>-1.04</Z_DOT>
      <X_DDOT>0.008</X_DDOT>
      <Y_DDOT>0.001</Y_DDOT>
      <Z_DDOT>-0.159</Z_DDOT>
    </stateVector>
    <stateVector>
      <EPOCH>1996-12-18T12:01:00.331</EPOCH>
      <X>2783.4</X>
      <Y>-308.1</Y>
      <Z>-1877.1</Z>
      <X_DOT>5.19</X_DOT>
      <Y_DOT>-2.42</Y_DOT>
      <Z_DOT>-2.00</Z_DOT>
      <X_DDOT>0.008</X_DDOT>
      <Y_DDOT>0.001</Y_DDOT>
      <Z_DDOT>0.001</Z_DDOT>
    </stateVector>
    <stateVector>
      <EPOCH>1996-12-18T12:02:00.331</EPOCH>
      <X>2776.0</X>
      <Y>-336.9</Y>
      <Z>-2008.7</Z>
      <X_DOT>5.64</X_DOT>
      <Y_DOT>-2.34</Y_DOT>
      <Z_DOT>-1.95</Z_DOT>
      <X_DDOT>0.008</X_DDOT>
      <Y_DDOT>0.001</Y_DDOT>
      <Z_DDOT>0.159</Z_DDOT>
    </stateVector>
    <stateVector>
      <EPOCH>1996-12-28T21:28:00.331</EPOCH>
      <X>-3881.0</X>
      <Y>564.0</Y>
      <Z>-682.8</Z>
      <X_DOT>-3.29</X_DOT>
      <Y_DOT>-3.67</Y_DOT>
      <Z_DOT>1.64</Z_DOT>
      <X_DDOT>-0.003</X_DDOT>
      <Y_DDOT>0.000</Y_DDOT>
      <Z_DDOT>0.000</Z_DDOT>
    </stateVector>
    <covarianceMatrix>
      <EPOCH></EPOCH>
      <COV_REF_FRAME>ITRF1997</COV_REF_FRAME>
      <CX_X>0.316</CX_X>
      <CY_X>0.722</CY_X>
      <CY_Y>0.518</CY_Y>
  </data>

```

CCSDS PROPOSED STANDARD FOR ORBIT DATA MESSAGES

```
<CZ_X>0.202</CZ_X>
<CZ_Y>0.715</CZ_Y>
<CZ_Z>0.002</CZ_Z>
<CX_DOT_X>0.912</CX_DOT_X>
<CX_DOT_Y>0.306</CX_DOT_Y>
<CX_DOT_Z>0.276</CX_DOT_Z>
<CX_DOT_X_DOT>0.797</CX_DOT_X_DOT>
<CY_DOT_X>0.562</CY_DOT_X>
<CY_DOT_Y>0.899</CY_DOT_Y>
<CY_DOT_Z>0.022</CY_DOT_Z>
<CY_DOT_X_DOT>0.079</CY_DOT_X_DOT>
<CY_DOT_Y_DOT>0.415</CY_DOT_Y_DOT>
<CZ_DOT_X>0.245</CZ_DOT_X>
<CZ_DOT_Y>0.965</CZ_DOT_Y>
<CZ_DOT_Z>0.950</CZ_DOT_Z>
<CZ_DOT_X_DOT>0.435</CZ_DOT_X_DOT>
<CZ_DOT_Y_DOT>0.621</CZ_DOT_Y_DOT>
<CZ_DOT_Z_DOT>0.991</CZ_DOT_Z_DOT>
</covarianceMatrix>
</data>
</segment>
</body>
</oem>
```

Annex Fig. F-4: OEM file example in XML format

ANNEX G

OCM EXAMPLES AND ASSOCIATED SUPPLEMENTARY
INFORMATION

(INFORMATIVE)

The following are examples of Orbit Comprehensive Messages (OCMs).

OCM examples in KVN:

The following figures are examples of OCMs in Keyword Value Notation (KVN) format. The first has only a time history of orbital states and constitutes a minimal content OCM. The second includes space object characteristics and perturbations specifications; the third includes a time series of maneuvers, a time history of Cartesian position and velocity orbit states, followed by a time history of Keplerian elements; the fourth includes a time series of covariance matrices, and the fifth contains a State Transition Matrix and an Ephemeris Compression section.

```

CCSDS_OCM_VERS = 3.0
CREATION_DATE = 1998-11-06T09:23:57
META_START
DEF_EPOCH_TZERO = 1998-12-18T14:28:15.1172
DEF_TIME_SYSTEM = UTC
META_STOP
ORB_START
DT=0.0 2789.6 -280.0 -1746.8 4.73 -2.50 -1.04
T=1998-12-18T14:28:25.1172 2783.4 -308.1 -1877.1 5.19 -2.42 -2.00
DT=20.0 2776.0 -336.9 -2008.7 5.64 -2.34 -1.95
< intervening data records omitted here >
DT=500.0 2164.375 1115.811 -688.131 -3.53328 -2.88452 0.88535
ORB_STOP

```

Annex Fig. G-1: Simple/Succinct OCM File example with only Cartesian ephemeris. Reference frame (ORB_REF_FRAME) defaults to ITRF2000, CENTER_NAME defaults to EARTH and orbit type (ORB_TYPE) to CARTPV. In this example, at the expense of readability, KVN values are unaligned to minimize message storage and transmission size.

CCSDS PROPOSED STANDARD FOR ORBIT DATA MESSAGES

```

CCSDS_OCM_VERS = 3.0
COMMENT This OCM reflects the latest conditions post-maneuver A67Z
COMMENT This example shows the specification of multiple comment lines
CREATION_DATE = 1998-11-06T09:23:57

META_START
ORIGINATOR = JAXA

ORIGINATOR_POC = R. Rabbit
ORIGINATOR_POSITION = Flight Dynamics Mission Design Lead
ORIGINATOR_PHONE = (719)555-1234

TECH_POC = Mr. Rodgers
TECH_PHONE = (719)555-1234
TECH_ADDRESS = email@email.XXX

OBJECT_NAME = GODZILLA 5
INTERNATIONAL_DESIGNATOR = 1998-999A

DEF_EPOCH_TZERO = 1998-12-18T00:00:00.0000
DEF_TIME_SYSTEM = UT1

TAIMUTC_TZERO = 36 [s]
UT2MUTC_TZERO = .357 [s]
UT1MUTC_RATE_TZERO = 0.0001 [ms/day]
META_STOP

ORB_START
COMMENT GEOCENTRIC, CARTESIAN, EARTH FIXED
COMMENT THIS IS MY SECOND COMMENT LINE
ORB_EPOCH_TZERO = 1998-12-18T14:28:35.1172
ORB_REF_FRAME = EFG
ORB_TYPE = CARTEVA
DT=0.000000 2789.6 -280.0 -1746.8 4.73 -2.50 -1.04 0.008 0.001 -0.159
ORB_STOP

PHYS_START
COMMENT S/C Physical Characteristics:
MASS = 100.0 [kg]
OES_Q1 = 0.03123
OES_Q2 = 0.78543
OES_Q3 = 0.39158
OES_QC = 0.47832
OES_MAX = 2.0 [m]
OES_MED = 1.0 [m]
OES_MIN = 0.5 [m]
AREA_ALONG_OES_MAX = 0.15 [m**2]
AREA_ALONG_OES_MED = 0.3 [m**2]
AREA_ALONG_OES_MIN = 0.5 [m**2]
PHYS_STOP

PERT_START
COMMENT Perturbations Specification:
ATMOSPHERIC_MODEL = NRLMSIS00
GRAVITY_MODEL = EGM-96: 36D 360
GM = 398600.4415 [km**3/s**2]
N_BODY_PERTURBATIONS = MOON, SUN
FIXED_GEOMAG_KP = 12.0
FIXED_F10P7 = 105.0
FIXED_F10P7_MEAN = 120.0
PERT_STOP

USER_START
EARTH_MODEL = WGS-84
USER_STOP

```

Annex Fig. G-2: OCM example with space object characteristics and perturbations

CCSDS PROPOSED STANDARD FOR ORBIT DATA MESSAGES

```

CCSDS_OCM_VERS = 3.0
CREATION_DATE = 1998-11-06T09:23:57

META_START
DEF_EPOCH_TZERO = 1998-12-18T14:28:15.1172
META_STOP

ORB_START
COMMENT ORBIT EPHEMERIS INCORPORATING DEPLOYMENTS AND MANEUVERS (BELOW)
ORB_REF_FRAME = TOD
ORB_FRAME_EPOCH = 1998-12-18T14:28:15.1172
ORB_TYPE = CARTEVA
DT=0.000000 2789.6 -280.0 -1746.8 4.73 -2.50 -1.04 0.008 0.001 -0.159
DT=10.000000 2783.4 -308.1 -1877.1 5.19 -2.42 -2.00 0.008 0.001 0.001
DT=20.000000 2776.0 -336.9 -2008.7 5.64 -2.34 -1.95 0.008 0.001 0.159
< intervening data records omitted here >
T=1998-12-18T14:36:35.1172 2164.375 1115.811 -688.131 -3.53328 -2.88452 0.88535
ORB_STOP

PHYS_START
COMMENT S/C Physical Characteristics:
DRAG_AREA = 10.00 [m**2]
DRAG_COEFF = 2.300
MASS = 100.0 [kg]
SOLAR_RAD_AREA = 4.00
SOLAR_RAD_COEFF = 1.300
PHYS_STOP

MAN_START
COMMENT = Ten lkg objects deployed from 200kg host over 100 s timespan
COMMENT = 20 deg off of back-track direction
MAN_BASIS = PREDICTED
MAN_IS_ADDITIVE = YES
MAN_PURPOSE = DEPLOY
MAN_EOI=DV_X, DV_Y, DV_Z, DV_SIGMA, DV_DMASS, DEPLOY_ID, DEPLOY_DV_X, DEPLOY_DV_Y, DEPLOY_DV_Z, DEPLOY_MASS
MAN_REF_FRAME = RTN
DT=500.0 -0.00144 0.00470 -0.00092 0.0 -1.0 CUBESAT_10 0.28773 -0.93969 0.18491 1.0
DT=510.0 -0.00071 0.00470 -0.00156 0.0 -1.0 CUBESAT_10 0.14208 -0.93969 0.31111 1.0
DT=520.0 0.00024 0.00470 -0.00169 0.0 -1.0 CUBESAT_10 -0.04867 -0.93969 0.33854 1.0
DT=530.0 0.00112 0.00470 -0.00129 0.0 -1.0 CUBESAT_10 -0.22398 -0.93969 0.25848 1.0
DT=540.0 0.00164 0.00470 -0.00048 0.0 -1.0 CUBESAT_10 -0.32817 -0.93969 0.09636 1.0
DT=550.0 0.00164 0.00470 0.00048 0.0 -1.0 CUBESAT_10 -0.32817 -0.93969 -0.09636 1.0
DT=560.0 0.00112 0.00470 0.00129 0.0 -1.0 CUBESAT_10 -0.22398 -0.93969 -0.25848 1.0
DT=570.0 0.00024 0.00470 0.00169 0.0 -1.0 CUBESAT_10 -0.04867 -0.93969 -0.33854 1.0
DT=580.0 -0.00071 0.00470 0.00156 0.0 -1.0 CUBESAT_10 0.14208 -0.93969 -0.31111 1.0
DT=590.0 -0.00144 0.00470 0.00092 0.0 -1.0 CUBESAT_10 0.28773 -0.93969 -0.18491 1.0
MAN_STOP

MAN_START
COMMENT = 100 s of 0.5N +in-track thrust w/effic η=0.95, Isp=300s, 5% 1-sigma
error
MAN_BASIS = PREDICTED
MAN_IS_ADDITIVE = YES
MAN_PURPOSE = ORBIT_ADJUST
MAN_EOI = MAN_DURA, THR_X, THR_Y, THR_Z, THR_SIGMA, THR_INTERP, THR_ISP,
THR EFFIC
MAN_REF_FRAME = RTN
DT=500.0 100.0 0.0 0.5 0.0 5.0 NO 300.0 0.95
MAN_STOP

PERT_START
COMMENT Perturbations specification
GM = 398600.4415 [km**3/s**2]
PERT_STOP

OD_START
COMMENT Orbit Determination information
OD_ID OD #10059
OD_PREV_ID OD #10058
OD_EPOCH 2001-11-06T11:17:33
OBS_USED 273
    
```

```
TRACKS_USED  91  
OD_STOP
```

Annex Fig. G-3: OCM example with deployed objects and low-level thrusting maneuver during deployment to make “string-of-pearls” deployment

CCSDS PROPOSED STANDARD FOR ORBIT DATA MESSAGES

```

CCSDS_OCM_VERS = 3.0
CREATION_DATE = 1998-11-06T09:23:57

META_START
ORIGINATOR = JAXA
OBJECT_NAME = GODZILLA 5
INTERNATIONAL_DESIGNATOR = 1998-999A

DEF_EPOCH_TZERO = 1998-12-18T14:28:15.1172
DEF_TIME_SYSTEM = UTC
META_STOP

ORB_START
ORB_BASIS = PREDICTED
ORB_REF_FRAME = TOD
ORB_FRAME_EPOCH = 1998-12-18T14:28:15.1172
ORB_TYPE = CARTPVA
DT=0.000000 2789.6 -280.0 -1746.8 4.73 -2.50 -1.04 0.008 0.001 -0.159
DT=10.000000 2783.4 -308.1 -1877.1 5.19 -2.42 -2.00 0.008 0.001 0.001
DT=20.000000 2776.0 -336.9 -2008.7 5.64 -2.34 -1.95 0.008 0.001 0.159
< intervening data records omitted here >
T=1998-12-18T14:36:35.1172 2164.375 1115.811 -688.131 -3.53328 -2.88452 0.88535
ORB_STOP

ORB_START
ORB_BASIS = DETERMINED_OD
ORB_REF_FRAME = J2000
ORB_TYPE = KPLR
DT=0.000000 6600.0 .03 28.5 50.0 30.0 10.0
DT=10.000000 6600.0 .03 28.5 50.0 30.0 10.1
DT=20.000000 6600.0 .03 28.5 50.0 30.0 10.2
< intervening data records omitted here >
DT=500.000000 6600.0 .03 28.5 50.0 30.0 35.0
ORB_STOP


PHYS_START
COMMENT S/C Physical Characteristics:
DRAG_AREA = 10.00 [m**2]
DRAG_COEFF = 2.300
MASS = 100.0 [kg]
SOLAR_RAD_AREA = 4.00
SOLAR_RAD_COEFF = 1.300
PHYS_STOP

MAN_START
COMMENT = 200 s of 10N thrust (in-track transitioning to radial)
COMMENT = w/effic η=0.95, Isp=300s, 5% 1-sigma error
MAN_BASIS = PREDICTED
MAN_IS_ADDITIVE = YES
MAN_PURPOSE = ORBIT_ADJUST
MAN_EOI = MAN_DURA, THR_X, THR_Y, THR_Z, THR_SIGMA, THR_INTERP, THR_ISP, THR EFFIC
MAN_REF_FRAME = RTN
DT=500.0 100.0 0.0 10.0 0.0 5.0 ON 300.0 0.95
DT=600.0 100.0 10.0 0.0 0.0 5.0 OFF 300.0 0.95
MAN_STOP

PERT_START
COMMENT Perturbations specification
GM = 398600.4415 [km**3/s**2]
PERT_STOP

OD_START
COMMENT Orbit Determination information
OD_ID = OD #10059
OD_PREV_ID = OD #10058
OD_EPOCH = 2001-11-06T11:17:33
OBS_USED = 273
TRACKS_USED = 91
OD_STOP
    
```

**Annex Fig. G-4: OCM example with multiple orbit time histories, a maneuver, OD,
Cartesian & Keplerian ephemeris**



CCSDS PROPOSED STANDARD FOR ORBIT DATA MESSAGES

```

CCSDS_OCM_VERS = 3.0

CREATION_DATE = 1998-11-06T09:23:57
ORIGINATOR = JAXA

META_START
OBJECT_NAME = GODZILLA 5
INTERNATIONAL_DESIGNATOR = 1998-999A
DEF_EPOCH_TZERO = 1998-12-18T14:28:15.1172
DEF_TIME_SYSTEM = UTC
META_STOP

ORB_START
COMMENT = GEOCENTRIC, CARTESIAN, EARTH FIXED
CENTER_NAME = EARTH
ORB_REF_FRAME = TOD_EARTH
ORB_FRAME_EPOCH = 1998-12-18T14:28:15.1172
ORB_TYPE = CARTPVA

DT= 0.000000 2789.6 -280.0 -1746.8 4.73 -2.50 -1.04 0.008 0.001 -0.159
DT= 10.000000 2783.4 -308.1 -1877.1 5.19 -2.42 -2.00 0.008 0.001 0.001
DT= 20.000000 2776.0 -336.9 -2008.7 5.64 -2.34 -1.95 0.008 0.001 0.159
< intervening data records omitted here >
DT=500.000000 2164.375 1115.811 -688.131 -3.53328 -2.88452 0.88535
ORB_STOP

PHYS_START
COMMENT S/C Physical Characteristics:
DRAG_AREA = 10.000 [m**2]
DRAG_COEFF = 2.300
MASS = 1913.000 [kg]
SOLAR_RAD_AREA = 10.000 [m**2]
SOLAR_RAD_COEFF = 1.300
PHYS_STOP

COV_START
COV_EPOCH_TZERO = 1998-12-18T14:28:15.1172
COV_REF_FRAME = J2000
COV_TYPE = ADBARV

DT = 10.00
3.331349e-04
4.618927e-04 6.782421e-04
-3.070007e-04 -4.221234e-04 3.231931e-04
-3.349365e-07 -4.686084e-07 2.484949e-07 4.296022e-10
-2.211832e-07 -2.864186e-07 1.798098e-07 2.608899e-10 1.767514e-10
-3.041346e-07 -4.989496e-07 3.540310e-07 1.869263e-10 1.008862e-10 6.224444e-10
< intervening data records omitted here >
T = 1998-12-18T14:31:35.1172
3.442450e-04
4.507816e-04 6.893532e-04
-3.060006e-04 -4.110123e-04 3.342042e-04
-3.238254e-07 -4.575073e-07 2.373838e-07 4.307133e-10
-2.100721e-07 -2.753075e-07 1.687087e-07 2.507788e-10 1.878625e-10
-3.030235e-07 -4.878385e-07 3.430200e-07 1.758152e-10 1.007751e-10 6.224444e-10
COV_STOP

COV_START
COV_EPOCH_TZERO = 1998-12-18T14:31:35.1172
COV_TYPE = EFG
DT = 30.00
3.331349e-04
4.618927e-04 6.782421e-04
-3.070007e-04 -4.221234e-04 3.231931e-04
COV_STOP

PERT_START
COMMENT Perturbations specification
GM = 398600.4415 [km**3/s**2]
PERT_STOP
    
```

Annex Fig. G-5: OCM example with Covariance Matrix

```

CCSDS_OCM_VERS = 3.0
CREATION_DATE = 1998-11-06T09:23:57

META_START
ORIGINATOR = JAXA
OBJECT_NAME = GODZILLA 5
INTERNATIONAL DESIGNATOR = 1998-999A
DEF_EPOCH_TZERO = 1998-12-18T14:28:15.1172
META_STOP

STM_START
COMMENT HERE IS A STATE TRANSITION MATRIX DATA BLOCK:
STM_MAP_MODE = STATE
STM_EPOCH_TZERO = 0.0
STM_ORB_STATE = 2789.6 -280.0 -1746.8 4.73 -2.50 -1.04
STM_REF_FRAME = ICRF3
STM_TYPE = CARTPV

DT = 0.00
1.0 0.0 0.0 0.0 0.0 0.0
0.0 1.0 0.0 0.0 0.0 0.0
0.0 0.0 1.0 0.0 0.0 0.0
0.0 0.0 0.0 1.0 0.0 0.0
0.0 0.0 0.0 0.0 1.0 0.0
0.0 0.0 0.0 0.0 0.0 1.0

< intervening data records omitted here >

DT = 500.00
1.23456 7.89012 3.45678 9.01234 5.67890 1.23456
7.89012 3.45678 9.01234 5.67890 1.23456 7.89012
3.45678 9.01234 5.67890 1.23456 7.89012 3.45678
9.01234 5.67890 1.23456 7.89012 3.45678 9.01234
5.67890 1.23456 7.89012 3.45678 9.01234 5.67890
1.23456 7.89012 3.45678 9.01234 5.67890 1.23456
STM_STOP
    
```

Annex Fig. G-6: OCM example with STM (Cartesian position and velocity elements)

OCM example in XML:

Annex Fig. G-7 contains an example of an Orbit Comprehensive Message in Extensible Markup Language (XML) format.

OCM XML EXAMPLES HERE

Annex Fig. G-7: OCM file example in XML format

ANNEX H

ABBREVIATIONS AND ACRONYMS

(INFORMATIVE)


ASCII	American Standard Code for Information Interchange
CCSDS	Consultative Committee for Space Data Systems
CIO	Celestial Intermediate Origin
CIP	Celestial Intermediate Pole
DSST	Draper Semi-Analytic Satellite Theory
ECI	Earth Centered Inertial
EGM	Earth Gravitational Model, Earth Geopotential Model
EOP	Earth Orientation Parameters
GCRF	Geocentric Celestial Reference Frame
GPS	Global Positioning System
IAU	International Astronomical Union
ICD	Interface Control Document
ICRF	International Celestial Reference Frame
IEC	International Electro-technical Commission
IERS	International Earth Rotation and Reference Systems Service
IIRV	Improved Inter-Range Vector
ISO	International Standards Organization
ITRF	International Terrestrial Reference Frame
ITRS	International Terrestrial Reference System
GRC	Greenwich Rotating Coordinate Frame
J2000	Earth Mean Equator and Equinox of J2000 (Julian Date 2000)
KVN	Keyword = Value Notation

CCSDS PROPOSED STANDARD FOR ORBIT DATA MESSAGES

NORAD	North American Aerospace Defense Command
OD	Orbit Determination
ODM	Orbit Data Message
OES	Optimally-Encompassing Shape
OEM	Orbit Ephemeris Message
OCM	Orbit Comprehensive Message
OMM	Orbit Mean-Elements Message
OPM	Orbit Parameter Message
RTN	Radial, Transverse (along-track) and Normal
S/C	Spacecraft
SGP4	US Air Force Simplified General Perturbations No. 4
SPK	Satellite, Planetary Kernel
TAI	International Atomic Time
TCB	Barycentric Coordinate Time
TCG	Geocentric Coordinate Time
TDB	Barycentric Dynamical Time
TDR	True of Date Rotating
TDT	Terrestrial Dynamical Time (see also 'TT')
TEME	True Equator Mean Equinox
TLE	Two Line Element
TOD	True Equator and Equinox of Date
TT	Terrestrial Dynamical Time (see also 'TDT')
USM	Universal Semi-analytical Method
UTC	Coordinated Universal Time
W3C	World Wide Web Consortium
WGS	World Geodetic System

CCSDS PROPOSED STANDARD FOR ORBIT DATA MESSAGES

XML Extensible Markup Language



ANNEX I

RATIONALE FOR ORBIT DATA MESSAGES

(INFORMATIVE)

II OVERVIEW

This annex presents the rationale behind the design of each message. It may help the application engineer to select a suitable message.

A specification of requirements agreed to by all parties is essential to focus design and to ensure the product meets the needs of the Member Agencies and satellite operators. There are many ways of organizing requirements, but the categorization of requirements is not as important as the agreement to a sufficiently comprehensive set. In this section the requirements are organized into three categories:

- a) **Primary Requirements:** These are the most elementary and necessary requirements. They would exist no matter the context in which the CCSDS is operating, i.e., regardless of pre-existing conditions within the CCSDS, its Member Agencies, or other independent users.
- b) **Heritage Requirements:** These are additional requirements that derive from pre-existing Member Agency or other independent user requirements, conditions or needs. Ultimately these carry the same weight as the Primary Requirements. This Recommended Standard reflects heritage requirements pertaining to some of the CCSDS Areas' home institutions collected during the preparation of the document; it does not speculate on heritage requirements that could arise from other sources. Corrections and/or additions to these requirements are expected during future updates.
- c) **Desirable Characteristics:** These are not requirements, but they are felt to be important or useful features of the Recommended Standard.

12 PRIMARY REQUIREMENTS ACCEPTED BY THE ORBIT DATA MESSAGES

12.1 PRIMARY REQUIREMENTS

#	Requirement	OPM?	OMM?	OEM?	OCM?
P1	Data must be provided in digital form (computer file).	Y	Y	Y	Y
P2	The file specification must not require of the receiving exchange partner the separate application of, or modeling of, spacecraft dynamics or gravitational force models, or integration or propagation.	N	N	Y	Y
P3	The interface must facilitate the receiver of the message to generate a six-component Cartesian state vector (position and velocity) at any required epoch.	Y	Y	Y	Y
P4	State vector information must be provided in a reference frame that is clearly identified and unambiguous.	Y	Y	Y	Y
P5	Identification of the object and the center(s) of motion must be clearly identified and unambiguous.	Y	Y	Y	Y
P6	Time measurements (time stamps, or epochs) must be provided in a commonly used, clearly specified system.	Y	Y	Y	Y
P7	The time bounds of the ephemeris must be unambiguously specified.	N/A	N/A	Y	Y
P8	The Recommended Standard must provide for clear specification of units of measure.	Y	Y	Y	Y
P9	Files must be readily ported between, and useable within, 'all' computational environments in use by Member Agencies.	Y	Y	Y	Y
P10	Files must have means of being uniquely identified and clearly annotated. The file name alone is considered insufficient for this purpose.	Y	Y	Y	Y
P11	File name syntax and length must not violate computer constraints for those computing environments in use by Member Agencies.	Y	Y	Y	Y
P12	A means to convey information about the uncertainty of the state shall be provided.	Y	Y	Y	Y

12.2 HERITAGE REQUIREMENTS

#	Requirement	OPM?	OMM?	OEM?	OCM?
H1	Ephemeris data is reliably convertible into the SPICE SPK (NASA) format (reference [M-6]) and IIRV (NASA) format (reference [M-7]) using a standard, multi-mission, unsupervised pipeline process. A complete ephemeris, not subject to integration or propagation by the customer, must be provided.	N	N	Y	Y
H2	Ephemeris data provided for scheduling or operations (metric predicts) is to be certified by the providing Agency as correct and complete for the intended purpose. The receiving Agency cannot provide evaluation, trajectory propagation or other usability services.	N	N	Y	Y

CCSDS PROPOSED STANDARD FOR ORBIT DATA MESSAGES

H3	The ODM shall provide a mechanism by which messages may be uniquely identified and clearly annotated. Facilitates discussion between the recipient and the message originator, should that be necessary.	N	N	N	Y
H4	The ODM shall provide a mechanism by which maneuvers may be uniquely identified and clearly annotated. Facilitates discussion between the recipient and the message originator, should that be necessary.	N	N	N	Y
H5	The Recommended Standard is, or includes, an ASCII format.	Y	Y	Y	Y
H6	The Recommended Standard does not require software supplied by other Agencies.	Y	N	Y	Y

I2.3 DESIRABLE CHARACTERISTICS

#	Requirement	OPM?	OMM?	OEM?	OCM?
DC1	The Recommended Standard applies to non-traditional objects, such as landers, rovers, balloons, and natural bodies (asteroids, comets).	Y	N	Y	Y
DC2	The Recommended Standard allows state vectors to be provided in other than the traditional J2000 inertial reference frame; one example is the International Astronomical Union (IAU) Mars body-fixed frame. (In such a case, provision or ready availability of supplemental information needed to transform data into a standard frame must be arranged.)	Y	Y	Y	Y
DC3	The Recommended Standard is extensible with no disruption to existing users/uses.	Y	Y	Y	Y
DC4	The Recommended Standard is consistent with, and ideally a part of, ephemeris products and processes used for other space science purposes.	Y	Y	Y	Y
DC5	The Recommended Standard is as consistent as reasonable with any related CCSDS ephemeris Recommended Standards used for earth-to-spacecraft or spacecraft-to-spacecraft applications.	Y	Y	Y	Y

I2.4 APPLICABILITY OF CRITERIA TO MESSAGE OPTIONS

The selection of one particular message will depend on the optimization criteria in the given application. Section I2.5 compares the four recommended messages in terms of the relevant selection criteria identified by the CCSDS:

I2.5 APPLICABILITY OF THE CRITERIA TO ORBIT DATA MESSAGES

Criteria	Definition	Applicable to OPM?	Applicable to OMM?	Applicable to OEM?	Applicable to OCM?
Modeling Fidelity	Permits modeling of any dynamic perturbation to the trajectory.	N	N	Y	Y
Human Readability	Provides easily readable message corresponding to widely used orbit representation.	Y	Y	Y	Y
Remote Body Extensibility	Permits use for assets on remote solar system bodies.	Y	N	Y	Y
Lander/Rover Compatibility	Permits exchange of non-orbit trajectories.	N	N	Y	Y

I3 INCREASING ORBIT PROPAGATION FIDELITY OF AN OPM OR OMM

Some OPM or OMM users may desire/require a higher fidelity propagation of the state vector or Keplerian elements. A higher fidelity technique may be desired/required to minimize inconsistencies in predictions generated by diverse, often operator-unique propagation schemes. Nominally the OPM and OMM are engineered only for low- to medium-fidelity orbit propagation. However, with the inclusion of additional context information, it is possible for users to provide data that could be used to provide a relatively higher fidelity orbit propagation. For this relatively higher fidelity orbit propagation, a much greater amount of ancillary information regarding spacecraft properties and dynamical models should be provided. Higher fidelity orbit propagations may be useful in special studies such as orbit conjunction studies.

Spacecraft orbit determination is a stochastic estimation problem; observations are inherently uncertain, and not all of the phenomena that influence satellite motion are clearly discernible. State vectors and Keplerian elements with their respective covariances are best propagated with models that include the same forces and phenomena that were used for determining the orbit. Including this information in an OPM or OMM allows exchange partners to compare the results of their respective orbit propagations.

With additional context information, the OPM and OMM may be used for assessing mutual physical or electromagnetic interference among Earth-orbiting spacecraft, developing collaborative maneuvers, and propagating the orbits of active satellites, inactive man-made objects, and near-Earth debris fragments. The additional information facilitates dynamic modeling of any user's approach to conservative and non-conservative phenomena.

The primary vehicle for the provision of additional optional ancillary information to be used when propagating an OPM or OMM is the COMMENT mechanism. Alternatively, the 'USER_DEFINED_' keyword prefix may be used, though this usage is not encouraged.

I4 SERVICES RELATED TO THE DIFFERENT ORBIT DATA MESSAGE FORMATS

The different orbit data messages have been distinguished by the self-interpretability of the messages. The different services that can be achieved without special arrangements between users of the CCSDS orbit data messages are listed in table I4.1

I4.1 SERVICES AVAILABLE WITH ORBIT DATA MESSAGES

Service	Definition	Applicable to OPM?	Applicable to OMM?	Applicable to OEM?	Applicable to OCM?
Absolute Orbit Interpretation	State availability at specific times for use in additional computations (geometry, event detection, etc.).	Y	Y	Y	Y
Relative Orbit Interpretation	Trajectory comparison and differencing for events based on the same time source.	Only at time specified at Epoch	Only at time specified at Epoch	Y	Y

ANNEX J

ITEMS FOR AN INTERFACE CONTROL DOCUMENT

(INFORMATIVE)

J1 STANDARD ICD ITEMS

In several places in this document there are references to items which should be specified in an Interface Control Document (ICD) between participants that supplements an exchange of ephemeris data. The ICD should be jointly produced by both participants in a cross-support involving the transfer of ephemeris data. This annex compiles those recommendations into a single section. Although the Orbit Data Messages described in this document may at times be used in situations in which participants have not negotiated interface control documents (ICD), ICDs based on the content specified in this Recommended Standard should be developed and negotiated whenever possible.¹

Item	Section
1) Definition of orbit accuracy requirements pertaining to any particular ODM.	1.2
2) Method of physically exchanging ODMs (transmission).	1.2, 3.1, 4.1, 5.1, 6.1
3) Whether the ASCII format of the ODM will be KVN or XML.	1.1
4) OPM, OMM, OEM and/or OCM file-naming conventions.	3.1, 4.1, 5.1, 6.1
5) Situations where the OBJECT_ID is not published in the UN OOSA index (reference [2]).	3.2.3, 4.2.3, 5.2.3, 6.2.3
6) Detailed description of any user defined parameters used.	3.2.4, 4.2.4, 6.2.12
7) If floating point numbers in extended-single or extended-double precision are to be used, then discussion of implementation specific attributes is required in an ICD between exchange partners.	7.5.5
8) Specific OPM, OMM OEM and/or OCM version numbers that will be exchanged.	7.8.1
9) Specific information security interoperability provisions that apply between agencies.	Annex N
10) Exceptions for Timing System, Reference Frame, Orbital Element, and Covariance-Related keywords that are not drawn from ANNEX B (and the SANA registry, [Annex B, reference B-1])	Annex B

¹ EDITOR'S COMMENT: The greater the amount of material which must be specified via ICD, the lesser the utility/benefit of the ODM (custom programming may be required to tailor software for each ICD).

CCSDS PROPOSED STANDARD FOR ORBIT DATA MESSAGES

Item	Section
11) Interpretation of TIME_SYSTEM specified as SCLK, if to be exchanged, and how to transform them to a standardized time system. The ICD should specify that in using the timing format rules specified in 7.5.10, elapsed days are to be used relative time, with year starting at zero.	Annex B

ANNEX K

CHANGES IN ODM VERSION 3

(INFORMATIVE)

This annex lists the differences between ODM 2.0 and ODM 3.0. The differences are divided into those which affect the content of one or more of the orbit data messages, and those which only affect the document.

Note that changes to previous versions of the ODM can be found in CCSDS Silver Book CCSDS 502.0-B-2-S, published November 2009.

K1 CHANGES IN THE MESSAGES

1. The Orbit Comprehensive Message (OCM) was added to provide better support for ISO Technical Committee 20, Subcommittee 14 objectives (see section 4).
- 2.

K2 CHANGES IN THE DOCUMENT

1. A new CCSDS repository for normative keyword values for navigation messages has been created at the SANA Registry of Organizations, accessible on the Internet at: <https://sanaregistry.org/r/organizations>. See Annex B for details on the affected keywords and links to the content. This content replaces non-normative references to the Navigation Green Book (reference [M-1]). The CCSDS documents are not allowed to make normative references to non-normative documents.
2. Several annexes were added. Some are required by CCSDS rule changes, and some are for the provision of supplementary material.
3. Examples for OPM, OMM, and OEM that formerly appeared in Sections 3, 4, and 5 respectively have been moved to Informative Annexes.
4. The "Checklist ICD" that was added in ODM Version 2 has been removed. It is replaced by the material that can be specified in the Orbit Comprehensive Message.

ANNEX L

5. SECURITY, SANA, AND PATENT CONSIDERATIONS SECURITY CONSIDERATIONS

L1.1 ANALYSIS OF SECURITY CONSIDERATIONS

This Section presents the results of an analysis of security considerations applied to the technologies specified in this Recommended Standard.

L1.2 CONSEQUENCES OF NOT APPLYING SECURITY TO THE TECHNOLOGY

The consequences of not applying security to the systems and networks on which this Recommended Standard is implemented could include potential loss, corruption, and theft of data. Because these messages are used in preparing pointing and frequency predicts used during spacecraft commanding, and may also be used in collision avoidance analyses, the consequences of not applying security to the systems and networks on which this Recommended Standard is implemented could include compromise or loss of the mission if malicious tampering of a particularly severe nature occurs.

L1.3 POTENTIAL THREATS AND ATTACK SCENARIOS

Potential threats or attack scenarios include, but are not limited to, (a) unauthorized access to the programs/processes that generate and interpret the messages, (b) unauthorized access to the messages during transmission between exchange partners and (c) modification of the messages between partners. Protection from unauthorized access during transmission is especially important if the mission utilizes open ground networks, such as the Internet, to provide ground-station connectivity for the exchange of data formatted in compliance with this Recommended Standard. It is strongly recommended that potential threats or attack scenarios applicable to the systems and networks on which this Recommended Standard is implemented be addressed by the management of those systems and networks.

L1.4 DATA PRIVACY

Privacy of data formatted in compliance with the specifications of this Recommended Standard should be assured by the systems and networks on which this Recommended Standard is implemented.

L1.5 DATA INTEGRITY

Integrity of data formatted in compliance with the specifications of this Recommended Standard should be assured by the systems and networks on which this Recommended Standard is implemented.

L1.6 AUTHENTICATION OF COMMUNICATING ENTITIES

Authentication of communicating entities involved in the transport of data which complies with the specifications of this Recommended Standard should be provided by the systems and networks on which this Recommended Standard is implemented.

L1.7 DATA TRANSFER BETWEEN COMMUNICATING ENTITIES

The transfer of data formatted in compliance with this Recommended Standard between communicating entities should be accomplished via secure mechanisms approved by the Information Technology Security functionaries of exchange participants.

L1.8 CONTROL OF ACCESS TO RESOURCES

Control of access to resources should be managed by the systems upon which originator formatting and recipient processing are performed.

L1.9 AUDITING OF RESOURCE USAGE

Auditing of resource usage should be handled by the management of systems and networks on which this Recommended Standard is implemented.

L1.10 UNAUTHORIZED ACCESS

Unauthorized access to the programs/processes that generate and interpret the messages should be prohibited in order to minimize potential threats and attack scenarios.

L1.11 DATA SECURITY IMPLEMENTATION SPECIFICS

Specific information-security interoperability provisions that may apply between agencies and other independent users involved in an exchange of data formatted in compliance with this Recommended Standard could be specified in an ICD.

L2 SANA CONSIDERATIONS

The following ODM-related items items have been registered with the SANA Operator.

- The ODM XML schema (see Section 8).

The following normative ODM elements shall be selected from the SANA registry:

- ODM Message ORIGINATORs;
- Spacecraft identifiers;
- Reference Frame Center and Third-Body Perturbations;
- Time Systems
- Reference Frames (inertial, quasi-inertial, orbit-relative, spacecraft & attitude frames);

- Orbital element set and covariance column definitions;

The registration rule for new entries in the SANA registry is the approval of new requests by the CCSDS Area or Working Group responsible for the maintenance of the ODM at the time of the request. New requests for this registry should be sent to SANA (<mailto:info@sanaregistry.org>).

L3 PATENT CONSIDERATIONS

The recommendations of this document have no patent issues.

ANNEX M

INFORMATIVE REFERENCES

(INFORMATIVE)

- [M-1] *Navigation Data—Definitions and Conventions*. Report Concerning Space Data System Standards, CCSDS 500.0-G-3. Green Book. Issue 3. Washington, D.C.: CCSDS, May 2010
- [M-2] *Organization and Processes for the Consultative Committee for Space Data Systems*. CCSDS A02.1-Y-4. Yellow Book. Issue 4. Washington, D.C.: CCSDS, April 2014.
- [M-3] “CelesTrak.” Center for Space Standards & Innovation (CSSI). <<http://celestrak.com/>>
- [M-4] David A. Vallado, et al. “Revisiting Spacetrack Report #3.” In *Proceedings of the AIAA/AAS Astrodynamics Specialist Conference and Exhibit* (21–24 August 2006, Keystone, Colorado). AIAA 2006-6753. Reston, Virginia: AIAA, 2006. <<http://www.centerforspace.com/downloads/files/pubs/AIAA-2006-6753.pdf>>
- [M-5] *Attitude Data Messages*. Recommendation for Space Data System Standards, CCSDS 504.0-B-1. Blue Book. Issue 1. Washington, D.C.: CCSDS, May 2008.
- [M-6] “Documentation.” *SPICE: NASA’s Solar System Exploration Ancillary Information System*. Navigation and Ancillary Information Facility (NAIF). <<http://naif.jpl.nasa.gov/naif/documentation.html>>
- [M-7] *Ground Network Tracking and Acquisition Data Handbook*. 453-HNDK-GN. Greenbelt, Maryland: Goddard Space Flight Center, May 2007, http://imbrium.mit.edu/LRORS/DOCUMENT/453_HDBK_GN.PDF.
- [M-8] Oltrogge, D.L., et al, “Ephemeris Requirements for Space Situational Awareness,” AAS 11-151, February 2011.
- [M-9] David A. Vallado, et al. *Fundamentals of Astrodynamics and Applications, 4th Ed.*, Microcosm Press and Springer, ISBN 978-1881883180.
- [M-10] Williams, J.G., Boggs, D.H., and Folkner, W.M., “DE430 Lunar Orbit, Physical Librations, and Surface Coordinates,” Jet Propulsion Laboratory Interoffice Memorandum, IOM 335-JW,DB,WF-20130722-016, 22 July 2013, https://naif.jpl.nasa.gov/pub/naif/generic_kernels/spk/planets/de430_moon_coord.pdf.
- [M-11] Jet Propulsion Laboratory, “Lunar Constants and Models Document,” JPL D-32296, 23 Sept 2005, https://www.hq.nasa.gov/alsj/lunar_cmd_2005_jpl_d32296.pdf.

CCSDS PROPOSED STANDARD FOR ORBIT DATA MESSAGES

- [M-12] Oltrogge, D.L., North, P. and Nicholls, M., “Multi-Phenomenology Observation Network Evaluation Tool (MONET),” AMOS 2015 Space Situational Awareness Conference, Maui, HI, September 2015.
- [M-13] Newhall, X.X., “Numerical Representation of Planetary Ephemerides,” *Celestial Mechanics*, vol. 45, pp. 305-310, 1989.
- [M-14] Hoots, F.R. and France, R.G., “Hybrid Ephemeris Compression Model,” *Astrodynamics Specialist Conference*, AAS 97-690, http://www.space-flight.org/AAS_meetings/1997_astro/abstracts/97-690.html.
- [M-15] Braun, V. and Klinkrad, H., “Providing Orbital Information for Objects in Earth Orbits as Chebyshev Polynomials,” in *IAC-15, 2015*, IAC-15,A6,7,9,x31103.
- [M-16] Woodburn, J., & Tanygin, S. (2002). Position covariance visualization. *AIAA/AAS Astrodynamics Specialist Conference and Exhibit*, Monterey, California, https://www.researchgate.net/profile/Sergei_Tanygin/publication/265672620_Attitude_Covariance_Visualization/links/54d578b10cf25013d02b3819/Attitude-Covariance-Visualization.pdf.
- [M-17] ESA Space Debris DISCOS Database website, <https://discosweb.esoc.esa.int/group/guest/statistics>.